The thermodynamics package*

Karl D. Hammond
kaiserkarl31@yahoo.com

2026/10/26

Abstract

A package, thermodynamics, is defined that makes typesetting quantities found in thermodynamics texts relatively simple. The commands are flexible and intended to be relatively intuitive. It handles several sets of notation for total, specific, and molar quantities; allows changes between symbols (e.g., A vs. F for Helmholtz free energy); and greatly simplifies the typesetting of symbols and partial derivatives commonly encountered in mixture thermodynamics. Changes of one's notes from one textbook to another can be achieved relatively easily by changing package options.

1 Introduction

The purpose of this package is to simplify the typesetting of equations in thermodynamics, particularly chemical engineering thermodynamics, which are often cumbersome to enter. For example, consider the following equation:

$$d\underline{U} = \left(\frac{\partial \underline{U}}{\partial \underline{S}}\right)_{\underline{V},\vec{n}} d\underline{S} + \left(\frac{\partial \underline{U}}{\partial \underline{V}}\right)_{\underline{S},\vec{n}} d\underline{V} + \sum_{i=1}^{C} \left(\frac{\partial \underline{U}}{\partial n_i}\right)_{\underline{S},\underline{V},n_{j\neq i}} dn_i. \tag{1}$$

This equation is pretty basic, and equations like it occur all the time in thermodynamics. Without this package, you might typeset it like this:

```
\[ d\underline{U} =
   \left(\frac{\partial\underline{U}}
             {\partial\underline{S}}\right)_{\underline{V},\vec{n}}
   d\underline{S}
 + \left(\frac{\partial\underline{U}}
             {\partial\underline{V}}\right)_{\underline{S},\vec{n}}
   d\underline{V}
 + \sum_{i=1}^C \left(\frac{\partial\underline{U}}
     {\partial n_i}\right)_{\underline{S},\underline{V},n_{j\neq i}}
   dn_i. \]
```

This is a lot of code, and even then the output is slightly clunky:

$$d\underline{U} = \left(\frac{\partial \underline{U}}{\partial \underline{S}}\right)_{\underline{V},\vec{n}} d\underline{S} + \left(\frac{\partial \underline{U}}{\partial \underline{V}}\right)_{\underline{S},\vec{n}} d\underline{V} + \sum_{i=1}^{C} \left(\frac{\partial \underline{U}}{\partial n_i}\right)_{\underline{S},\underline{V},n_{j\neq i}} dn_i.$$

*This document corresponds to thermodynamics v2.05, dated 2026/10/26.

It is also frustratingly difficult to change one's notes or handouts from one textbook that uses, say, n_1 to denote moles of component 1 to another textbook that uses N_1 for the same quantity, or perhaps denotes the total internal energy as U or U^t rather than $\underline{U}$. For example, if you wanted it to be

$$dU = \left(\frac{\partial U}{\partial S}\right)_{V,N_1,\ldots,N_C} dS + \left(\frac{\partial U}{\partial V}\right)_{S,N_1,\ldots,N_C} dV + \sum_{i=1}^{C} \left(\frac{\partial U}{\partial N_i}\right)_{S,V,N_1,\ldots,[N_i],\ldots,N_C} dN_i.$$

without changing any of your code—to update it across all handouts, exams, and homework sets after changing textbooks, say—you would be out of luck (or in for a lot of work).

With this package, you could reduce the code to typeset this equation to

```
\begin{equation}
   d\Ut = \Partial*{\Ut}{\St}{\Vt,\allNs} d\St
     + \Partial*{\Ut}{\Vt}{\St,\allNs} d\Vt
     + \sumall_i \Partial*{\Ut}{\Nt_i}{\St,\Vt,\allNsbut{i}} d\Nt_i
\end{equation}
```

and it will render similarly to Equation (1), including the shortened underscores and negative kerning. If you later decide to change the notation such that extensive properties are not underlined, you can do that without changing any of your code (just change a package option). Similarly, if you want $\vec{n}$ replaced by $n_1, \ldots, n_C$, you can do that with a package option, too.

The package handles second derivatives, too. For example,

```
\[ \Partial*{\Hm}{T}{P} = T\Partial*{\Sm}{T}{P}
                        = -T\PartialSecond*{\Gm}{T}{P} = \cP \]
```

renders (using the default options)

$$\left(\frac{\partial H}{\partial T}\right)_P = T\left(\frac{\partial S}{\partial T}\right)_P = -T\left(\frac{\partial^2 G}{\partial T^2}\right)_P = C_P.$$

Similarly, macros are defined for mixed second partial derivatives that allow things like

```
\[ \Partial*{\Gpm_i}{P}{T,\allNs}
  = \PartialMixSecond*{\Gt}{P}{\Nt_i}{T,\allNsbut{i}}
  = \PartialMixSecond*{\Gt}{\Nt_i}{P}{T,\allNsbut{i}}
  = \Partial*{\Vt}{\Nt_i}{T,P,\allNsbut{i}} = \Vpm_i \],
```

which renders

$$\left(\frac{\partial \overline{G_i}}{\partial P}\right)_{T,\vec{n}} = \left(\frac{\partial^2 \underline{G}}{\partial P \partial n_i}\right)_{T,n_{j\neq i}} = \left(\frac{\partial^2 \underline{G}}{\partial n_i \partial P}\right)_{T,n_{j\neq i}} = \left(\frac{\partial \underline{V}}{\partial n_i}\right)_{T,P,n_{j\neq i}} = \overline{V_i}$$

using the defaults.

2 Using the Package

There are three categories of macros defined in this package: macros that produce symbols (or groups of them), macros that typeset derivatives, and macros that are used internally that the user need not know about. There are also several environments that allow the user to change notation temporarily.

2.1 Predefined Symbols

The macros used to produce symbols fall into five categories: extensive properties, molar properties, specific properties (i.e., per unit mass), partial molar properties, and shortcut macros (e.g., macros for the heat capacities, saturation pressure, and so forth). The macros corresponding to extensive, molar, and specific properties are shown in Table 1. Examples using the enthalpy are

`\Ht` `\Hm` `\Hs` `\Hpm`

```
\[ \Ht \quad \Hm \quad \Hs \quad \Hpm_i. \]
```

Using the default package options, the above renders as

$$\underline{H} \quad H \quad \hat{H} \quad \overline{H_i}.$$

In addition, the properties in Table 2 are defined for convenience. A more comprehensive list, including how those properties are represented in the various textbook-related options supported by this package, are shown in Appendix A.

`\Ut` `\Um`

How these symbols are rendered can be customized by package options. As long as the user consistently uses `\Ut` to render the total internal energy, `\Um` to render the molar internal energy, and so forth, switching notation from, say, $\underline{U}$ to U^t for extensive properties is trivial.

`\cP` `\cV` `\cPt` `\cVt` `\cPs` `\cVs` `\cPpm` `\cVpm`

The heat capacities (see Table 2) are generally assumed to be molar (e.g., `\cP` is interpreted to be the molar heat capacity). To get the specific heat capacities, the macros `\cPs` and `\cVs` are provided, which by default render as $\hat{C}_P$ and $\hat{C}_V$, respectively. There are also extensive versions, so `\cPt` and `\cVt` will render as $\underline{C}_P$ and $\underline{C}_V$, respectively. Note that `\cP` and friends require you to surround `\text` with brackets. For example, `\cP_i^\text{A}` will not work, nor will `\cP^\text{A}_i`; you need to use `\cP_i^{\text{A}}` and `\cP^{\text{A}}_i`. Using `\cP^\IG_i` will work as expected.

You can also get partial molar heat capacities via `\cPpm` and `\cVpm`, though the latter's mathematical definition is a bit hard to wrap one's head around:

```
\[ \cVpm_i = \Partial*{\cVt}{\Nt_i}{T,P,\allNsbut{i}}
           = \frac{\partial}{\partial\Nt_i}
             \left[ -T\PartialSecond{\Ft}{T}{\Vt,\allNs}
             \right]_{T,P,\allNsbut{i}} \]
```

yields

$$\overline{C_{V,i}} = \left(\frac{\partial \underline{C}_V}{\partial n_i}\right)_{T,P,n_{j\neq i}} = \frac{\partial}{\partial n_i}\left[-T\left(\frac{\partial^2 \underline{A}}{\partial T^2}\right)_{\underline{V},\vec{n}}\right]_{T,P,n_{j\neq i}}.$$

2.2 Partial Molar Properties

`\Upm` `\Vpm`

Partial molar quantities are defined with the suffix `pm`. For example, `\Upm` refers to the partial molar internal energy. There are two options for how to enter partial molar quantities: as commands or as super/subscripts. For example,

```
\[ \Upm{i} \quad \Upm[\IG]{i} \quad \Vpm_i \quad \Vpm^\IG_i \]
```

will typeset as

$$\overline{U_i} \quad \overline{U_i^{\mathrm{IG}}} \quad \overline{V_i} \quad \overline{V_i^{\mathrm{IG}}}.$$

There are also partial molar heat capacities available via the macros `\cPpm` and `\cVpm`.

Important: The `\text` command defined by the amstext package is usually robust

Table 1. Commands defined in this package to represent extensive thermodynamic quantities and their molar and specific analogs. These macros should be used even if the symbol the user wishes to use does not match the command used (e.g., `\Ft` for total Helmholtz free energy even if it ends up being set as $\underline{A}$).

					Excess				Residual (Departure)			
Property	Total	Molar	Specific	Partial Molar	T	M	S	PM	T	M	S	PM
Heat	`\Qt`	`\Qm`	`\Qs`									
Work	`\Wt`	`\Wm`	`\Ws`									
Total energy	`\Et`	`\Em`	`\Es`	`\Epm`	`\EEt`	`\EE`	`\EEs`	`\EEpm`	`\ERt`	`\ER`	`\ERs`	`\ERpm`
Internal energy	`\Ut`	`\Um`	`\Us`	`\Upm`	`\UEt`	`\UE`	`\UEs`	`\UEpm`	`\URt`	`\UR`	`\URs`	`\URpm`
Enthalpy	`\Ht`	`\Hm`	`\Hs`	`\Hpm`	`\HEt`	`\HE`	`\HEs`	`\HEpm`	`\HRt`	`\HR`	`\HRs`	`\HRpm`
Entropy	`\St`	`\Sm`	`\Ss`	`\Spm`	`\SEt`	`\SE`	`\SEs`	`\SEpm`	`\SRt`	`\SR`	`\SRs`	`\SRpm`
Volume	`\Vt`	`\Vm`	`\Vs`	`\Vpm`	`\VEt`	`\VE`	`\VEs`	`\VEpm`	`\VRt`	`\VR`	`\VRs`	`\VRpm`
Helmholtz free energy	`\Ft`	`\Fm`	`\Fs`	`\Fpm`	`\FEt`	`\FE`	`\FEs`	`\FEpm`	`\FRt`	`\FR`	`\FRs`	`\FRpm`
Gibbs free energy	`\Gt`	`\Gm`	`\Gs`	`\Gpm`	`\GEt`	`\GE`	`\GEs`	`\GEpm`	`\GRt`	`\GR`	`\GRs`	`\GRpm`
Surface area	`\At`	`\Am`	`\As`	`\Apm`								
Grand potential[a]	`\Lt`	`\Lm`	`\Ls`	`\Lpm`	`\LEt`	`\LE`	`\LEs`	`\LEpm`	`\LRt`	`\LR`	`\LRs`	`\LRpm`
Moles	`\Nt`											

[a] The grand potential, $\underline{\Omega}(T, \underline{V}, \mu_1, \ldots, \mu_C) = \underline{U} - T\underline{S} - \sum_{i=1}^{C} \mu_i n_i$, is also called the Landau free energy by some authors.

enough that something like `\Um^\text{L}` will work as expected, without additional braces. This does *not* work for partial molar properties; for example, `\Hpm^\text{L}_i` will produce an error, as will `\Hpm_i^\text{L}`. The expression `\Hpm_i^{\text{L}}` will work as expected.

`\partialmolar` New partial molar properties can be defined for any "simple" symbol using the `\partialmolar` macro. "Simple" means it has no subscripts or superscripts. For example, the macro for the partial molar Gibbs free energy is effectively defined via `\Gpm` the macro

```
\NewDocumentCommand{\Gpm}{}{\partialmolar{G}}.
```

A list of pre-defined macros for total, molar, specific, and partial molar quantities commonly used in thermodynamics is included in Table 1.

2.3 Defining New Properties

`\NewExtensiveProperty` Users can create new properties using a family of commands. Typically, a user would want to define at least the total, molar, and specific properties, which can be accomplished by the `\NewExtensiveProperty` command. For example,

```
\NewExtensiveProperty{J}{K}
```

would define the commands `\Jt`, `\Jm`, and `\Js`, which would produce (using the default package options) the symbols $\underline{K}$, K, and $\hat{K}$, respectively.

`\NewPartialMolarProperty` Partial molar properties can be created either with the `\partialmolar` macro directly as described above or with `\NewPartialMolarProperty`, which has the same argument style as `\NewExtensiveProperty`.

`\NewExcessProperty` `\NewResidualProperty` Similarly, one can define commands for the total, molar, and specific excess properties using `\NewExcessProperty` in a similar manner, and similar commands for the residual properties with `\NewResidualProperty`.

`\NewThermodynamicProperty` It is common that a user wants the total, molar, specific, and partial molar commands for a new symbol, as well as excess and residual (departure) properties for each

Table 2. Convenience macros and their default symbols. These are generally "smart": for example, `\cP_i` renders as $C_{P,i}$, as expected, and `\cP_i^\std` renders as $C^\circ_{P,i}$, also as expected. You can also reverse it: `\cP^\std_i` becomes $C^\circ_{P,i}$.

Name	Macro	Sym.	Definition	Base Symbol Macro
Isobaric heat capacity	`\cP`[a]	C_P	$T\left(\frac{\partial S}{\partial T}\right)_P$	`\heatcapacitysymbol`
Isochoric heat capacity	`\cV`[a]	C_V	$T\left(\frac{\partial S}{\partial T}\right)_V$	`\heatcapacitysymbol`
Isothermal compressibility	`\kappaT`	κ_T	$-\frac{1}{V}\left(\frac{\partial V}{\partial P}\right)_T$	`\compressibilitysymbol`
Isentropic compressibility	`\kappaS`	κ_S	$-\frac{1}{V}\left(\frac{\partial V}{\partial P}\right)_S$	`\compressibilitysymbol`
Isobaric expansivity	`\alphaP`	α_P	$\frac{1}{V}\left(\frac{\partial V}{\partial T}\right)_P$	`\expansivitysymbol`
Isentropic expansivity	`\alphaS`	α_S	$\frac{1}{V}\left(\frac{\partial V}{\partial T}\right)_S$	`\expansivitysymbol`
Joule–Thomson coeff.	`\muJT`	μ_{JT}	$\left(\frac{\partial T}{\partial P}\right)_H$	`\JTsymbol`
Pure fugacity	`\fpure`	f	ϕP	
Saturation fugacity	`\fsat`	f^{sat}	$\phi^{\text{sat}} P^{\text{sat}}$	`\sat`
Mixture fugacity	`\fmix`	$\hat{f}$	$\hat{f}_i = x_i \hat{\phi}_i P$	
Pure fugacity coefficient	`\phipure`	ϕ	$\phi_i = \exp\left(\frac{1}{RT}\int_0^P V_i(T,p) - \frac{RT}{p}\,dp\right)$	
Saturation fugacity coeff.	`\phisat`	ϕ^{sat}	$\phi(T, P^{\text{sat}})$	`\sat`
Mixture fugacity coeff.	`\phimix`	$\hat{\phi}$	$\hat{\phi}_i = \exp\left(\frac{1}{RT}\int_0^P \overline{V}_i(T,p,\vec{x}) - \frac{RT}{p}\,dp\right)$	
Absolute activity	`\actabs`	λ	$\lambda_i = \exp(\mu_i/RT)$	
Relative activity	`\actrel`	a	$a_i = \exp\left(\frac{\mu_i - \mu_i^\circ}{RT}\right) = \frac{\hat{f}_i(T,P,\vec{x})}{f_i^\circ(T)}$	
Henry's constant (rational)	`\Henryrat`	h	$\gamma_i^\infty f_i$	
Henry's constant (molal)	`\Henrymol`	$\mathcal{H}$	$M_s \gamma_i^\infty f_i$	
Rational activity coeff.	`\gammarat`	γ^*	γ/γ^∞	
Molal activity coeff.	`\gammamol`	$\gamma^\square$	$x_s\gamma/\gamma^\infty$	
Saturation pressure	`\Psat`[b]	P^{sat}		`\sat`
Standard state	`\std`[c]			
Standard pressure	`\Pstd`	P°		`\std`
Standard molality	`\Cstd`	C°		`\std`
Standard fugacity	`\fstd`	f°	$f_i^\circ = f_i(T, P^\circ, x^\circ)$	`\std`
Standard chemical potential	`\mustd`	μ°	$\mu_i^\circ = \mu(T, P^\circ, x^\circ)$	`\std`
Change on mixing	`\Deltamix`[d]	ΔM_{mix}	$M - \sum_{i=1}^C x_i M_i$	`\mixing`
Change on reaction	`\Deltarxn`[d]	ΔM_{rxn}	$\sum_{i=1}^C \nu_i M_i$	`\reaction`
Change on melting	`\Deltafus`[d]	ΔM^{fus}	$M^L - M^S$	`\fusion`
Change on boiling	`\Deltavap`[d]	ΔM^{vap}	$M^V - M^L$	`\vaporization`
Change on subliming	`\Deltasub`[d]	ΔM^{sub}	$M^V - M^S$	`\sublimation`
Electric potential	`\Epot`	E	$-n_e \mathscr{F} \Delta G_{\text{rxn}}$	
Extent of reaction	`\xrxn`	ξ		

[a] Extensive and specific (per-unit-mass) versions are available as `\cPt` and `\cPs`, respectively, with similar macros for the isochoric heat capacity.

[b] `\Pvap` is a synonym for `\Psat`; if you want it to produce P^{vap}, you should redefine the `\sat` macro

[c] Typical usage: `$\Deltarxn\Gm^\std = \sumall_i\Deltaf\Gm^\std_i` yielding $\Delta G^\circ_{\text{rxn}} = \sum_{i=1}^C \Delta G^\circ_{f,i}$

[d] The usual usage would be something like `$\Deltamix\Vm^\IGM = 0$`.

case. Users can define such properties—common examples are $\underline{B}$ and $\underline{M}$ to represent uncommon or arbitrary properties—by using `\NewThermodynamicProperty`, which calls all four of the aforementioned declarations on the same command/symbol combinations. For example,

```
\NewThermodynamicProperty{B}{B}
```

defines the commands `\Bt`, `\Bm`, `\Bs`, and `\Bpm`, which define the total, molar, specific, and partial molar properties, respectively. It also defines `\BEt`, `\BE`, `\BEs`, and `\BEpm` for the corresponding excess properties, and `\BRt`, `\BR`, `\BRs`, and `\BRpm` for residual (departure) properties. These produce, respectively, $\underline{B}, B, \hat{B}, \overline{B}_i, \underline{B}^E, B^E, \hat{B}^E, \overline{B}_i^E, \underline{B}^R, B^R, \hat{B}^R$, and $\overline{B}_i^R$ using the defaults.

2.4 Other Predefined Symbols and Modifiers

There are a number of predefined symbols and modifiers. While these symbols could be defined or used without these macros, such use is not recommended: changing package options will result in inconsistencies if these macros are not used.

2.4.1 Heat Capacities, Compressibilities, and Expansivities

`\cP` `\cV` `\kappaS` `\kappaT` `\alphaP` `\alphaS`

The isobaric and isochoric heat capacities are produced with `\cP` and `\cV`, respectively. Four other measurable quantities are defined: the isothermal and isentropic compressibilities, `\kappaT` and `\kappaS`, respectively; and the isobaric and isentropic volume expansivities, `\alphaP` and `\alphaS`, respectively. Some textbooks use β instead of α for the volume expansivity to differentiate it from the *linear* expansivity; this can be changed by redefining `\expansivitysymbol`, which is done automatically by some of the package options that create notation specific to a particular textbook.

2.4.2 Joule–Thomson Coefficient

`\muJT`

The Joule–Thomson coefficient is produced with `\muJT`, which by default is rendered μ_{JT}. Some books call this coefficient α_H; this is handled automatically for books of which the package author is aware.

2.4.3 Chemical Potentials

`\mu` `\muit`

The chemical potential is always produced by the macro `\mu`. Some textbook-related options use μ instead of μ for chemical potential; if so, the macro `\muit` will always produce μ.

2.4.4 Fugacities and Fugacity Coefficients

`\fpure` `\fmix` `\phipure` `\phimix`

Different textbooks use different variations on the symbol f for fugacity, so it is recommended to use the macro `\fpure` to denote the pure-component fugacity and `\fmix` to denote the mixture fugacity. Similarly, the pure-component fugacity coefficient should be generated with `\phipure`, and that in a mixture should be `\phimix`.

For example, the following markup is an example of a common equation in mixture thermodynamics:

```
\[ \fmix_j = x_j \phimix_j P = x_j \gamma_j \fpure_j
           = x_j \gamma_j \phipure_j P. \]
```

With the default package options, this produces

$$\hat{f_j} = x_j\hat{\phi}_j P = x_j\gamma_j f_j = x_j\gamma_j\phi_j P.$$

With the `Thompson` package option, however, the same markup produces

$$\widehat{f_j} = x_j\widehat{\phi}_j P = x_j\gamma_j f_j^\bullet = x_j\gamma_j\phi_j^\bullet P.$$

Similarly, the `Prausnitz` package option causes it to generate

$$f_j = x_j\phi_j P = x_j\gamma_j f_{\text{pure},j} = x_j\gamma_j\phi_{\text{pure},j} P,$$

and the `Sandler` option causes it to generate

$$\bar{f_j} = x_j\bar{\phi}_j P = x_j\gamma_j f_j = x_j\gamma_j\phi_j P.$$

2.4.5 Activity Coefficients and Henry's Constants

`\gamma` `\gammait` `\gammarat` `\gammamol` `\Henryrat` `\Henrymol`

The activity coefficient based on the Lewis–Randall rule can be generated with `\gamma`, as usual. The symbol `\gammait` is provided just in case `\gamma` has been redefined by a package option and you want to use the original symbol for some reason. The Henry's Law activity coefficients should be produced with `\gammarat` (rational basis) and `\gammamol` (molal basis). There are also macros to generate the Henry's law constants for both the rational basis (`\Henryrat`) and the molal basis (`\Henrymol`). These are interrelated:

```
\[ \fmix_i = x_i \gamma_i \fpure_i = x_i \gammarat_i \Henryrat_i
           = C_i \gammamol_i \Henrymol_i \]
```

produces

$$\hat{f_i} = x_i\gamma_i f_i = x_i\gamma_i^* h_i = C_i\gamma_i^\square \mathcal{H}_i$$

using the default options. These symbols can be customized either directly or by using package options. For example, the `TesterModell` package option changes the equation above to

$$\hat{f_i} = x_i\gamma_i f_i = x_i\gamma_i^{**} f_i^{**} = C_i\gamma_i^* f_i^*$$

without any changes in markup.

Note that some books (e.g., `ElliottLira`) prefer the atmospheric chemistry convention for the molal basis, namely

$$\hat{f_i} = x_i\gamma_i f_i = x_i\gamma_i^* h_i = C_i\gamma_i^\square / K_{H,i}$$

(that is, using $1/K_{H,i}$ in place of $\mathcal{H}_i$). Unfortunately, this makes it impossible to change symbols without any edits to markup, so this convention is *not* supported by this package.

2.4.6 Saturation Properties

`\Psat` `\Pvap` `\fsat` `\phisat`

The saturation pressure is generated with `\Psat`. The macro `\Pvap` is an alias for `\Psat`. The fugacity and fugacity coefficient at saturation are accessed via `\fsat` and `\phisat`, respectively. Package options can be used to change some of these to match the notation of specific textbooks.

`\sat`

The `\sat` macro is used "behind the scenes" as part of `\Psat`, `\fsat`, and `\phisat`, which produce P^{sat}, f^{sat}, and ϕ^{sat}, respectively (using the defaults). If you wanted to redefine them to be P^{vap}, f^{vap}, and ϕ^{vap}, you could simply redefine `\sat` with `\RenewDocumentCommand{\sat}{}{{\text{vap}}}`. This is done automatically using package option `Sandler`.

2.4.7 Standard States and Chemical Reactions

\std \Pstd \Cstd \fstd \mustd

The symbol ∘ (\circ) is used by default for standard states. This is intended to be easy to change should the user want to replace P° with $P^\ominus$, say. This is accessed via the \std macro. The macro \Pstd is defined as P^\std for convenience to denote standard pressure, \Cstd is defined as C^\std to denote standard molality, \fstd is defined for standard fugacities, and \mustd is defined for standard chemical potentials so as to ease implementation across textbooks.

The usual usage would be something like this:

```
\[ \Deltarxn\Gm = \sumall_i \nu_i \mu_i = \sumall_i \left[ \nu_i \mustd_i
   + \nu_i RT \log\left(\frac{\fmix_i}{\fstd_i}\right) \right]
   = \Deltarxn\Gm^\std + RT \log\left[\prodall_i a_i^{\nu_i} \right] \],
```

which produces

$$\Delta G_{\text{rxn}} = \sum_{i=1}^{C} \nu_i \mu_i = \sum_{i=1}^{C} \left[\nu_i \mu_i^\circ + \nu_i RT \log\left(\frac{\hat{f}_i}{f_i^\circ}\right)\right] = \Delta G_{\text{rxn}}^\circ + RT \log\left[\prod_{i=1}^{C} a_i^{\nu_i}\right]$$

with the default settings.

The extent of reaction is generated by the macro \xrxn, which by default is printed as ξ.

2.4.8 Changes on Mixing, Reaction, Fusion, Vaporization, and Sublimation

\Deltamix

Mixing properties are handled via the \Deltamix macro, and are used as in the following example:

```
\[ \Deltamix\Gm = \Gm - \sumall_i x_i \Gm_i
                = \Deltamix\Hm - T\Deltamix\Sm \],
```

which yields, using the default options,

$$\Delta G_{\text{mix}} = G - \sum_{i=1}^{C} x_i G_i = \Delta H_{\text{mix}} - T\Delta S_{\text{mix}}$$

Some textbooks (Sandler, Thompson) choose to typeset these with the word "mix" *before* the symbol, which is handled automatically by this package. The macro \mixing determines how the change in mixing label is rendered; the default is {\text{mix}}.

\mixing

\Deltafus \Deltasub \Deltavap

The commands \Deltafus, \Deltasub, and \Deltavap typeset changes due to fusion (melting), sublimation (subliming), and vaporization (boiling), respectively. Their use is straightforward, viz.,

```
\[ \Deltasub\Hm = \Hm^V - \Hm^S = \Hm^V - \Hm^L + (\Hm^L - \Hm^S)
                = \Deltafus\Hm + \Deltavap\Hm \],
```

yielding

$$\Delta H^{\text{sub}} = H^V - H^S = H^V - H^L + (H^L - H^S) = \Delta H^{\text{fus}} + \Delta H^{\text{vap}}$$

with the default options. Note that some textbooks (e.g., Sandler) typeset these quantities quite differently; this is handled automatically. Other textbooks (e.g., Koretsky) typeset them as subscripts; this is also handled automatically.

\Deltaf \Deltarxn

The macros \Deltaf and \Deltarxn are intended to typeset the enthalpy or free energy of formation and reaction, respectively. For example,

```
\[ \Deltarxn\Hm^\std = \sumall_i \nu_i \Deltaf\Hm_i^\std \]
```

results in

$$\Delta H^\circ_{\text{rxn}} = \sum_{i=1}^{C} \nu_i \Delta H^\circ_{f,i}.$$

It is not anticipated that this command will be combined with something like a heat capacity, which already has a (potentially double) subscript, but as there is no "formation" heat capacity, that should not present a problem.

2.5 Residual and Excess Properties

\UR
\URt
\URs
\URpm
\UE
\UEt
\UEs
\UEpm
\excess
\residual

Additional macros are defined that make it easy to typeset the residual (also called "departure") and excess total, molar, specific, and partial molar properties. These macros follow the same pattern: `\UR`, `\URt`, `\URs`, and `\URpm` typeset the molar, total, specific, and partial molar residual internal energies, respectively, and by default expand to U^R, $\underline{U}^R$, $\hat{U}^R$, and $\overline{U}_i^R$ (the last is called as `\URpm{i}` or `\URpm_i`). Similarly, `\UE`, `\UEt`, `\UEs`, and `\UEpm` typeset the corresponding excess properties. The first character of the macros for other properties follow the same pattern as in Table 1.

The R and E characters are generated by the macros `\residual` and `\excess`, respectively. These macros can be redefined; for example, if you want `\SE`, which normally produces S^E, to give you S^{EX}—and let's be honest, who doesn't want that?[1]—then you can redefine it with

```
\RenewDocumentCommand{\excess}{}{{EX}},
```

or possibly

```
\RenewDocumentCommand{\excess}{}{{\mathrm{EX}}}
```

or even

```
\RenewDocumentCommand{\excess}{}{\text{EX}},
```

which cause `\SE` to expand to S^{EX}, S^{EX}, and S^{EX}, respectively.

It is generally possible to use superscripts with the excess or residual properties; in the event this fails, the `\excess` and `\residual` macros can be used directly, viz.,

```
\begin{gather*}
  \HE^\std = \Hm^{\excess,\std} = \HE(T,\Pstd)
    = \HR(T,\Pstd) - \HR^\IS(T,\Pstd) = \HR^\std - \HR^{\IS,\std} \\
\RenewDocumentCommand{\excess}{{EX}}
  \HE^\std = \Hm^{\excess,\std} = \HE(T,\Pstd)
    = \HR(T,\Pstd) - \HR^\IS(T,\Pstd)
\end{gather*},
```

which yields

$$H^{E,\circ} = H^{E,\circ} = H^E(T,P^\circ) = H^R(T,P^\circ) - H^{R,\mathrm{IS}}(T,P^\circ) = H^{R,\circ} - H^{R,\mathrm{IS},\circ}$$
$$H^{EX,\circ} = H^{EX,\circ} = H^{EX}(T,P^\circ) = H^R(T,P^\circ) - H^{R,\mathrm{IS}}(T,P^\circ)$$

using the default options.

2.6 Partial Derivatives

\Partial
\Partial*

Partial derivatives are easily rendered using the \Partial command. There is a starred form (\Partial*) that additionally adjusts the spacing after the closing symbol to remove some of the space, anticipating that the following binary operator will overhang the subscripts. Compare the following:

```
\[ \Partial{\Hm}{T}{P} = \cP \qquad \Partial*{\Hm}{T}{P} = \cP \],
```

which yields

$$\left(\frac{\partial H}{\partial T}\right)_P = C_P \qquad \left(\frac{\partial H}{\partial T}\right)_P = C_P.$$

\Partialinline

Inline first derivatives[2] can be entered the same way; compare:

```
\[ \Partial*{\Hm}{T}{P} = \Partialinline{\Hm}{T}{P}
     = T\Partial{\Sm}{T}{P} \],
```

which results in

$$\left(\frac{\partial H}{\partial T}\right)_P = (\partial H/\partial T)_P = T\,(\partial S/\partial T)_P\,.$$

There is no need for an inline starred form, as the subscripts do not extend far enough below the baseline.

2.6.1 Second-Order Partial Derivatives

\PartialSecond
\PartialSecond*
\PartialMixSecond
\PartialMixSecond*

Second partial derivatives and mixed-second partial derivatives are typeset with the commands \PartialSecond and \PartialMixSecond, respectively. Like the first-order variety, these also have starred versions that remove the space immediately following the closing symbols, anticipating that the equals sign or other binary operator following the derivative will overhang the elements held constant. For example,

```
\[ \Vpm_i = \Partial*{\Vt}{\Nt_i}{T,P,\allNsbut{i}}
          = \PartialMixSecond*{\Gt}{\Nt_i}{P}{T,\allNsbut{i}}
          = \PartialMixSecond*{\Gt}{P}{\Nt_i}{T,\allNsbut{i}}
          = \Partial{\Gpm_i}{P}{T,\allNs} \]
```

looks like

$$\overline{V}_i = \left(\frac{\partial V}{\partial n_i}\right)_{T,P,n_{j\neq i}} = \left(\frac{\partial^2 G}{\partial n_i \partial P}\right)_{T,n_{j\neq i}} = \left(\frac{\partial^2 G}{\partial P \partial n_i}\right)_{T,n_{j\neq i}} = \left(\frac{\partial \overline{G}_i}{\partial P}\right)_{T,\vec{n}}.$$

\PartialSecondinline
\PartialMixSecondinline

Inline versions[2] of second-order derivatives are handled with \PartialSecondinline and \PartialMixSecondinline, viz.,

```
\begin{equation}
  \Vpm_i = \Partialinline{\Vt}{\Nt_i}{T,P,\allNsbut{i}}
         = \PartialMixSecondinline{\Gt}{\Nt_i}{P}{T,\allNsbut{i}}
         = \PartialMixSecondinline{\Gt}{P}{\Nt_i}{T,\allNsbut{i}}
         = \Partialinline{\Gpm_i}{P}{T,\allNs}
\end{equation}
```

[1] You knew that joke was coming.

[2] The "inline" versions of partial derivatives are "sticky": if you issue \Partialinline or its second-order equivalents anywhere in a line, all subsequent \Partial and \Partial[Mix]Second macros on the same line (technically, anywhere in the same TEX "group") will expand inline as well. To prevent this, enclose your \Partialinline and associated arguments in its own group (i.e., {\Partialinline...}).

looks like

$$\overline{V}_i = \left(\partial \underline{V} \middle/ \partial n_i\right)_{T,P,n_{j\neq i}} = \left(\partial^2 \underline{G} \middle/ \partial n_i \partial P\right)_{T,n_{j\neq i}} = \left(\partial^2 \underline{G} \middle/ \partial P \partial n_i\right)_{T,n_{j\neq i}} = \left(\partial \overline{G}_i \middle/ \partial P\right)_{T,\vec{n}} \tag{2}$$

with the default options.

2.6.2 Delimiter Sizing

\PartialBigg
\PartialSecondBigg
\PartialMixSecondBigg
\Partialbigg
\PartialSecondbigg
\PartialMixSecondbigg

There are instances (such as the line above) when \Partial causes parentheses that are slightly too tall but do not need to be—particularly when partial molar properties, specific quantities, or fugacities are involved. The macro \PartialBigg uses amsmath's \Biggl and \Biggr macros in place of \left and \right to size the delimiters accordingly; \Partialbigg uses \biggl and \biggr in a similar fashion. For example, compare the following:

```
\[ \Vpm_i = \Partial*{\Vt}{\Nt_i}{T,P,\allNsbut{i}}
          = \Partial*{\Gpm_i}{P}{T,\allNs}
          = \PartialBigg*{\Gpm_i}{P}{T,\allNs}
          = RT\Partial*{\log\fmix_i}{P}{T,\allNs}
          = RT\PartialBigg*{\log\fmix_i}{P}{T,\allNs}
          = RT\Partialbigg{\log\fmix_i}{P}{T,\allNs} \],
```

which typesets as

$$\overline{V}_i = \left(\frac{\partial \underline{V}}{\partial n_i}\right)_{T,P,n_{j\neq i}} = \left(\frac{\partial \overline{G}_i}{\partial P}\right)_{T,\vec{n}} = \left(\frac{\partial \overline{G}_i}{\partial P}\right)_{T,\vec{n}} = RT\left(\frac{\partial \log \hat{f}_i}{\partial P}\right)_{T,\vec{n}} = RT\left(\frac{\partial \log \hat{f}_i}{\partial P}\right)_{T,\vec{n}} = RT\left(\frac{\partial \log \hat{f}_i}{\partial P}\right)_{T,\vec{n}}.$$

Note that a similar effect—possibly with other side effects—can be achieved with amsmath's \smash command, which has the effect of removing all vertical space associated with a particular character. Observe:

```
\[ \Vpm_i = \Partial*{\Vt}{\Nt_i}{T,P,\allNsbut{i}}
          = \Partial{\smash{\Gpm_i}}{P}{T,\allNs} \]
```

produces

$$\overline{V}_i = \left(\frac{\partial \underline{V}}{\partial n_i}\right)_{T,P,n_{j\neq i}} = \left(\frac{\partial \overline{G}_i}{\partial P}\right)_{T,\vec{n}}.$$

\Partialinlinetext
\PartialSecondinlinetext
\PartialMixSecondinlinetext

Similarly, there are times when \Partialinline causes parentheses that are too big for inline text, and they do not need to be—particularly for symbols with overlines, underlines, or other decorations. In this case, the macros \Partialinlinetext, \PartialSecondinlinetext, and \PartialMixSecondinlinetext come in handy; using these macros like so,

```
\[ \Vpm_i = \Partialinlinetext{\Vt}{\Nt_i}{T,P,\allNsbut{i}}
          = \PartialMixSecondinlinetext{\Gt}{\Nt_i}{P}{T,\allNsbut{i}}
          = \PartialMixSecondinlinetext{\Gt}{P}{\Nt_i}{T,\allNsbut{i}}
          = \Partialinlinetext{\Gpm_i}{P}{T,\allNs} \],
```

Equation (2) looks like

$$\overline{V}_i = (\partial \underline{V}/\partial n_i)_{T,P,n_{j\neq i}} = (\partial^2 \underline{G}/\partial n_i \partial P)_{T,n_{j\neq i}} = (\partial^2 \underline{G}/\partial P \partial n_i)_{T,n_{j\neq i}} = (\partial \overline{G}_i/\partial P)_{T,\vec{n}}.$$

2.6.3 Higher-Order Derivatives

It is possible to "fake" higher-order derivatives via some trickery. For example,

```
\[ \cPpm_i = T\Partial*{\Spm_i}{T}{P,\allXs}
           = T\PartialMixSecond*{\St}{T}{\Nt_i}{P,\allNsbut{i}}
           = -T\Partial{^3\Gt}{T^2\partial\Nt_i}{P,\allNsbut{i}} \]
```

gives

$$\overline{C_{P,i}} = T\left(\frac{\partial \overline{S_i}}{\partial T}\right)_{P,\vec{x}} = T\left(\frac{\partial^2 \underline{S}}{\partial T \partial n_i}\right)_{P,n_{j\neq i}} = -T\left(\frac{\partial^3 \underline{G}}{\partial T^2 \partial n_i}\right)_{P,n_{j\neq i}},$$

which is probably pretty close to what you wanted. Using this trickery with the package option `nosubscripts` will not work, and the use of third- and higher-order derivatives with this package should generally be considered unsupported.

2.7 Holding Constant the Number of Moles of Several Species

`\allNs`
`\allNsbut`
`\allmus`
`\allmusbut`
`\allXs`
`\allXsbut`
`\allYs`
`\allYsbut`
`\allMs`
`\allMsbut`
`\allWs`
`\allWsbut`

It is common in thermodynamics to use notation such as

$$\overline{V_k} = \left(\frac{\partial \underline{V}}{\partial n_k}\right)_{T,P,n_{j\neq k}},$$

or perhaps

$$\overline{V_k} = \left(\frac{\partial \underline{V}}{\partial n_k}\right)_{T,P,n_1,\ldots,[n_k],\ldots,n_C}$$

or

$$\overline{V_k} = \left(\frac{\partial \underline{V}}{\partial n_k}\right)_{T,P,n_j[k]},$$

to mean partial derivatives that hold the number of moles of each species constant *except* the one being changed. Similarly, a property determined with all mole fractions held constant might be written

$$C_P = \left(\frac{\partial H}{\partial T}\right)_{P,\vec{x}},$$

or perhaps

$$C_P = \left(\frac{\partial H}{\partial T}\right)_{P,x_1,\ldots,x_C}.$$

There are several macros that standardize such constructs. The `\allNs` macro expands to something meaning the number of moles of all species; by default, this is $\vec{n}$ (package option `moles-index`), but can be changed to $n_1, \ldots, n_C$ using the package option `moles-range`. Similarly, the macros `\allmus` and `\allmusbut` do the same but with n replaced by μ, and `\allMsbut` is the same with m instead of n. There are analogous macros for mole fractions, namely `\allXs` and `\allXsbut` for x and `\allYs` and `\allYsbut` for y, as well as `\allWs` and `\allWsbut` for mass fractions—these implicitly assume that all mole or mass fractions *except* the last are used as variables. These macros all take an optional argument; for example,

```
\[ \Partial{\Ht}{\Nt_1}{T,P,\allNsbut{1}} =
   \Partial{\Ht}{\Nt_1}{T,P,\allNsbut[m]{1}} = \Hpm_1 \]
```

typesets as

$$\left(\frac{\partial \overline{H}}{\partial n_1}\right)_{T,P,n_{j\neq 1}} = \left(\frac{\partial \overline{H}}{\partial n_1}\right)_{T,P,n_{m\neq 1}} = \overline{H_1}.$$

Similarly,

```
\[ \Partial{\Hm}{x_i}{T,P,\allXsbut{i}}
  = \Partial{\Hm}{x_i}{T,P,\allXsbut[m]{i}}
  = \Hpm_i - \Hpm_\ncomponents \]
```

becomes

$$\left(\frac{\partial H}{\partial x_i}\right)_{T,P,x_{j\neq i,C}} = \left(\frac{\partial H}{\partial x_i}\right)_{T,P,x_{m\neq i,C}} = \overline{H_i} - \overline{H_C}.$$

Users must supply their own redefinitions if they wish to hold something other than `\ncomponents` constant in addition to the argument for mole and mass fractions. Using the `moles-range` package option, for which `\allXsbut{k}` expands to $x_1, \ldots, [x_k], \ldots, x_{C-1}$ rather than $x_{j\neq k,C}$, the optional argument is ignored.

The optional argument to `\allNs` and similar commands is ignored when using the default options; it is relevant for package options that redefine `\allNs` to make N_i, for example; in this case, one can enter `\allNs[j]` to make TEX render N_j instead of N_i. This is useful if you are using i somewhere else in the equation.

`\allbut` `\allbutlastand`

Users can define new "all but" macros using the `\allbut` and `\allbutlastand` commands. For example,

```
\NewDocumentCommand{\allNsbut}{O{j} m}{\allbut[#1]{#2}{\Nt}}
\NewDocumentCommand{\allXsbut}{O{j} m}{\allbutlastand[#1]{#2}{x}}
```

are the definitions of `\allNsbut` and `\allXsbut`, respectively.

2.8 Jacobians

`\Jacobian` `\Jacobiandet` `\Jacobianbmatrix` `\Jacobianpmatrix`

The Jacobian determinant is often denoted with Leibnitz-like notation, viz.,

```
\[ \Jacobian{K,L}{X,Y} = \Jacobiandet{K,L}{X,Y} \],
```

which produces (assuming the amsmath package has been loaded)

$$\frac{\partial(K,L)}{\partial(X,Y)} = \begin{vmatrix} \left(\frac{\partial K}{\partial X}\right)_Y & \left(\frac{\partial K}{\partial Y}\right)_X \\ \left(\frac{\partial L}{\partial X}\right)_Y & \left(\frac{\partial L}{\partial Y}\right)_X \end{vmatrix}.$$

There are two optional arguments to `\Jacobiandet`. The first will be pre-pended before every element of the matrix (typically `\textstyle` or `\displaystyle`); the second is the extra spacing added between rows (default is 1.25 ex for text-style fractions and 2.75 ex for display-style fractions). More than two variables can be specified, viz.,

```
\[ \Jacobian{K,L,M}{X,Y,Z}
  = \Jacobiandet[\displaystyle][3ex]{K,L,M}{X,Y,Z} \]
```

will produce

$$\frac{\partial(K,L,M)}{\partial(X,Y,Z)} = \begin{vmatrix} \left(\frac{\partial K}{\partial X}\right)_{Y,Z} & \left(\frac{\partial K}{\partial Y}\right)_{X,Z} & \left(\frac{\partial K}{\partial Z}\right)_{X,Y} \\ \left(\frac{\partial L}{\partial X}\right)_{Y,Z} & \left(\frac{\partial L}{\partial Y}\right)_{X,Z} & \left(\frac{\partial L}{\partial Z}\right)_{X,Y} \\ \left(\frac{\partial M}{\partial X}\right)_{Y,Z} & \left(\frac{\partial M}{\partial Y}\right)_{X,Z} & \left(\frac{\partial M}{\partial Z}\right)_{X,Y} \end{vmatrix}.$$

The `\Jacobiandet` macro will understand implied multicomponent Jacobians, too, namely,

```
\[ \Jacobian{f_1,\dots,f_m}{x_1,\dots,x_m} =
   \Jacobiandet{f_1,\dots,f_m}{x_1,\dots,x_m} \]
```

typesets as

$$\frac{\partial(f_1,\dots,f_m)}{\partial(x_1,\dots,x_m)} = \begin{vmatrix} \left(\frac{\partial f_1}{\partial x_1}\right)_{x_{j\neq 1}} & \cdots & \left(\frac{\partial f_1}{\partial x_m}\right)_{x_{j\neq m}} \\ \vdots & \ddots & \vdots \\ \left(\frac{\partial f_m}{\partial x_1}\right)_{x_{j\neq 1}} & \cdots & \left(\frac{\partial f_m}{\partial x_m}\right)_{x_{j\neq m}} \end{vmatrix}.$$

If the option `moles-range` or the `thermomolesrange` environment is used, the same code produces

$$\frac{\partial(f_1,\dots,f_m)}{\partial(x_1,\dots,x_m)} = \begin{vmatrix} \left(\frac{\partial f_1}{\partial x_1}\right)_{x_2,\dots,x_m} & \cdots & \left(\frac{\partial f_1}{\partial x_m}\right)_{x_1,\dots,x_{m-1}} \\ \vdots & \ddots & \vdots \\ \left(\frac{\partial f_m}{\partial x_1}\right)_{x_2,\dots,x_m} & \cdots & \left(\frac{\partial f_m}{\partial x_m}\right)_{x_1,\dots,x_{m-1}} \end{vmatrix}.$$

The commands `\Jacobianbmatrix` and `\Jacobianpmatrix` are also provided for users who want the Jacobian *matrix* instead of its determinant. These typeset the Jacobian matrix with brackets or parentheses, respectively. For example,

```
\[ \Jacobianpmatrix{f_1,\dots,f_m}{x_1,\dots,x_n} =
   \Jacobianbmatrix{f_1,\dots,f_m}{x_1,\dots,x_n} \]
```

typesets as

$$\begin{pmatrix} \left(\frac{\partial f_1}{\partial x_1}\right)_{x_{j\neq 1}} & \cdots & \left(\frac{\partial f_1}{\partial x_n}\right)_{x_{j\neq n}} \\ \vdots & \ddots & \vdots \\ \left(\frac{\partial f_m}{\partial x_1}\right)_{x_{j\neq 1}} & \cdots & \left(\frac{\partial f_m}{\partial x_n}\right)_{x_{j\neq n}} \end{pmatrix} = \begin{bmatrix} \left(\frac{\partial f_1}{\partial x_1}\right)_{x_{j\neq 1}} & \cdots & \left(\frac{\partial f_1}{\partial x_n}\right)_{x_{j\neq n}} \\ \vdots & \ddots & \vdots \\ \left(\frac{\partial f_m}{\partial x_1}\right)_{x_{j\neq 1}} & \cdots & \left(\frac{\partial f_m}{\partial x_n}\right)_{x_{j\neq n}} \end{bmatrix}$$

2.9 Sums and Products

`\sumall` `\sumallbutlast` `\prodall`

It is common to require sums and products such as

$$\sum_{i=1}^{C} x_i = 1 \quad \text{or} \quad x_C = 1 - \sum_{i=1}^{C-1} x_i \quad \text{or} \quad \underline{G} = \sum_{j=1}^{C} \mu_j n_j \quad \text{and} \quad K = \prod_{k=1}^{C} a_k^{\nu_k}.$$

This package defines shortcuts to typeset such terms thus:

```
\[ \sumall_i x_i = 1 \quad \text{or} \quad
   x_\ncomponents = 1 - \sumallbutlast_i x_i \quad \text{or} \quad
   \Gt = \sumall_j \mu_j\Nt_j \quad \text{and} \quad
   K = \prodall_k a_k^{\nu_k} \].
```

The symbol C can be changed by redefining the expandable macro `\ncomponents`. This is done automatically by some package options (e.g., `TesterModell` changes it to n; `Sandler` changes it to C; `Thompson` changes it to c).

3 Loading the Package

To load the package with the defaults enabled, load it the usual way:

```
\usepackage{thermodynamics}
```

The package options loaded by default are `EUAGHan`, `subscripts`, `parentheses`, `intensive-plain`, and `moles-index`. These define, respectively, the default symbols to use for total energy, internal energy, Helmholtz free energy, and so forth; the manner of writing partial derivatives; the delimiters around partial derivatives; the manner of denoting extensive, molar, and specific properties; and the manner of writing the number of moles of all or most species in partial derivatives. The default behavior can be altered by options in the following section.

3.1 Package Options

There are three categories of options: options that affect which symbols are used, options that affect how symbols are decorated, and options that affect how partial derivatives are displayed. These are presented in turn.

3.1.1 Options that Change Symbol Sets

There are several options that choose the set of symbols to use for total energy, internal energy, Helmholtz free energy, and so forth. These are summarized in Table 3. The default is `EUAGHan`.

Using `EUAGHan` (the default), we might use the following markup:

```
\[ \Ft = \Ut - T\St = -P\Vt + \sumall_i \mu_i \Nt_i + \sigma \At
   \qquad \Hm = \Um + P\Vm \qquad \Et = \Ut + \frac12 mv^2 \],
```

which would look like

$$\underline{A} = \underline{U} - T\underline{S} = -P\underline{V} + \sum_{i=1}^{C} \mu_i n_i + \sigma \underline{a} \qquad H = U + PV \qquad \underline{E} = \underline{U} + \frac{1}{2}mv^2$$

Using the `EEFGHAN` option, the same markup would yield

$$\underline{F} = \underline{E} - T\underline{S} = -P\underline{V} + \sum_{i=1}^{C} \mu_i N_i + \sigma \underline{A} \qquad H = U + PV \qquad \underline{\mathcal{E}} = \underline{E} + \frac{1}{2}mv^2.$$

Table 3. Options controlling which symbols to use by default. The macros `\Et`, `\Ut`, `\Ft`, `\Gt`, `\Ht`, `\At`, and `\Nt` represent the total energy, internal energy, Helmholtz free energy, Gibbs free energy, enthalpy, surface area, and number of moles, respectively. Symbols are shown as they would appear with the (default) option `intensive-plain`.

Option	`\Et`	`\Ut`	`\Ft`	`\Gt`	`\Ht`	`\At`	`\Nt`
`EUAGHan`	$\underline{E}$	$\underline{U}$	$\underline{A}$	$\underline{G}$	$\underline{H}$	a	n
`EUAGHaN`	$\underline{E}$	$\underline{U}$	$\underline{A}$	$\underline{G}$	$\underline{H}$	a	N
`EUHAGan`	(synonym for `EUAGHan`)						
`EUHAGaN`	(synonym for `EUAGHaN`)						
`EUFGHAn`	$\underline{E}$	$\underline{U}$	$\underline{F}$	$\underline{G}$	$\underline{H}$	$\underline{A}$	n
`EUFGHAN`	$\underline{E}$	$\underline{U}$	$\underline{F}$	$\underline{G}$	$\underline{H}$	$\underline{A}$	N
`EEFGHAn`	$\underline{\mathcal{E}}$	$\underline{E}$	$\underline{F}$	$\underline{G}$	$\underline{H}$	$\underline{A}$	n
`EEFGHAN`	$\underline{\mathcal{E}}$	$\underline{E}$	$\underline{F}$	$\underline{G}$	$\underline{H}$	$\underline{A}$	N
`EEFGHan`	$\underline{\mathcal{E}}$	$\underline{E}$	$\underline{F}$	$\underline{G}$	$\underline{H}$	a	n
`EEFGHaN`	$\underline{\mathcal{E}}$	$\underline{E}$	$\underline{F}$	$\underline{G}$	$\underline{H}$	a	N
`EEAGHaN`	$\underline{\mathcal{E}}$	$\underline{E}$	$\underline{A}$	$\underline{G}$	$\underline{H}$	a	N
`EEAGHAN`	$\underline{\mathcal{E}}$	$\underline{E}$	$\underline{A}$	$\underline{G}$	$\underline{H}$	$\underline{\mathcal{A}}$	n
`EUAGHAN`	$\underline{E}$	$\underline{U}$	$\underline{A}$	$\underline{G}$	$\underline{H}$	$\underline{\mathcal{A}}$	N
`EUFGHan`	$\underline{E}$	$\underline{U}$	$\underline{F}$	$\underline{G}$	$\underline{H}$	a	n
`EUFGHaN`	$\underline{E}$	$\underline{U}$	$\underline{F}$	$\underline{G}$	$\underline{H}$	a	N

3.1.2 Options for Extensive vs. Molar Properties

There are four sets of notation that define how extensive properties are represented, as shown in Table 4. The default is `intensive-plain`, which (using the volume as an example) represents the total, molar, specific, and partial molar volumes, respectively, as $\underline{V}$, V, $\hat{V}$, and $\overline{V}_j$.

For example, the definition of the partial molar enthalpy would be different depending on which set of notation is used. The markup

```
\[ \Hpm_i = \Partial*{\Ht}{\Nt_i}{T,P,\allNsbut{i}}
          = \Partial{\Nt\Hm}{\Nt_i}{T,P,\allNsbut{i}} \]
```

yields the following, depending on the package option loaded:

$$\overline{H_i} = \left(\frac{\partial \underline{H}}{\partial n_i}\right)_{T,P,n_{j\neq i}} = \left(\frac{\partial nH}{\partial n_i}\right)_{T,P,n_{j\neq i}} \qquad \texttt{intensive-plain}$$

$$\overline{H_i} = \left(\frac{\partial H}{\partial n_i}\right)_{T,P,n_{j\neq i}} = \left(\frac{\partial n\underline{H}}{\partial n_i}\right)_{T,P,n_{j\neq i}} \qquad \texttt{extensive-plain}$$

$$\overline{H_i} = \left(\frac{\partial H^t}{\partial n_i}\right)_{T,P,n_{j\neq i}} = \left(\frac{\partial nH}{\partial n_i}\right)_{T,P,n_{j\neq i}} \qquad \texttt{extensive-superscript}$$

$$\overline{h_i} = \left(\frac{\partial H}{\partial n_i}\right)_{T,P,n_{j\neq i}} = \left(\frac{\partial nh}{\partial n_i}\right)_{T,P,n_{j\neq i}} \qquad \texttt{intensive-lowercase}$$

The use of `intensive-lowercase` is strongly discouraged.

Note that the number of moles can be changed from n to N via the options in the previous section.

`thermointensiveplain` (*env.*)
`thermoextensiveplain` (*env.*)
`thermoextensivesuperscript` (*env.*)
`thermointensivelowercase` (*env.*)

It is possible to change notation locally, though there are very, very few good reasons why you would want to do this in a regular document—normally, one would use the corresponding package options. The environment `thermointensiveplain`

Table 4. Notation sets that can be set using the options `intensive-plain` (the default), `extensive-plain`, `extensive-superscript`, and `intensive-lowercase`.

Option	`\Vt`	`\Vm`	`\Vs`	`\Vpm_i`
`intensive-plain`	$\underline{V}$	V	$\hat{V}$	$\overline{V}_i$
`extensive-plain`	V	$\underline{V}$	$\hat{V}$	$\overline{V}_i$
`extensive-superscript`	V^t	V	$\hat{V}$	$\overline{V}_i$
`intensive-lowercase`	V	v	$\hat{v}$	$\overline{v}_i$

means `\St` will become $\underline{S}$ and `\Sm` will become S in the text. Similarly, inside `thermoextensiveplain`, `\St` will become S and `\Sm` will become $\underline{S}$. Inside `thermoextensivesuperscript`, `\St` will become S^t and `\Sm` will be S; and inside `thermointensivesubscript`, `\St` will be S and `\Sm` will be s.

3.1.3 Options Affecting Partial Molar Properties

There are two options that change how partial molar properties are typeset. For option `longpm` (the default), the subscript and superscript are considered part of the symbol, producing something like $\overline{H}_i^E$. The option `shortpm` makes it display as $\overline{H}_i^E$. The `shortpm` option is the default for several textbook-related options.

`thermolongpm` (*env.*)
`thermoshortpm` (*env.*)

It is possible to change partial molar notation locally—this could be useful if you have a very, very long superscript or subscript and the default option looks silly, say. The environment `thermolongpm` sets the style equivalent to the `longpm` option, while the `thermoshortpm` environment sets the local style equivalent to the `shortpm` option. For example,

```
\[ \Spm_i = \Spm_i^\IGM + \SRpm_i
    \begin{thermoshortpm}
      = \Spm_i^\IGM + \SRpm_i
    \end{thermoshortpm} \]
```

produces

$$\overline{S}_i = \overline{S_i^{\mathrm{IGM}}} + \overline{S}_i^R = \overline{S}_i^{\mathrm{IGM}} + \overline{S}_i^R,$$

assuming the default options are loaded.

3.1.4 Options Affecting Partial Derivatives

There are several options that change how partial derivatives are rendered. First are the options that affect the delimiters. We will use the following code as an example:

```
\[ \Partial*{\Vm}{T}{P} = \PartialMixSecond{\Gm}{T}{P}{}
                        = \PartialMixSecond{\Gm}{P}{T}{}
                        = -\Partial{\Sm}{P}{T}. \]
```

Using the `parentheses` option (the default), this gives

$$\left(\frac{\partial V}{\partial T}\right)_P = \left(\frac{\partial^2 G}{\partial T \partial P}\right) = \left(\frac{\partial^2 G}{\partial P \partial T}\right) = -\left(\frac{\partial S}{\partial P}\right)_T.$$

The option `brackets` changes the output to

$$\left[\frac{\partial V}{\partial T}\right]_P = \left[\frac{\partial^2 G}{\partial T \partial P}\right] = \left[\frac{\partial^2 G}{\partial P \partial T}\right] = -\left[\frac{\partial S}{\partial P}\right]_T .$$

The option `bar` changes the output to

$$\left.\frac{\partial V}{\partial T}\right|_P = \frac{\partial^2 G}{\partial T \partial P} = \frac{\partial^2 G}{\partial P \partial T} = -\left.\frac{\partial S}{\partial P}\right|_T .$$

The option `plain-derivatives` eliminates all delimiters; this forces the `nosubscripts` option. The output in this case is

$$\frac{\partial V(T,P)}{\partial T} = \frac{\partial^2 G(T,P)}{\partial T \partial P} = \frac{\partial^2 G(T,P)}{\partial P \partial T} = -\frac{\partial S(T,P)}{\partial P} .$$

Accompanying the `plain-derivatives` option is the `nosubscripts` option, which overrides the default option `subscripts`. This option makes partial derivatives such as

$$\left(\frac{\partial V}{\partial P}\right)_T \qquad (\texttt{subscripts} \text{ option}),$$

and instead renders them

$$\left(\frac{\partial V(T,P)}{\partial P}\right) \qquad (\texttt{nosubscripts} \text{ option}).$$

Combined with `plain-derivatives`, this would give

$$\frac{\partial V(T,P)}{\partial P} \qquad (\texttt{nosubscripts} \text{ and } \texttt{plain-derivatives} \text{ options}).$$

The variables are sorted into an order defined by an internal constant, meaning T will always be listed before P. The order by default is in the order that terms appear in the fundamental equations, that is,

$$\begin{aligned} d\underline{U} &= T\,d\underline{S} - P\,d\underline{V} + \mu\,dn \\ d\underline{H} &= T\,d\underline{S} + \underline{V}\,dP + \mu\,dn \\ d\underline{A} &= -\underline{S}\,dT - P\,d\underline{V} + \mu\,dn \\ &\vdots \\ d\underline{\Omega} &= -\underline{S}\,dT - P\,d\underline{V} - n\,d\mu, \end{aligned}$$

with the exception that subscripted variables are (currently) not sortable. If `\Nt_i` or some similar construct appears as a variable and `\allNsbut{i}` appears in the held-constant list, the package will assume that the argument list *should* contain all of the mole numbers. Symbols without subscripts that are not in the fundamental equation or one of its variants are sorted in alphabetical order.

`thermoparentheses` (*env.*)
`thermobrackets` (*env.*)
`thermobraces` (*env.*)
`thermobar` (*env.*)
`thermoplain` (*env.*)
`thermosubscripts` (*env.*)
`thermoNOsubscripts` (*env.*)

If you want to use parentheses *locally*, even though your overall document uses another delimiter, the `thermoparentheses` environment will do that. Similarly, `thermobrackets` will temporarily switch to brackets, `thermobar` will temporarily switch to a tailing vertical bar, and `thermoplain` will remove delimiters altogether.

The environments `thermosubscripts` and `thermoNOsubscripts` force the use or disuse of subscripts, respectively.

Table 5. Illustration of the `moles-index` and `moles-range` options and their effects on `\allNs` and `\allNsbut`.

Macro[a]	`moles-index`	`moles-range`
`\allNs`	$\vec{n}$	$n_1,\ldots,n_C$
`\allNsbut{1}`	$n_{j\neq 1}$	$n_2,\ldots,n_C$
`\allNsbut{i}`	$n_{j\neq i}$	$n_1,\ldots,[n_i],\ldots,n_C$
`\allNsbut{j}`	$n_{k\neq j}$	$n_1,\ldots,[n_j],\ldots,n_C$
`\allNsbut{\ncomponents}`	$n_{j\neq C}$	$n_1,\ldots,n_{C-1}$
`\allNsbut[k]{i}`	$n_{k\neq i}$	$n_1,\ldots,[n_i],\ldots,n_C$
`\allXs`	$\vec{x}$	$x_1,\ldots,x_C$
`\allXsbut{1}`	$x_{j\neq 1,C}$	$x_2,\ldots,x_{C-1}$
`\allXsbut{i}`	$x_{j\neq i,C}$	$x_1,\ldots,[x_i],\ldots,x_{C-1}$
`\allXsbut{j}`	$x_{k\neq j,C}$	$x_1,\ldots,[x_j],\ldots,x_{C-1}$
`\allXsbut{\ncomponents-1}`	$x_{j\neq C-1,C}$	$x_1,\ldots,x_{C-2}$
`\allXsbut[k]{\ncomponents-1}`	$x_{k\neq C-1,C}$	$x_1,\ldots,x_{C-2}$
`\allXsbut{\ncomponents}`[b]	$x_{j\neq C}$	$x_1,\ldots,x_{C-1}$

[a] You may use C directly instead of `\ncomponents` here, but then it will not change to another symbol if you want to switch to an option that redefines `\ncomponents` later.

[b] This would typically be used to denote something like $\underline{G}(T,P,n,x_1,\ldots,x_{C-1})$ rather than in a subscript, but it looks silly if we do not handle this case this way.

3.1.5 Options Regarding the Number of Moles

`\allNs` `\allNsbut` The default option `moles-index` defines the macro `\allNs` to expand to $\vec{n}$ and the macro `\allNsbut{i}` to expand to $n_{j\neq i}$. You can change the dummy index: `\allNsbut[k]{i}` expands to $n_{k\neq i}$ by default. This is typically not necessary, however: if you type `\allNsbut{j}`, the package will figure out that you want $n_{k\neq j}$ rather than $n_{j\neq j}$. The time to use the optional argument is in situations such as

$$\left(\frac{\partial \mu_j}{\partial n_k}\right)_{n_{i\neq k}},$$

which is incorrect if the dummy index j is used in place of the i.

You can change these to expand to ranges using the `moles-range` option, which renders `\allNs` as $n_1,\ldots,n_C$ and `\allNsbut{i}` as $n_1,\ldots,[n_i],\ldots,n_C$. The optional argument is ignored in this set of notation. Examples of these options are shown in Table 5.

`thermomolesrange` (*env.*) The environment `thermomolesrange` temporarily redefines `\allNs` and other range-oriented macros as though the `moles-range` package option had been invoked.

`\ncomponents` You can change the symbol for the number of components (default: C) by redefining the macro `\ncomponents`. This is done for you by some package options that define notation for particular textbooks.

3.1.6 Other Options

`\dbar` The default for path-dependent one-forms (often called "inexact differentials") is `\dbar`, which looks like đ. This can be changed, if desired, to a delta (δ) with the `delta` option to the package.

It should be noted that the `\dbar` macro is context-dependent: changing the typeface to something not supported will probably ruin it, as the kerning is very

font-specific. This package currently supports Computer Modern, Times, Palatino, Bitstream Charter, Garamond, and Utopia, but other typefaces may require a manual redefinition.

3.1.7 Options for Particular Textbooks

There are several options that load package options and/or redefine particular commands to match the notation in a particular textbook. A table showing how various properties are typeset using each of these packages is included in Appendix A. So far, the following textbooks are supported:

Bejan Notation used by Bejan, *Advanced Engineering Thermodynamics*, Third Edition. Wiley: Hoboken, 2006.

CBK Notation used by Çengel, Boles, and Kanoğlu, *Thermodynamics: An Engineering Approach*, Ninth Edition. McGraw Hill: Singapore, 2020. Their symbols for specific and total volume, which appear to be from the font ITC Benguiat Gothic (and reasonably approximated by Krub Italic), are not directly supported.[3]

ElliottLira Notation used by Elliott and Lira, *Introductory Chemical Engineering Thermodynamics*, Second Edition. Prentice Hall: Upper Saddle River, 2012. *Note: these authors use Henry's Law (molal basis) in the form $y_i P = m_i / K_{H,i}$, which is inconsistent with their notation for the rational basis, so that macro is left set to its default.*

KlotzRosenberg Notation used by Klotz and Rosenberg, *Chemical Thermodynamics: Basic Concepts and Methods*, Seventh Edition. Wiley: Hoboken, 2008.

Koretsky Notation used by Koretsky, *Engineering and Chemical Thermodynamics*, Second Edition. Wiley: New Caledonia, 2013.

ModellReid Alias for `TesterModell` (the first and second editions were by Modell and Reid; Reid died prior to the third edition).

MSBB Notation used by Moran, Shapiro, Boettner, and Bailey, *Fundamentals of Engineering Thermodynamics*, Eighth Edition. Wiley: Kendallville, 2014.

Prausnitz Notation used by Prausnitz, Lichtenthaler, and de Azevedo, *Molecular Thermodynamics of Fluid-Phase Equilibria*, Third Edition, Pearson, 1998.

Sandler Notation used by Sandler, *Chemical, Biochemical, and Engineering Thermodynamics*, Fifth Edition. Wiley: Hoboken, 2017.

SVNAS Notation used by Smith, Van Ness, Abbott, and Swihart, *Introduction to Chemical Engineering Thermodynamics*, Ninth Edition. McGraw-Hill: Boston, 2021.

[3] If you have ITC Benguiat Gothic installed and want to use it for the volume symbol, you can use it through XeTeX; try this:

```
\usepackage{fontspec}
\setsansfont{ITC Benguiat Gothic}
\ExplSyntaxOn
  \tl_gset:Nn \g__thermodynamics_volume_symbol {{\text{\sffamily V}}}
\ExplSyntaxOff
```

TesterModell Notation used by Tester and Modell, *Thermodynamics and Its Applications*, Third Edition, Prentice Hall: Upper Saddle River, 1997.

Thompson Notation used by Thompson, *A Unified Introduction to Chemical Engineering Thermodynamics*, Stillwater Press: Orono, 2000. Note that he uses c, c, n_C, and n for the number of components in various places in the book; I chose c for the definition of `\ncomponents`, but it is impossible to be completely consistent with his notation.

There may well be some inconsistencies between the notation in these books and the symbols used here. I will fix such inconsistencies as I become aware of them.

Important: Some textbooks use symbols other than μ for chemical potential and γ for activity coefficients. For example, `KlotzRosenberg` uses μ for the chemical potential and γ for the activity coefficient. In such cases, the macro `\mu` will produce whatever symbol *is* used for the chemical potential, and `\gamma` will produce the activity coefficient. The original symbols will still be available as `\gammait` and `\muit`, respectively.

A Notation Across Textbooks

Some of the textbooks supported by this package use multiple symbols for the same quantity—for example, Sandler's textbook uses both P^{sat} and P^{vap} for vapor (saturation) pressure, and Elliott and Lira use both ΔH° and ΔH_R^o for the standard enthalpy of reaction. This package may only support one of the two in such cases.

Table 6 gives a description of each symbol supported by the package, the corresponding command, and the way that command is rendered using each of the textbook-related options in Section 3.1.7. Packages consisting of two names are shortened to one name in the headers for space considerations.

Table 6. How symbols are typeset for various textbooks. Entries in gray indicate quantities that are not directly or indirectly defined in a particular textbook and are therefore inherited from the defaults. *Note: Options with two authors, such as* `ElliottLira`*, only include one name so as to fit on one page.*

Quantity	Macro	Default	Bejan	CBK	Elliott	Klotz	Koretsky	MSBB	Prausnitz	Sandler	SVNAS	Modell	Thompson
# components	`\ncomponents`	C	n	C	C	C	m	C	m	$\mathcal{C}$	C	n	c
activity (absolute)	`\actabs_i`	λ_i	λ_i	λ_i	λ_i	λ_i	λ_i	λ_i	λ_i	λ_i	λ_i	λ_i	λ_i
activity (relative)	`\actrel_i`	a_i	a_i	a_i	a_i	a_i	a_i	a_i	a_i[a]	a_i	a_i	a_i	$\widehat{a_i}$
activity coefficient (ordinary)	`\gamma_i`	γ_i	γ_i	γ_i	γ_i	γ_i	γ_i	γ_i	γ_i	γ_i	γ_i	γ_i	γ_i
activity coefficient (Henry, rational)	`\gammarat_i`	γ_i^*	γ_i^*	γ_i^*	γ_i^*	γ_i	$\gamma_i^{\text{Henry's}}$	γ_i^*	γ_i^*	γ_i^*	γ_i^*	γ_i^{**}	γ_i^*
activity coefficient (Henry, molal)	`\gammamol_i`	$\gamma_i^\square$	$\gamma_i^\square$	$\gamma_i^\square$	$\gamma_i^\square$	γ_i	γ_i^m	$\gamma_i^\square$	$\gamma_i^\square$	$\gamma_i^\square$	γ_i^*	γ_i^*	$\gamma_i^\square$
adiabatic compressibility	*See* isentropic compressibility												
adiabatic expansivity	*See* isentropic expansivity												
area (total)	`\At`	$\underset{\sim}{a}$	A	A	$\underset{\sim}{a}$	a	A	A	A	a	a^t	$\underline{\boldsymbol{a}}$	$\underline{\mathcal{A}}$
chemical potential	`\mu`	μ	μ	μ	μ	μ	μ	μ	μ	μ	μ	μ	μ
electric potential	`\Epot`	E	E	E	E	$\mathscr{E}$[b]	E	E	$\mathscr{E}$[b]	E	E	$\exists$	E
electric potential (standard)	`\Epot^\std`	E°	E°	E°	E°	$\mathscr{E}^\circ$	E^o	E°	$\mathscr{E}^0$	E°	E°	$\exists^o$	E°
energy (total)	`\Et`	$\underline{E}$	E	E	$\underline{E}$	E	E	E	E	E	E^t	$\underline{E}$	$\underline{E}$
energy (molar)	`\Em`	$\bar{E}$	$\bar{e}$	$\bar{e}$	$\bar{E}$	E_{m}	e	$\bar{e}$	e	$\underline{E}$	E	$\bar{E}$	$\bar{E}$
energy (specific)	`\Es`	$\hat{E}$	e	e	E	$\hat{E}$	$\hat{e}$	e	$\hat{e}$	$\hat{E}$	E	$\hat{E}$	E
enthalpy (total)	`\Ht`	$\underline{H}$	H	H	$\underline{H}$	H	H	H	H	H	H^t	$\underline{H}$	$\underline{H}$
enthalpy (molar)	`\Hm`	H	$\bar{h}$	$\bar{h}$	H	H_{m}	h	$\bar{h}$	h	$\underline{H}$	H	H	H
enthalpy (specific)	`\Hs`	$\hat{H}$	h	h	H	$\hat{H}$	$\hat{h}$	h	$\hat{h}$	$\hat{H}$	H	$\hat{H}$	$\hat{H}$
enthalpy (partial molar) of i	`\Hpm_i`	$\overline{H}_i$	$\bar{h}_i$	$\widetilde{h}_i$	$\overline{H}_i$	$H_{\text{m}i}$	$\overline{H}_i$	$\overline{H}_i$	$\bar{h}_i$	$\overline{H}_i$	$\overline{H}_i$	$\overline{H}_i$	$\overline{H}_i$
enthalpy of reaction	`\Deltarxn\Hm`	ΔH_{rxn}	$\Delta\bar{h}_{\text{rxn}}$	$\bar{h}_R$	ΔH	ΔH_{m}	Δh_{rxn}	$\Delta\bar{h}_{\text{rxn}}$	Δh_{rxn}	$\Delta_{\text{rxn}}\underline{H}$	ΔH	ΔH_{rx}	ΔH_R
enthalpy of fusion	`\Deltafus\Hm`	ΔH^{fus}	$\bar{h}_{sf}$	$\bar{h}_{sf}$	ΔH^{fus}	ΔH_{m}	Δh_{fus}	$\bar{h}^{\text{fus}}$	Δh^{fus}	$\Delta_{\text{fus}}\underline{H}$	ΔH^{sl}	ΔH^{fus}	ΔH^{SL}
enthalpy of vaporization	`\Deltavap\Hm`	ΔH^{vap}	$\bar{h}_{sf}$	$\bar{h}_{fg}$	ΔH^{vap}	ΔH_{m}	Δh_{vap}	$\bar{h}^{\text{vap}}$	Δh^{vap}	$\Delta_{\text{vap}}\underline{H}$	ΔH^{vl}	ΔH^{vap}	ΔH^{LV}
enthalpy of sublimation	`\Deltasub\Hm`	ΔH^{sub}	$\bar{h}_{sg}$	$\bar{h}_{sg}$	ΔH^{sub}	ΔH_{m}	Δh_{sub}	$\bar{h}^{\text{sub}}$	Δh^{sub}	$\Delta_{\text{sub}}\underline{H}$	ΔH^{vs}	ΔH^{sub}	ΔH^{SV}
entropy (total)	`\St`	$\underline{S}$	S	S	$\underline{S}$	S	S	S	S	S	S^t	$\underline{S}$	$\underline{S}$
entropy (molar)	`\Sm`	$\bar{S}$	$\bar{s}$	$\bar{s}$	$\bar{S}$	S_{m}	s	$\bar{s}$	s	$\underline{S}$	S	$\bar{S}$	$\bar{S}$
entropy (specific)	`\Ss`	$\hat{S}$	s	s	S	$\hat{S}$	$\hat{s}$	s	$\hat{s}$	$\hat{S}$	S	$\hat{S}$	$\hat{S}$
entropy (partial molar) of i	`\Spm_i`	$\overline{S}_i$	$\overline{S}_i$	$\widetilde{s}_i$	$\overline{S}_i$	$S_{\text{m}i}$	$\overline{S}_i$	$\overline{S}_i$	$\bar{s}_i$	$\overline{S}_i$	$\overline{S}_i$	$\overline{S}_i$	$\overline{S}_i$
extent of reaction	`\xrxn`	ξ	ζ	ξ	ξ	ξ	ξ	ε	ξ	X	ε	ξ	ξ
fugacity of pure substance	`\fpure`	f	f	f	f	f	f	f	f_{pure}	f	f	f	f
fugacity of pure i	`\fpure_i`	f_i	$f_i^\bullet$	f_i	f_i	$f_i^\bullet$	f_i	f_i	$f_{\text{pure}\,i}$	f_i	f_i	f_i	$f_i^\bullet$
fugacity of i in mixture	`\fmix_i`	$\hat{f}_i$	f_i	$\hat{f}_i$	$\hat{f}_i$	f_i	$\hat{f}_i$	$\bar{f}_i$	f_i	$\bar{f}_i$	$\hat{f}_i$	$\hat{f}_i$	f_i
fugacity at saturation	`\fsat`	f^{sat}	f^{sat}	f^{sat}	f^{sat}	f^{sat}	f^{sat}	f^{sat}	f^s_{pure}	f^{sat}	f^{sat}	f^{sat}	f^{sat}
fugacity coefficient of pure substance	`\phipure`	ϕ	ϕ	ϕ	ϕ	γ	φ	ϕ	φ_{pure}	ϕ	ϕ	ϕ	ϕ
fugacity coefficient of pure i	`\phipure_i`	ϕ_i	$\phi_i^\bullet$	ϕ_i	ϕ_i	$\gamma_i^\bullet$	φ_i	ϕ_i	$\varphi_{\text{pure}\,i}$	ϕ_i	ϕ_i	ϕ_i	$\phi_i^\bullet$
fugacity coefficient of i in mixture	`\phimix_i`	$\hat{\phi}_i$	ϕ_i	$\hat{\phi}_i$	$\hat{\phi}_i$	γ_i	$\hat{\varphi}_i$	$\bar{\phi}_i$	φ_i	$\bar{\phi}_i$	$\hat{\phi}_i$	$\hat{\phi}_i$	$\bar{\phi}_i$
fugacity coefficient at saturation	`\phisat`	ϕ^{sat}	ϕ^{sat}	ϕ^{sat}	ϕ^{sat}	γ^{sat}	φ^{sat}	ϕ^{sat}	φ^s	ϕ^{sat}	ϕ^{sat}	ϕ^{sat}	ϕ^{sat}

continued on next page...

[a] The symbol a requires the `dutchcal` fonts to be installed, though the package itself is not loaded. This symbol is an approximation to the one the book actually uses.
[b] The symbol $\mathscr{E}$ requires the `emf` package. If that package is not loaded, $\mathcal{E}$ is used instead.

Quantity	Macro	Default	Bejan	CBK	Elliott	Klotz	Koretsky	MSBB	Prausnitz	Sandler	SVNAS	Modell	Thompson
Gibbs free energy (total)	\Gt	$\underline{G}$	G	$\underline{G}$	$\underline{G}$	G	G	G	G	G	G^t	$\underline{G}$	$\underline{G}$
Gibbs free energy (molar)	\Gm	$\overline{G}$	$\overline{g}$	$\overline{g}$	$\overline{G}$	G_m	g	$\overline{g}$	g	$\underline{G}$	G	$\overline{G}$	$\overline{G}$
Gibbs free energy (specific)	\Gs	$\hat{G}$	g	g	G	$\hat{G}$	$\hat{g}$	g	$\hat{g}$	$\hat{G}$	G	$\hat{G}$	$\hat{G}$
Gibbs free energy (partial molar)	\Gpm_i	$\overline{G}_i$	$\overline{G}_i$	$\widetilde{g}_i$	$\overline{G}_i$	$G_{\mathrm{m}i}$	$\overline{G}_i$	$\overline{G}_i$	$\overline{g}_i$	$\overline{G}_i$	$\overline{G}_i$	$\overline{G}_i$	$\overline{G}_i$
Gibbs free energy of mixing	\Deltamix\Gt	$\Delta\underline{G}_\mathrm{mix}$	ΔG_mix	ΔG_mix	$\Delta\underline{G}_\mathrm{mix}$	ΔG_mix	ΔG_mix	ΔG_mix	ΔG_mixing	$\Delta_\mathrm{mix}G$	ΔG^t	$\Delta\underline{G}_\mathrm{mix}$	$\Delta_{MIX}\underline{G}$
Gibbs free energy of reaction	\Deltarxn\Gm	ΔG_rxn	$\Delta\overline{g}_\mathrm{rxn}$	$\overline{g}_R$	ΔG	ΔG_m	Δg_rxn	$\Delta\overline{g}_\mathrm{rxn}$	Δg_rxn	$\Delta_\mathrm{rxn}\underline{G}$	ΔG	ΔG_{rx}	ΔG_R
grand potential (total)	\Lt	$\underline{\Omega}$	F_μ	Ω	$\underline{\Omega}$	Ω	Ω	Ω	Ω	Ω	$\underline{\Omega}$	$\underline{\Omega}$	$\underline{\Omega}$
grand potential (molar)	\Lm	Ω	$\overline{f}_\mu$	$\overline{\omega}$	Ω	Ω_m	ω	$\overline{\omega}$	ω	$\underline{\Omega}$	Ω	Ω	Ω
grand potential (specific)	\Ls	$\hat{\Omega}$	f_μ	ω	$\hat{\Omega}$	$\hat{\Omega}$	$\hat{\omega}$	ω	$\hat{\omega}$	$\hat{\Omega}$	Ω	$\hat{\Omega}$	$\hat{\Omega}$
heat (total)	\Qt	Q	Q	Q	Q	Q	Q	Q	Q	Q	Q^t	Q	Q
heat (molar)	\Qm	$\overline{Q}$	$\overline{q}$	$\overline{q}$	$\overline{Q}$	Q_m	q	$\overline{q}$	q	Q	Q	$\overline{Q}$	$\overline{Q}$
heat (specific)	\Qs	$\hat{Q}$	q	q	Q	$\hat{Q}$	$\hat{q}$	q	$\hat{q}$	$\hat{Q}$	Q	$\hat{Q}$	$\hat{Q}$
heat capacity (isobaric, total)	\cPt	$\underline{C}_P$	C_P	C_p	$\underline{C}_P$	C_P	C_P	C_p	C_p	NC_P	nC_P	$\underline{C}_p$	$\underline{C}_p$
heat capacity (isobaric, molar)	\cP	C_P	$\bar{c}_P$	$\bar{c}_p$	C_P	$C_{P\mathrm{m}}$	c_P	$\bar{c}_p$	c_p	C_P	C_P	C_p	C_P
heat capacity of i (isobaric, molar)	\cP_i	$C_{P,i}$	$\bar{c}_{P,i}$	$\bar{c}_{p,i}$	$C_{P,i}$	$C^\bullet_{P\mathrm{m}i}$	$C_{P,i}$	$\bar{c}_{p\,i}$	$c_{p\,i}$	$C_{P,i}$	$C_{P\,i}$	C_{pi}	$C_{P,i}$
heat capacity (isobaric, specific)	\cPs	$\hat{C}_P$	c_P	c_p	C_P	$\hat{C}_P$	$\hat{c}_P$	c_p	$\hat{c}_p$	$\hat{C}_P$	C_P	$\hat{C}_p$	$\hat{C}_p$
heat capacity (isobaric, partial molar)	\cPpm_i	$\overline{C}_{P,i}$	$\bar{c}_{P,i}$	$\overline{C}_{p,i}$	$\overline{C}_{P,i}$	$C_{P\mathrm{m}i}$	$\overline{C}_{P,i}$	$\overline{C}_{p,i}$	$\bar{c}_{p\,i}$	$\overline{C}_{P,i}$	$\overline{C}_{P\,i}$	$\overline{C}_{pi}$	$\overline{C}_{P,i}$
heat capacity (isochoric, total)	\cVt	$\underline{C}_V$	C_V	C_V[3]	$\underline{C}_V$	C_V	C_V	C_v	C_v	NC_V	nC_V	$\underline{C}_v$	$\underline{C}_V$
heat capacity (isochoric, molar)	\cV	C_V	$\bar{c}_v$	$\bar{c}_V$[3]	C_V	$C_{V\mathrm{m}}$	c_V	$\bar{c}_v$	c_v	C_V	C_V	C_v	C_V
heat capacity (isochoric, specific)	\cVs	$\hat{C}_V$	c_v	c_V[3]	C_V	$\hat{C}_V$	$\hat{c}_v$	c_v	$\hat{c}_p$	$\hat{C}_V$	C_V	$\hat{C}_v$	$\hat{C}_V$
heat capacity (isochoric, partial molar)	\cVpm_i	$\overline{C}_{V,i}$	$\bar{c}_{v,i}$	$\overline{C}_{V,i}$[3]	$\overline{C}_{V,i}$	$C_{V\mathrm{m}i}$	$\overline{C}_V$	$\overline{C}_{v,i}$	$\bar{c}_{v\,i}$	$\overline{C}_{V,i}$	$\overline{C}_{V\,i}$	$\overline{C}_{vi}$	$\overline{C}_{V,i}$
Helmholtz free energy (total)	\Ft	$\underline{A}$	F	A	$\underline{A}$	A	A	Ψ	A	A	A^t	$\underline{A}$	$\underline{A}$
Helmholtz free energy (molar)	\Fm	A	$\bar{f}$	$\bar{a}$	A	A_m	a	$\overline{\psi}$	a	$\underline{A}$	A	A	A
Helmholtz free energy (specific)	\Fs	$\hat{A}$	f	a	A	$\hat{A}$	$\hat{a}$	ψ	$\hat{a}$	$\hat{A}$	A	$\hat{A}$	$\hat{A}$
Helmholtz free energy (partial molar)	\Fpm_i	$\overline{A}_i$	$\overline{f}_i$	$\widetilde{a}_i$	$\overline{A}_i$	$A_{\mathrm{m}i}$	$\overline{A}_i$	$\overline{\Psi}_i$	$\overline{a}_i$	$\overline{A}_i$	$\overline{A}_i$	$\overline{A}_i$	$\overline{A}_i$
Henry's constant (rational basis)	\Henryrat_i	h_i	h_i	h_i	h_i	k_i	$\mathcal{H}_i$	h_i	H_i	H_i	$\mathcal{H}_i$	f^{**}	$k_{H,i}$
Henry's constant (molal basis)	\Henrymol_i	$\mathcal{H}_i$	$\mathcal{H}_i$	$\mathcal{H}_i$	$\mathcal{H}_i$	k_i''	$\mathcal{H}_i$	$\mathcal{H}_i$	$\mathcal{H}_i$	$\mathcal{H}_i$	$\mathcal{H}_i$	f^*	$k_{H,i}$
ideal gas enthalpy	\Hm^\IG	H^IG	$\bar{h}^\mathrm{IG}$	$\overline{h}^\mathrm{IG}$	H^{ig}	H^IG_m	$h^\text{ideal gas}$	$\overline{h}^*$	h^id	H^IG	H^{ig}	H^o	H^{IG}
ideal gas mixture enthalpy	\Hm^\IGM	H^IGM	$\bar{h}^\mathrm{IG}$	$\overline{h}^\mathrm{IGM}$	H^{ig}	$H^\mathrm{IGM}_\mathrm{m}$	h^ideal	$\overline{h}^*$	h^id	H^IGM	H^{ig}	H^o	H^{IG}
ideal solution enthalpy	\Hm^\IS	H^IS	$\bar{h}^\mathrm{IS}$	$\overline{h}^\mathrm{IS}$	H^{is}	H^IS_m	h^ideal	$\overline{h}^\mathrm{IS}$	$h^\mathrm{(ideal)}$	H^IM	H^{id}	H^{ID}	H^{IS}
inexact differential	\dbar	đ	δ	δ	d	d	δ	δ	đ	đ	đ	δ	δ
internal energy (total)	\Ut	$\underline{U}$	U	$\underline{U}$	$\underline{U}$	U	U	U	U	U	U^t	$\underline{U}$	$\underline{U}$
internal energy (molar)	\Um	$\overline{U}$	$\bar{u}$	$\overline{u}$	$\overline{U}$	U_m	u	$\overline{u}$	u	$\underline{U}$	U	$\overline{U}$	$\overline{U}$
internal energy (specific)	\Us	$\hat{U}$	u	u	U	$\hat{U}$	$\hat{u}$	u	$\hat{u}$	$\hat{U}$	U	u	$\hat{U}$
internal energy (partial molar)	\Upm_i	$\overline{U}_i$	$\overline{u}_i$	$\widetilde{u}_i$	$\overline{U}_i$	$U_{\mathrm{m}i}$	$\overline{U}_i$	$\overline{U}_i$	$\overline{u}_i$	$\overline{U}_i$	$\overline{U}_i$	$\overline{U}_i$	$\overline{U}_i$
isothermal compressibility	\kappaT	κ_T	κ	α	κ_T	β	κ	κ	β	κ_T	κ	κ_T	κ_T
isentropic compressibility	\kappaS	κ_S	κ_S	α_S	κ_S	β_S	κ_S	α	β_S	κ_S	κ_S	κ_S	κ_S
isobaric expansivity	\alphaP	α_P	β	β	α_P	α	β	β	α	α	β	α_P	α_P
isentropic expansivity	\alphaS	α_S	β_S	β_S	α_S	α_S	β_S	β_S	α_S	α_S	β_S	α_S	α_S
Joule–Thomson coefficient	\muJT	μ_JT	μ_J	μ_JT	μ_{JT}	$\mu_\mathrm{J.T.}$	μ_JT	μ_J	μ_JT	μ	μ	α_H	α_H
moles	\Nt	n	N	N	n	n	n	n	n	N	n	N	n

continued on next page...

Quantity	Macro	Default	Bejan	CBK	Elliott	Klotz	Koretsky	MSBB	Prausnitz	Sandler	SVNAS	Modell	Thompson
saturation pressure	`\Psat`	P^{sat}	P^{sat}	P^{v}	P^{sat}	p	P^{sat}	P^{sat}	P^{s}	P^{sat}	P^{sat}	P^{sat}	P^{sat}
saturation pressure of i	`\Psat_i`	P_i^{sat}	P_i^{sat}	P_i^{v}	P_i^{sat}	$p_i^{\bullet}$	P_i^{sat}	P_i^{sat}	P_i^{s}	P_i^{sat}	P_i^{sat}	P_i^{sat}	P_i^{sat}
standard molality	`\Cstd_i`	C_i°	C_i°	C_i°	m_i°	m_i°	C_i^{o}	C_i°	C_i^{0}	1 molal	m°	m^{+}	m_i°
standard chemical potential	`\mustd`	μ°	μ°	μ°	μ°	μ°	μ^{o}	$\overline{g}_i^{\circ}$	μ^{0}	μ°	G°	μ^{o}	Γ
standard enthalpy	`\Hm^\std`	H°	$\bar{h}^{\circ}$	$\overline{h}^{\circ}$	H°	H_{m}°	h^{o}	$\overline{h}^{\circ}$	h^{0}	$\underline{H}^{\circ}$	H°	H^{o}	H°
standard enthalpy of formation	`\Deltaf\Hm^std`	ΔH_f°	$\bar{h}_f^{\circ}$	$\overline{h}_f^{\circ}$	ΔH_f°	$\Delta_f H_{\text{m}}^{\circ}$	Δh_f^{o}	$\bar{h}_{\text{f}}^{\circ}$	Δh_f^{0}	$\Delta_{\text{f}}\underline{H}^{\circ}$	ΔH_{f298}°	ΔH_f^{o}	ΔH_F°
standard enthalpy of formation of i	`\Deltaf\Hm^std_i`	$\Delta H_{f,i}^{\circ}$	$\bar{h}_{f,i}^{\circ}$	$\overline{h}_{f,i}^{\circ}$	$\Delta H_{f,i}^{\circ}$	$\Delta_f H_{\text{m}i}^{\circ}$	$(\Delta h_f^{o})_i$	$(\bar{h}_{\text{f}}^{\circ})_i$	$\Delta h_{f\,i}^{0}$	$\Delta_{\text{f}}\underline{H}_i^{\circ}$	ΔH_{f298i}°	ΔH_{fi}^{o}	$\Delta H_{F,i}^{\circ}$
standard enthalpy of reaction	`\Deltarxn\Hm^std`	$\Delta H_{\text{rxn}}^{\circ}$	$\bar{h}_{\text{rxn}}^{\circ}$	$\overline{h}_R^{\circ}$	ΔH°	ΔH_{m}	$\Delta h_{\text{rxn}}^{o}$	$\Delta\bar{h}_{\text{rxn}}^{\circ}$	$\Delta h_{\text{rxn}}^{0}$	$\Delta_{\text{rxn}}\underline{H}^{\circ}$	ΔH°	ΔH_{rx}^{o}	ΔH_R°
standard free energy of formation	`\Deltaf\Gm^std`	ΔG_f°	$\bar{g}^{\circ}$	$\bar{g}_f^{\circ}$	ΔG_f°	$\Delta_f G_{\text{m}}^{\circ}$	Δg_f^{o}	$\bar{g}_{\text{f}}^{\circ}$	Δg_f^{0}	$\Delta_{\text{f}}\underline{G}^{\circ}$	ΔG_{f298}°	ΔG_f^{o}	ΔG_F°
standard free energy of formation of i	`\Deltaf\Gm_i^std`	$\Delta G_{f,i}^{\circ}$	$\bar{g}_{f,i}^{\circ}$	$\bar{g}_{f,i}^{\circ}$	$\Delta G_{f,i}^{\circ}$	$\Delta_f G_{\text{m}i}^{\circ}$	$(\Delta g_f^{o})_i$	$(\bar{g}_{\text{f}}^{\circ})_i$	$\Delta g_{f\,i}^{0}$	$\Delta_{\text{f}}\underline{G}_i^{\circ}$	ΔG_{f298i}°	ΔG_{fi}^{o}	$\Delta G_{F,i}^{\circ}$
standard free energy of reaction	`\Deltarxn\Gm^std`	$\Delta G_{\text{rxn}}^{\circ}$	$\bar{g}_{\text{rxn}}^{\circ}$	$\bar{g}_R^{\circ}$	ΔG°	ΔG_{m}	$\Delta g_{\text{rxn}}^{o}$	$\Delta\bar{g}_{\text{rxn}}^{\circ}$	$\Delta g_{\text{rxn}}^{0}$	$\Delta_{\text{rxn}}\underline{G}^{\circ}$	ΔG°	ΔG_{rx}^{o}	ΔG_R°
standard fugacity	`\fstd`	f°	f°	f°	f°	f°	f^{o}	f°	f^{0}	$\bar{f}^{\circ}$	f°	f°	f°
standard Gibbs free energy	`\Gm^\std`	G°	$\bar{g}^{\circ}$	$\bar{g}^{\circ}$	G°	G_{m}°	g^{o}	$\overline{g}^{\circ}$	g^{0}	$\underline{G}^{\circ}$	G°	G^{o}	G°
standard Gibbs free energy of i	`\Gm^\std_i`	G_i°	$\bar{g}_i^{\circ}$	$\bar{g}_i^{\circ}$	G_i°	$G_{\text{m}i}^{\circ}$	g_i^{o}	$\overline{g}_i^{\circ}$	g_i^{0}	$\underline{G}_i^{\circ}$	G_i°	G_i^{o}	G_i°
standard pressure	`\Pstd`	P°	P_0	P_0	P°	P°	P^{o}	p_{ref}	P^{0}	1 bar	P°	$P^{\star}$	P°
vapor pressure	`\Pvap`	P^{sat}	P^{sat}	P^{v}	P^{std}	p	P^{sat}	p_{ref}	P^{s}	P^{vap}	P^{sat}	P^{sat}	P^{sat}
volume (total)	`\Vt`	$\underline{V}$	V	V^{3}	$\underline{V}$	V	V	V	V	V	V^{t}	$\underline{V}$	$\underline{V}$
volume (molar)	`\Vm`	$\overline{V}$	$\bar{v}$	$\overline{v}^{3}$	$\overline{V}$	V_{m}	v	$\overline{v}$	v	$\underline{V}$	V	$\overline{V}$	$\overline{V}$
volume (specific)	`\Vs`	$\hat{V}$	v	v^{3}	V	$\hat{V}$	$\hat{v}$	v	$\hat{v}$	$\hat{\underline{V}}$	V	v	$\hat{V}$
volume (molar, residual)	`\VR`	V^{R}	$\bar{v}^{R}$	$\overline{v}^{R3}$	V^{R}	V_{m}^{R}	v^{dep}	$\overline{v}^{R}$	v^{R}	$\underline{V}^{r}$	V^{R}	V^{R}	V^{R}
volume (molar, excess)	`\VE`	V^{E}	$\bar{v}^{E}$	$\overline{v}^{E3}$	V^{E}	V_{m}^{E}	v^{E}	$\overline{v}^{E}$	v^{E}	$\underline{V}^{\text{ex}}$	V^{E}	V^{EX}	V^{EX}
volume (partial molar, excess)	`\VEpm_i`	$\overline{V}_i^{E}$	$\bar{v}_i^{E}$	$\overline{v}^{E3}$	$\overline{V}_i^{E}$	$V_{\text{m}i}^{\text{E}}$	$\overline{V}_i^{E}$	$\overline{V}_i^{E}$	$\overline{v}_i^{E}$	$\overline{V}_i^{\text{ex}}$	$\overline{V}_i^{E}$	$\overline{V}_i^{EX}$	$\overline{V}_i^{EX}$
work (total)	`\Wt`	$\underline{W}$	W	W	$\underline{W}$	W	W	W	W	W	W^{t}	$\underline{W}$	$\underline{W}$
work (molar)	`\Wm`	$\overline{W}$	$\bar{w}$	$\overline{w}$	$\overline{W}$	W_{m}	w	$\overline{w}$	w	W	W	$\overline{W}$	$\overline{W}$
work (specific)	`\Ws`	$\hat{W}$	w	w	W	$\hat{W}$	$\hat{w}$	w	$\hat{w}$	$\hat{W}$	W	w	$\hat{W}$

B Implementation

We set up some non-standard token comparison variants; these are designed to catch both \ncomponents=\ncomponents and \ncomponents=*C* (using the default options); we have to define \ncomponents to be expandable to make these work at all.

```
\ExplSyntaxOn
\cs_generate_variant:Nn \tl_if_eq:nnTF { xxTF }
```

This package requires the amstext package, as \text is used to handle \sat, \IS, \IG, \IGM, \Henrymol, \fusion, \reaction, \vaporization, and \sublimation by default, as well as several other macros defined by package options.

```
\RequirePackage{amstext}
```

B.1 Symbols Controlled by Package Options

We set some symbols prior to declaring the package options. The default symbols follow package option EUAGHan, even though the macros follow the option EUFGHAN.

\dbar The way \dbar is defined depends on the typeface you are using. We try to determine, at \begin{document}, which typeface you chose based on the packages that are loaded and some of their internal definitions. The thermodynamics package currently supports Computer Modern (the default or through lmodern), Palatino (through pxfonts or newpxmath), Times (through txfonts, mathptmx, or newtxmath), Utopia (through mathdesign), Bitstream Charter (through mathdesign), and Garamond (through mathdesign). Definitions of \dbar (with \newcommand*, \providecommand*, \NewDocumentCommand, or \ProvideDocumentCommand) in the preamble will override the ones here.

```
\AtBeginDocument{
    \@ifpackageloaded{pxfonts}{%
        \ProvideDocumentCommand{\dbar}{}
            {\mkern5mu\mathchar'26\mkern-10mu d}
    }{}
    \@ifpackageloaded{newpxmath}{%
        \ProvideDocumentCommand{\dbar}{}
            {\mkern5mu\mathchar'26\mkern-10mu d}
    }{}
    \@ifpackageloaded{txfonts}{%
        \ProvideDocumentCommand{\dbar}{}
            {\mkern5mu\mathchar'26\mkern-11mu d}
    }{}
    \@ifpackageloaded{mathptmx}{%
        \ProvideDocumentCommand{\dbar}{}
            {\mkern5mu\mathchar'26\mkern-10mu d}
    }{}
    \@ifpackageloaded{newtxmath}{%
        \ProvideDocumentCommand{\dbar}{}
            {\mkern5mu\mathchar'26\mkern-11mu d}
    }{}
    \@ifpackageloaded{mathdesign}{%
        \tl_const:Nn \c_@@_charter_tl {mdbch}
        \tl_const:Nn \c_@@_utopia_tl {mdput}
        \tl_const:Nn \c_@@_garamond_tl {mdugm}
        \tl_if_eq:NNT \MD@default@family \c_@@_utopia_tl
        { \ProvideDocumentCommand{\dbar}{}
```

```
            {\mkern5mu\mathchar'26\mkern-20mu d}
        }
        \tl_if_eq:NNT \MD@default@family \c_@@_charter_tl
        { \ProvideDocumentCommand{\dbar}{}
            {\mkern5mu\mathchar'26\mkern-15mu d}
        }
        \tl_if_eq:NNT \MD@default@family \c_@@_garamond_tl
        { \ProvideDocumentCommand{\dbar}{}
            {\mkern5mu\mathchar'26\mkern-17mu d}
        }
    }{}
    % Defaults to Computer Modern
    \ProvideDocumentCommand{\dbar}{}
        {\mkern3mu\mathchar'26\mkern-12mu d}
}
```

Symbols are defined for the total energy, internal energy, Helmholtz free energy, Gibbs free energy, grand potential (Landau free energy), enthalpy, entropy, surface area, volume, number of moles, heat, and work; these are E, U, A, G, Ω, H, S, a, V, n, Q, and W, respectively. These commands should not be used on their own, but rather accessed through the macros `\Ut`, `\Um`, and `\Us` (using the internal energy as an example).

The default symbols are not intended to be easy to change—the intended mechanism is through package options. If you want to use a non-standard symbol that is not available through one of the package options, you can redefine the internal token lists inside `\ExplSyntaxOn`...`\ExplSyntaxOff`. For example,

```
\ExplSyntaxOn
   \tl_gset:Nn \g__thermodynamics_Helmholtz_symbol {H}
   \tl_gset:Nn \g__thermodynamics_enthalpy_symbol {h}
\ExplSyntaxOff
```

would define the ill-advised notation that I have nonetheless heard of that uses H for Helmholtz free energy and h for enthalpy. Note that the macros for temperature and pressure are only used inside the definitions of the compressibilities, expansivities, and heat capacities; there is no user-level macro for the temperature or the pressure, so it is up to the user to use consistent symbols for those properties.

```
\tl_new:N \g_@@_total_energy_symbol
\tl_new:N \g_@@_internal_energy_symbol
\tl_new:N \g_@@_Helmholtz_symbol
\tl_new:N \g_@@_Gibbs_symbol
\tl_new:N \g_@@_Landau_symbol
\tl_new:N \g_@@_enthalpy_symbol
\tl_new:N \g_@@_entropy_symbol
\tl_new:N \g_@@_area_symbol
\tl_new:N \g_@@_volume_symbol
\tl_new:N \g_@@_mole_symbol
\tl_new:N \g_@@_heat_symbol
\tl_new:N \g_@@_work_symbol
\tl_new:N \g_@@_temperature_symbol
\tl_new:N \g_@@_pressure_symbol

\tl_gset:Nn \g_@@_total_energy_symbol E
\tl_gset:Nn \g_@@_internal_energy_symbol U
\tl_gset:Nn \g_@@_Helmholtz_symbol A
```

```
\tl_gset:Nn \g_@@_Gibbs_symbol G
\cs_if_exist:NTF \Omegait
{ \tl_gset:Nn \g_@@_Landau_symbol \Omegait }
{ \tl_gset:Nn \g_@@_Landau_symbol \Omega }
\tl_gset:Nn \g_@@_enthalpy_symbol H
\tl_gset:Nn \g_@@_entropy_symbol S
\tl_gset:Nn \g_@@_area_symbol a
\tl_gset:Nn \g_@@_volume_symbol V
\tl_gset:Nn \g_@@_mole_symbol n
\tl_gset:Nn \g_@@_heat_symbol Q
\tl_gset:Nn \g_@@_work_symbol W
\tl_gset:Nn \g_@@_temperature_symbol T
\tl_gset:Nn \g_@@_pressure_symbol P
```

We then define two functions and several lengths that we shall use when drawing rules above or below a symbol. The default is to use underlined symbols for extensive quantities, plain symbols for molar quantities, and carets for specific quantities, but this can be changed using package options.

```
\cs_new:Nn \@@_underline:n
{ \mkern1mu\underline{\mkern-1mu #1\mkern-4mu}\mkern4mu }
\cs_new:Nn \@@_overline:n
{ \mkern2mu\overline{\mkern-2mu #1\mkern-1mu}\mkern1mu }
```

`\PartialOpen` `\PartialClose` `\PartialEmptyClose`

We define three commands to use to denote the beginning and end of partial derivatives. These symbols can be customized by package options. Default is `parentheses`, meaning that `\[ \Partial{f}{x}{y} \]` renders as

$$\left(\frac{\partial f}{\partial x}\right)_y$$

with the defaults. The macro `\PartialEmptyClose` is used when the last argument to `\Partial` is empty, which is important for the `bar` option to the document class or inside the `thermobar` environment.

```
\tl_new:N \l_@@_PartialOpen_tl
\tl_new:N \l_@@_PartialEmptyClose_tl
\tl_new:N \l_@@_PartialClose_tl

\tl_set:Nn \l_@@_PartialOpen_tl {(}
\tl_set:Nn \l_@@_PartialClose_tl {)}
\tl_set:Nn \l_@@_PartialEmptyClose_tl {)}
```

B.2 Package Options

We declare a bunch of options for which sets of symbols to use. These are summarized in Table 3.

```
\DeclareOption{EUAGHan}{}% the default
\DeclareOption{EUAGHaN}{\tl_gset:Nn \g_@@_mole_symbol N}%
\DeclareOption{EUHAGan}{\ExecuteOptions{EUAGHan}}
\DeclareOption{EUHAGaN}{\ExecuteOptions{EUAGHaN}}
\DeclareOption{EUFGHAn}{%
  \tl_gset:Nn \g_@@_Helmholtz_symbol F
  \tl_gset:Nn \g_@@_area_symbol A
}
\DeclareOption{EUFGHAN}{%
  \tl_gset:Nn \g_@@_Helmholtz_symbol F
```

```
  \tl_gset:Nn \g_@@_area_symbol A
  \tl_gset:Nn \g_@@_mole_symbol N
}
\DeclareOption{EEFGHAn}{%
  \tl_gset:Nn \g_@@_total_energy_symbol {\mathcal{E}}
  \tl_gset:Nn \g_@@_internal_energy_symbol E
  \tl_gset:Nn \g_@@_Helmholtz_symbol F
  \tl_gset:Nn \g_@@_area_symbol A
}
\DeclareOption{EEFGHAN}{%
  \tl_gset:Nn \g_@@_total_energy_symbol {\mathcal{E}}
  \tl_gset:Nn \g_@@_internal_energy_symbol E
  \tl_gset:Nn \g_@@_Helmholtz_symbol F
  \tl_gset:Nn \g_@@_area_symbol A
  \tl_gset:Nn \g_@@_mole_symbol N
}
\DeclareOption{EEFGHan}{%
  \tl_gset:Nn \g_@@_total_energy_symbol {\mathcal{E}}
  \tl_gset:Nn \g_@@_internal_energy_symbol E
  \tl_gset:Nn \g_@@_Helmholtz_symbol F
}
\DeclareOption{EEFGHaN}{%
  \tl_gset:Nn \g_@@_total_energy_symbol {\mathcal{E}}
  \tl_gset:Nn \g_@@_internal_energy_symbol E
  \tl_gset:Nn \g_@@_Helmholtz_symbol F
  \tl_gset:Nn \g_@@_mole_symbol N
}
\DeclareOption{EEAGHan}{%
  \tl_gset:Nn \g_@@_total_energy_symbol {\mathcal{E}}
  \tl_gset:Nn \g_@@_internal_energy_symbol E
}
\DeclareOption{EEAGHaN}{%
  \tl_gset:Nn \g_@@_total_energy_symbol {\mathcal{E}}
  \tl_gset:Nn \g_@@_internal_energy_symbol E
  \tl_gset:Nn \g_@@_mole_symbol N
}
\DeclareOption{EUAGHAn}{%
  \tl_gset:Nn \g_@@_area_symbol {\mathcal{A}}
}
\DeclareOption{EUAGHAN}{%
  \tl_gset:Nn \g_@@_area_symbol {\mathcal{A}}
  \tl_gset:Nn \g_@@_mole_symbol N
}
\DeclareOption{EUFGHan}{%
  \tl_gset:Nn \g_@@_Helmholtz_symbol F
}
\DeclareOption{EUFGHaN}{%
  \tl_gset:Nn \g_@@_Helmholtz_symbol F
  \tl_gset:Nn \g_@@_mole_symbol N
}
```

The `delta` option redefines `\dbar` to produce the symbol δ. The default is to use a d with a slash through it ($đ$) for inexact differentials unless the user overrides it with this option. The macro could also be redefined manually, of course.

```
\DeclareOption{delta}{ \cs_set_eq:NN \dbar \delta }
```

Next, we define options for the set of notation. The default is `intensive-plain`,

which produces things like V for molar volume, $\underline{V}$ for total volume, and $\hat{V}$ for specific volume. The symbols themselves are produced via internal (non-user-facing) macros.

```
\cs_new:Nn \@@_extensive:n {#1}
\cs_new:Nn \@@_intensive:n {#1}
\cs_new:Nn \@@_specific:n {\hat{#1}}

\cs_new:Npn \@@_set_intensive_plain
{
  \cs_set:Nn \@@_extensive:n {\@@_underline:n{##1}}
  \cs_set:Nn \@@_intensive:n {##1}
}
\cs_new:Npn \@@_set_extensive_plain
{
  \cs_set:Nn \@@_extensive:n {##1}
  \cs_set:Nn \@@_intensive:n {\@@_underline:n{##1}}
}
\cs_new:Npn \@@_set_lowercase_pms
{
  \RenewDocumentCommand{\partialmolar}{m}
  {
    \tl_set:Nn \l_@@_pm_symbol_tl {\text_lowercase:n {##1}}
    \@@_generic_pm:
  }
}
\cs_new:Npn \@@_set_intensive_lowercase
{
  \cs_set:Nn \@@_extensive:n {\text_uppercase:n {##1}}
  \cs_set:Nn \@@_intensive:n {\text_lowercase:n {##1}}
  \cs_set:Nn \@@_specific:n {\hat{\text_lowercase:n {##1}}}
}
\cs_new:Npn \@@_set_extensive_superscripts
{
  \cs_set:Nn \@@_extensive_one:n
  { \c_math_superscript_token {##1\l_@@_super_separator_tl t} }
  \cs_set:Nn \@@_extensive:n
  {
     \peek_catcode_remove:NTF \c_math_superscript_token
     { ##1 \@@_extensive_one:n }
     { ##1 \c_math_superscript_token t }
  }
  \cs_set:Nn \@@_intensive:n {##1}
}
\DeclareOption{extensive-plain}{\@@_set_extensive_plain}
\DeclareOption{intensive-plain}{\@@_set_intensive_plain} % the default
\DeclareOption{intensive-lowercase}{% PLEASE don't use this!
  \@@_set_intensive_lowercase
  \AtEndOfPackage{
    \@@_set_lowercase_pms
  }
}
\DeclareOption{extensive-superscript}{%
  \@@_set_extensive_superscripts
}
```

`thermolongpm` (*env.*)
`thermoshortpm` (*env.*)

The `longpm` option (the default) makes partial molar quantities that look like $\overline{U_i^E}$. The `shortpm` option (which is used by several textbooks) makes partial molar quantities

look like $\overline{U}_i^E$. The environments `thermolongpm` and `thermoshortpm` do the same thing locally.

```
\bool_new:N \l_@@_longpm_bool
\DeclareOption{longpm}{\bool_set_true:N \l_@@_longpm_bool}
\cs_set_eq:NN \@@_overline_copy:n \@@_overline:n
\DeclareOption{shortpm}{
  \bool_set_false:N \l_@@_longpm_bool
  \AtEndOfPackage{
    \RenewDocumentCommand{\cPpm}{}
    {
      \cs_set:Nn \@@_overline:n {##1}
      \partialmolar{\cPpmshort}
    }
    \RenewDocumentCommand{\cVpm}{}
    {
      \cs_set:Nn \@@_overline:n {##1}
      \partialmolar{\cVpmshort}
    }
  }
}
\NewDocumentEnvironment{thermolongpm}{}{%
  \bool_set_true:N \l_@@_longpm_bool
}{}
\NewDocumentEnvironment{thermoshortpm}{}{%
  \bool_set_false:N \l_@@_longpm_bool
     \RenewSubscriptedSymbol{\cPpm}{\@@_overline:n \heatcapacitysymbol}
        {\g_@@_pressure_symbol}
     \RenewSubscriptedSymbol{\cVpm}{\@@_overline:n \heatcapacitysymbol}
        {\g_@@_volume_symbol}
}{}
```

The next two options choose whether variables held constant are subscripted (the default) or placed next to the function. The difference is

$$\left(\frac{\partial U}{\partial S}\right)_V \quad \text{versus} \quad \left(\frac{\partial U(S,V)}{\partial S}\right)$$

for `subscripts` and `nosubscripts`, respectively.

```
\bool_new:N \l_@@_subscripted_bool
\bool_set_true:N \l_@@_subscripted_bool
\DeclareOption{subscripts}{\bool_set_true:N \l_@@_subscripted_bool}
\DeclareOption{nosubscripts}{\bool_set_false:N \l_@@_subscripted_bool}
```

These options change how `\Partial` and friends render derivatives. The default is parentheses, but other options include brackets, braces, a vertical bar on the right side, or plain (undecorated) derivatives.

```
\DeclareOption{parentheses}{}
\DeclareOption{brackets}{%
  \tl_set:Nn \l_@@_PartialOpen_tl {[}
  \tl_set:Nn \l_@@_PartialClose_tl {]}
  \tl_set:Nn \l_@@_PartialEmptyClose_tl {]}
}
\DeclareOption{braces}{%
  \tl_set:Nn \l_@@_PartialOpen_t1 {\{}
  \tl_set:Nn \l_@@_PartialClose_t1 {\}}
  \tl_set:Nn \l_@@_PartialEmptyClose_tl {\}}
```

```
}
\DeclareOption{bar}{%
  \tl_set:Nn \l_@@_PartialOpen_tl {.}
  \tl_set:Nn \l_@@_PartialClose_tl {\rvert}
  \tl_set:Nn \l_@@_PartialEmptyClose_tl {.}
}
\DeclareOption{plain-derivatives}{% This implies dU(S,V,N)/dS notation
  \tl_set:Nn \l_@@_PartialOpen_tl {.}
  \tl_set:Nn \l_@@_PartialClose_tl {.}
  \tl_set:Nn \l_@@_PartialEmptyClose_tl {.}
  \ExecuteOptions{nosubscripts}
}
```

B.3 The Number of Moles Macros

`\ncomponents` We define the number of components, default C, for use in the "all moles" and related macros. The command is expandable so we can perform comparisons to user-entered values.

```
\NewExpandableDocumentCommand \ncomponents {} {C}
```

`\allNs` `\allXs` `\allYs` `\allmus` `\allMs` `\allWs` Several macros define a shorthand for "moles of all species" (`\allNs`) and "moles of all species except" (`\allNsbut`), as well as similar quantities for masses (`\allMs`, `\allMsbut`) and chemical potentials (`\allmus`, `\allmusbut`), which occur frequently in mixture thermodynamics. The default is for `\allNs` to become $\vec{n}$ and `allNsbut{i}` to become $n_{j\neq i}$. The optional argument changes which index (default: j) to use in the left side of the inequality.[4] Essentially identical commands are defined for chemical potentials and masses: `\allmus` and `\allmusbut` and `\allMs` and `\allMsbut`, respectively.

```
\NewDocumentCommand{\allNs}{O{i}}{\allcomponents[#1]{\Nt}}
\NewDocumentCommand{\allXs}{O{i}}{\allcomponents[#1]{x}}
\NewDocumentCommand{\allYs}{O{i}}{\allcomponents[#1]{y}}
\NewDocumentCommand{\allmus}{O{i}}{\allcomponents[#1]{\mu}}
\NewDocumentCommand{\allMs}{O{i}}{\allcomponents[#1]{m}}
\NewDocumentCommand{\allWs}{O{i}}{\allcomponents[#1]{w}}
```

`\allNsbut` `\allXsbut` `\allYsbut` `\allMsbut` `\allWsbut` Similar commands are defined for mole fractions (`\allXs`, `\allYs`, etc.), but these assume the last mole fraction is *not* one of the variables—that is, `\allXsbut` and `\allYsbut` assume the argument *and* `\ncomponents` are held constant. For example,

```
\[ \Partial{\Gm}{T}{P,\allXs} = -\Sm \qquad
   \Partial{\Gm}{x_i}{T,P,\allXsbut{i}} \neq \Gpm_i \]
```

yields

$$\left(\frac{\partial G}{\partial T}\right)_{P,\vec{x}} = -S \qquad \left(\frac{\partial G}{\partial x_i}\right)_{T,P,x_{j\neq i,C}} \neq \overline{G}_i.$$

```
\NewDocumentCommand{\allNsbut}{O{j} m} {\allbut[#1]{#2}{\Nt}}
\NewDocumentCommand{\allXsbut}{O{j} m} {\allbutlastand[#1]{#2}{x}}
\NewDocumentCommand{\allYsbut}{O{j} m} {\allbutlastand[#1]{#2}{y}}
\NewDocumentCommand{\allmusbut}{O{j} m} {\allbut[#1]{#2}{\mu}}
\NewDocumentCommand{\allMsbut}{O{j} m} {\allbut[#1]{#2}{m}}
\NewDocumentCommand{\allWsbut}{O{j} m} {\allbutlastand[#1]{#2}{w}}
```

[4] The index j is automatically replaced with k if the user issues `\allNsbut{j}`.

\allbutlastand
\allbut
\allcomponents

The \allcomponents, \allbut, and \allbutlastand macros can be used to define new entities; say, if you want to use z_i as a mole fraction, then use

```
\NewDocumentCommand{\allZsbut}{O{j} m}{\allbutlastand[#1]{#2}{z}}
```

Similarly, something meaning the concentrations of every species could be defined via

```
\NewDocumentCommand{\allCs}{O{}}{\allcomponents[#1]{C}}
```

```
\NewDocumentCommand{\allcomponents}{O{} m}{\vec{#2}}
\NewDocumentCommand{\allbut}{O{j} m m}
{ \tl_if_eq:nnTF {#1} {#2}
  { {#3}\c_math_subscript_token{k \neq #2} }
  { {#3}\c_math_subscript_token{#1 \neq #2} }
}
\NewDocumentCommand{\allbutlastand}{O{j} m m}
{ \tl_if_eq:xxTF {#2} {\ncomponents}
  { {#3}\c_math_subscript_token{#1 \neq #2} }
  { \tl_if_eq:nnTF {#1} {#2}
    { {#3}\c_math_subscript_token{k \neq #2,\ncomponents} }
    { {#3}\c_math_subscript_token{#1 \neq #2,\ncomponents} }
  }
}
```

B.4 Package Options

We define two package options that change how to render \allNs and friends.

```
\DeclareOption{moles-index}{}
\DeclareOption{moles-range}{ \@@_set_moles_range }
\cs_new:Npn \@@_set_moles_range {%
  \RenewDocumentCommand{\allcomponents}{O{} m}
  { {##2}\c_math_subscript_token 1,\dots,
        {##2}\c_math_subscript_token{\ncomponents} }
  \RenewDocumentCommand{\allbut}{O{j} m m}
  { \tl_if_eq:nnTF {##2} {1}
    { {##3}\c_math_subscript_token 2,\dots,
        {##3}\c_math_subscript_token{\ncomponents} }
    { \tl_if_eq:xxTF {##2} {\ncomponents}
      { {##3}\c_math_subscript_token 1,\dots,
          {##3}\c_math_subscript_token{\ncomponents-1} }
      { {##3}\c_math_subscript_token 1,\dots,
            [{##3}\c_math_subscript_token{##2}],
            \dots,{##3}\c_math_subscript_token{\ncomponents} }
    }
  }
  \RenewDocumentCommand{\allbutlastand}{O{j} m m}
  { \tl_if_eq:nnTF {##2} {1}
    { {##3}\c_math_subscript_token 2,\dots,
        {##3}\c_math_subscript_token{\ncomponents-1} }
    { \tl_if_eq:xxTF {##2} {\ncomponents}
      { {##3}\c_math_subscript_token 1,\dots,
        {##3}\c_math_subscript_token{\ncomponents-1}
      }
      { \tl_if_eq:xxTF {##2} {\ncomponents-1}
        { {##3}\c_math_subscript_token 1,\dots,
          {##3}\c_math_subscript_token{\ncomponents-2} }
```

```
        {
          {##3}\c_math_subscript_token 1,\dots,
          [{##3}\c_math_subscript_token{##2}],\dots,
           {##3}\c_math_subscript_token{\ncomponents-1}
        }
      }
    }
  }
}
```

The remaining options define textbook-specific notation.

```
\DeclareOption{Bejan}{
  \ExecuteOptions{EUFGHAN,intensive-lowercase,delta,shortpm}
  \AtEndOfPackage{
    \cs_set:Nn \@@_specific:n {\text_lowercase:n {#1}}
    \cs_set:Nn \@@_intensive:n {\bar{\text_lowercase:n {#1}}}
    \cs_set:Nn \@@_extensive:n {\text_uppercase:n {#1}}
    \tl_gset:Nn \g_@@_volume_symbol v
    \RenewExpandableDocumentCommand{\ncomponents}{}{n}
    \RenewSubscriptedSymbol{\Lt}{\g_@@_Helmholtz_symbol}{\mu}
    \RenewSubscriptedSymbol{\Lm}
        {\bar{\text_lowercase:n \g_@@_Helmholtz_symbol}}{\mu}
    \RenewSubscriptedSymbol{\Ls}
        {\text_lowercase:n \g_@@_Helmholtz_symbol}{\mu}
    \cs_new:Npn \Delta_vap_sym {} {}
    \NewSubscriptedSymbol{\Delta_vap}{\Delta_vap_sym}{{fg}}
    \RenewDocumentCommand{\Deltavap}{m}{
      \cs_set:Npn \Delta_vap_sym {} {#1}
      \Delta_vap
    }
    \cs_new:Npn \Delta_fus_sym {} {}
    \NewSubscriptedSymbol{\Delta_fus}{\Delta_fus_sym}{{sf}}
    \RenewDocumentCommand{\Deltafus}{m}{
      \cs_set:Npn \Delta_fus_sym {} {#1}
      \Delta_fus
    }
    \cs_new:Npn \Delta_sub_sym {} {}
    \NewSubscriptedSymbol{\Delta_sub}{\Delta_sub_sym}{{sg}}
    \RenewDocumentCommand{\Deltasub}{m}{
      \cs_set:Npn \Delta_sub_sym {} {#1}
      \Delta_sub
    }
    \RenewExpandableDocumentCommand{\heatcapacitysymbol}{}{c}
    \RenewSubscriptedSymbol{\cV}{\@@_intensive:n {\heatcapacitysymbol}}
        {\text_lowercase:n \g_@@_volume_symbol}
    \RenewSubscriptedSymbol{\cVt}{\@@_extensive:n {\heatcapacitysymbol}}
        {\text_uppercase:n \g_@@_volume_symbol}
    \RenewSubscriptedSymbol{\cVpm}{\heatcapacitysymbol}
        {\text_lowercase:n \g_@@_volume_symbol}
    \RenewSubscriptedSymbol{\cPpm}{\heatcapacitysymbol}
        {\text_lowercase:n \g_@@_pressure_symbol}
    \RenewExpandableDocumentCommand{\xrxn}{}{\zeta}
    \RenewDocumentCommand{\fmix}{}{f}
    \RenewDocumentCommand{\Qm}{}{Q}
    \RenewDocumentCommand{\Qs}{}{Q}
    \RenewExpandableDocumentCommand{\kappaT}{}{\compressibilitysymbol}
    \RenewExpandableDocumentCommand{\expansivitysymbol}{}{\beta}
```

```
    \RenewExpandableDocumentCommand{\alphaP}{}{\expansivitysymbol}
    \RenewSubscriptedSymbol{\muJT}{\JTsymbol}{J}
    \RenewDocumentCommand{\Deltaf}{m}
    { \tl_set:Nn \l_@@_Deltaf_sym_tl {#1} \@@_Deltaf }
    \RenewDocumentCommand{\Pstd}{}{P\c_math_subscript_token 0}
    \RenewDocumentCommand{\Wm}{}{W}
    \RenewDocumentCommand{\Ws}{}{W}
    \cs_new:Nn \@@_fpure_one:n
    {
      f\c_math_subscript_token{#1}
      \peek_catcode_remove:NF \c_math_superscript_token
      { \c_math_superscript_token\bullet }
    }
    \RenewDocumentCommand{\fpure}{}
    {
      \peek_catcode_remove:NTF \c_math_subscript_token
      { \@@_fpure_one:n }
      { f }
    }
    \cs_new:Nn \@@_phipure_one:n
    {
      \phi\c_math_subscript_token{#1}
      \peek_catcode:NF \c_math_superscript_token
      { \c_math_superscript_token\bullet }
    }
    \RenewDocumentCommand{\phipure}{}
    {
      \peek_catcode_remove:NTF \c_math_subscript_token
      {
        \@@_phipure_one:n
      }
      {\phi}
    }
    \RenewDocumentCommand{\phimix}{}{\phi}
  }
}
\DeclareOption{CBK}{
  \ExecuteOptions{EUAGHAN,intensive-lowercase,delta,shortpm}
  \AtEndOfPackage{
    \cs_set:Nn \@@_overline:n {\widetilde #1}
    \cs_set:Nn \@@_overline_copy:n {\widetilde #1}
    \cs_set:Nn \@@_specific:n {\text_lowercase:n {#1}}
    \cs_set:Nn \@@_intensive:n {\bar{\text_lowercase:n{#1}}}
    \tl_gset:Nn \g_@@_area_symbol A
    \RenewExpandableDocumentCommand{\reaction}{}{R}
    \cs_new:Npn \Delta_vap_sym {} {}
    \NewSubscriptedSymbol{\Delta_vap}{\Delta_vap_sym}{{fg}}
    \RenewDocumentCommand{\Deltavap}{m}{
      \cs_set:Npn \Delta_vap_sym {} {#1}
      \Delta_vap
    }
    \cs_new:Npn \Delta_fus_sym {} {}
    \NewSubscriptedSymbol{\Delta_fus}{\Delta_fus_sym}{{sf}}
    \RenewDocumentCommand{\Deltafus}{m}{
      \cs_set:Npn \Delta_fus_sym {} {#1}
      \Delta_fus
```

```
    }
    \cs_new:Npn \Delta_sub_sym {} {}
    \NewSubscriptedSymbol{\Delta_sub}{\Delta_sub_sym}{{sg}}
    \RenewDocumentCommand{\Deltasub}{m}{
      \cs_set:Npn \Delta_sub_sym {} {#1}
      \Delta_sub
    }
    \tl_gset:Nn \g_@@_pressure_symbol p
    \RenewExpandableDocumentCommand{\compressibilitysymbol}{}{\alpha}
    \RenewExpandableDocumentCommand{\expansivitysymbol}{}{\beta}
    \RenewExpandableDocumentCommand{\kappaT}{}{\compressibilitysymbol}
    \RenewExpandableDocumentCommand{\alphaP}{}{\expansivitysymbol}
    \RenewSuperscriptedSymbol{\Psat}{P}{v}
    \RenewDocumentCommand{\Deltaf}{m}
    { \tl_set:Nn \l_@@_Deltaf_sym_tl {#1}
      \@@_Deltaf
    }
    \RenewDocumentCommand{\Pstd}{}{P\c_math_subscript_token 0}
    \RenewDocumentCommand{\Lm}{}{\@@_intensive:n\omega}
    \RenewDocumentCommand{\Ls}{}{\@@_specific:n\omega}
  }
}
\DeclareOption{ElliottLira}{
  \ExecuteOptions{shortpm}
  \AtEndOfPackage{
    \cs_gset_eq:NN \@@_specific:n \@@_intensive:n
    %^^A\RenewDocumentCommand{\partialmolar}{m}{\@@_overline:n #1}
    \RenewDocumentCommand{\allcomponents}{O{} m}{#2}
    \RenewDocumentCommand{\Deltarxn}{m}{\Delta #1}
    \RenewDocumentCommand{\fusion}{}{{fus}}
    \RenewDocumentCommand{\sublimation}{}{{sub}}
    \RenewDocumentCommand{\vaporization}{}{{vap}}
    \RenewDocumentCommand{\sat}{}{{sat}}
    %^^A\RenewSubscriptedSymbol{\Henrymol}{/K}{H} %^^A FIXME
    \RenewDocumentCommand{\IG}{}{{ig}}
    \RenewDocumentCommand{\IGM}{}{{ig}}
    \RenewDocumentCommand{\IS}{}{{is}}
    \RenewDocumentCommand{\Cstd}{}{m\c_math_superscript_token \std}
    \RenewDocumentCommand{\muJT}{}{\mu\c_math_subscript_token{JT}}
  }
}
\DeclareOption{KlotzRosenberg}{
  \ExecuteOptions{delta}
  \AtEndOfPackage{
    \tl_set:Nn \l_@@_sub_separator_tl {}
    \cs_set:Nn \@@_extensive:n {#1}
    \cs_new:Nn \@@_intensive_one:n
    {
      \c_math_superscript_token {#1}
      \peek_catcode_remove:NTF \c_math_subscript_token
      { \@@_intensive_three:n }
      { \c_math_subscript_token{\mathrm{m}} }
    }
    \cs_new:Nn \@@_intensive_three:n
    { \c_math_subscript_token{\mathrm{m}\l_@@_sub_separator_tl #1} }
    \cs_new:Nn \@@_intensive_two:n
```

```
  {
    \c_math_subscript_token{\mathrm{m}\l_@@_sub_separator_tl #1}
    \peek_catcode:NF \c_math_superscript_token
    { \c_math_superscript_token\bullet }
  }
  \cs_set:Nn \@@_intensive:n
  {
    #1
    \peek_catcode_remove:NTF \c_math_superscript_token
    { \@@_intensive_one:n }
    { \peek_catcode_remove:NTF \c_math_subscript_token
      { \@@_intensive_two:n }
      { \c_math_subscript_token{\mathrm{m}} }
    }
  }
  \cs_new:Nn \@@_fpure_one:n
  {
    f\c_math_subscript_token{#1}
    \peek_catcode_remove:NF \c_math_superscript_token
    { \c_math_superscript_token\bullet }
  }
  \RenewDocumentCommand{\fpure}{}
  {
    \peek_catcode_remove:NTF \c_math_subscript_token
    { \@@_fpure_one:n }
    { f }
  }
  \cs_new:Nn \@@_phipure_one:n
  {
    \gamma\c_math_subscript_token{#1}
    \peek_catcode_remove:NF \c_math_superscript_token
    { \c_math_superscript_token\bullet }
  }
  \RenewDocumentCommand{\phipure}{}
  {
    \peek_catcode_remove:NTF \c_math_subscript_token
    { \@@_phipure_one:n }
    { \gamma }
  }
  \RenewDocumentCommand{\fmix}{}{f}
  \RenewDocumentCommand{\phimix}{}{\gamma}
  \RenewDocumentCommand{\phisat}{}{\gamma^\sat}
  \cs_if_exist:NTF \gammaup
  { \RenewDocumentCommand{\gamma}{}{\gammaup} }
  { \cs_if_exist:NT \upgamma
      { \RenewDocumentCommand{\gamma}{}{\upgamma} }
  }
  \RenewDocumentCommand{\gammarat}{}{\gamma}
  \RenewDocumentCommand{\gammamol}{}{\gamma}
  \cs_if_exist:NTF \muup
    {\RenewDocumentCommand{\mu}{}{\muup}}
    {\cs_if_exist:NT \upmu
        {\RenewDocumentCommand{\mu}{}{\upmu}}
    }
  \cs_if_exist:NTF \alphaup
    {\RenewExpandableDocumentCommand{\expansivitysymbol}{}{\alphaup}}
```

```
    {\cs_if_exist:NTF \upalpha
      {\RenewExpandableDocumentCommand{\compressibilitysymbol}{}{\alphaup}}
      {\RenewExpandableDocumentCommand{\compressibilitysymbol}{}{\alpha}}
    }
  \cs_if_exist:NTF \betaup
    {\RenewExpandableDocumentCommand{\compressibilitysymbol}{}{\betaup}}
    {\cs_if_exist:NTF \upbeta
      {\RenewExpandableDocumentCommand{\compressibilitysymbol}{}{\betaup}}
      {\RenewExpandableDocumentCommand{\compressibilitysymbol}{}{\beta}}
    }
  \cs_if_exist:NTF \xiup
    {\RenewDocumentCommand{\xrxn}{}{\xiup}}
    {\cs_if_exist:NT \upxi
        {\RenewDocumentCommand{\xrxn}{}{\upxi}}
    }
  \RenewDocumentCommand{\kappaT}{}{\compressibilitysymbol}
  \RenewDocumentCommand{\alphaP}{}{\expansivitysymbol}
  \RenewSubscriptedSymbol{\muJT}{\JTsymbol}{\text{J.T.}}
  \RenewDocumentCommand{\Deltarxn}{m}{\Delta #1}
  \RenewDocumentCommand{\Deltaf}{}{\Delta\c_math_subscript_token\formation}
  \RenewDocumentCommand{\Deltafus}{}{\Delta}
  \RenewDocumentCommand{\Deltavap}{}{\Delta}
  \RenewDocumentCommand{\Deltasub}{}{\Delta}
%^^A FIXME: should be \Delta G_{\text{mix},\mathrm{m}} not other way around
  \RenewDocumentCommand{\Deltamix}{m}{
    \tl_set:Nn \l_@@_sub_separator_tl {,}
    \Delta #1\c_math_subscript_token{\mixing}
  }
  \RenewDocumentCommand{\excess}{}{{\mathrm{E}}}
  \RenewDocumentCommand{\residual}{}{{\mathrm{R}}}
  \cs_set:Nn \@@_overline:n {#1}
  \RenewDocumentCommand{\IS}{}{{\mathrm{I}}}
  \RenewDocumentCommand{\Psat}{}
  {
    \peek_catcode:NTF \c_math_subscript_token
      {p\c_math_superscript_token\bullet}
      {p}
  }
  \RenewDocumentCommand{\Cstd}{}{m^\std}
  \RenewDocumentCommand{\Henryrat}{}{k}
  \RenewDocumentCommand{\Henrymol}{}{k''}

  % Fix partial molar properties
  \cs_set:Npn \@@_pm_case_one #1
  {
    \l_@@_pm_symbol_tl\c_math_subscript_token{\mathrm{m}#1}
  }
  \cs_set:Npn \@@_pm_case_two [#1]#2
  {
    \l_@@_pm_symbol_tl
      \c_math_superscript_token{#1}\c_math_subscript_token{\mathrm{m}#2}
  }
  \cs_set:Npn \@@_pm_case_three_part_two #1
  {
    \l_@@_pm_symbol_tl
      \c_math_superscript_token{\l_@@_pm_arg_tl}
```

```
        \c_math_subscript_token{\mathrm{m}#1}
    }
    \cs_set:Npn \@@_pm_case_four #1
    {
      \l_@@_pm_symbol_tl\c_math_superscript_token{#1}
        \c_math_subscript_token{\mathrm{m}\l_@@_pm_arg_tl}
    }
    \cs_set:Npn \@@_pm_case_five
    {
      \l_@@_pm_symbol_tl
        \c_math_subscript_token{\mathrm{m}\l_@@_pm_arg_tl}
    }

    % fix heat capacities
    \RenewSubscriptedSymbol{\cP}{\heatcapacitysymbol}
        {\g_@@_pressure_symbol\mathrm{m}}
    \RenewSubscriptedSymbol{\cV}{\heatcapacitysymbol}
        {\g_@@_volume_symbol\mathrm{m}}
    \RenewDocumentCommand{\cPpm}{}{\partialmolar{\cPt}}
    \RenewDocumentCommand{\cVpm}{}{\partialmolar{\cVt}}

    \cs_set:Npn \cP_two:n #1
    { \heatcapacitysymbol
      \c_math_subscript_token{\g_@@_pressure_symbol\mathrm{m}
        \l_@@_sub_separator_tl #1}
      \peek_catcode:NF \c_math_superscript_token
      { \c_math_superscript_token\bullet }
    }
    \cs_set:Npn \cV_two:n #1
    { \heatcapacitysymbol
      \c_math_subscript_token{\g_@@_volume_symbol\mathrm{m}
        \l_@@_sub_separator_tl #1}
      \peek_catcode:NF \c_math_superscript_token
      { \c_math_superscript_token\bullet }
    }
  }
  \AtBeginDocument{
    \@ifpackageloaded{emf}{\RenewDocumentCommand{\Epot}{}{\emf}}
    {%
      \PackageWarningNoLine{thermodynamics}
        {Package~emf~not~loaded;~load~to~make~Epot~match~Klotz~
         and~Rosenberg's~notation}%
    }
  }
}
\DeclareOption{Koretsky}{
  \ExecuteOptions{EUAGHAn,brackets,intensive-lowercase,delta,shortpm}
  \AtEndOfPackage{
    \tl_gset:Nn \g_@@_area_symbol {A}
    \RenewExpandableDocumentCommand{\std}{}{o}
    \RenewExpandableDocumentCommand{\ncomponents}{}{m}
    \RenewDocumentCommand{\partialmolar}{m}
    {
      \tl_set:Nn \l_@@_pm_symbol_tl {#1}
      \@@_generic_pm:
    }
```

```
\RenewDocumentCommand{\expansivitysymbol}{}{\beta}
\RenewDocumentCommand{\IS}{}{{\text{ideal}}}
\RenewDocumentCommand{\residual}{}{{\text{dep}}}
\RenewDocumentCommand{\IG}{}{{\text{ideal~gas}}}
\RenewDocumentCommand{\IGM}{}{{\text{ideal}}}
\RenewDocumentCommand{\Henryrat}{}{{\mathcal{H}}}
\RenewDocumentCommand{\gammarat}{}
    {\gamma\c_math_superscript_token\text{Henry's}}
\RenewDocumentCommand{\gammamol}{}{\gamma\c_math_superscript_token{m}}
\RenewDocumentCommand{\phipure}{}{\varphi}
\RenewDocumentCommand{\phimix}{}{\hat\varphi}
\RenewDocumentCommand{\phisat}{}{\varphi\c_math_superscript_token\sat}
\cs_new:Npn \Delta_fus_sym {} {}
\NewSubscriptedSymbol{\Delta_fus}{\Delta_fus_sym}{\fusion}
\RenewDocumentCommand{\Deltafus}{m}{
  \cs_set:Npn \Delta_fus_sym {} { \Delta #1 }
  \Delta_fus
}
\cs_new:Npn \Delta_vap_sym {} {}
\NewSubscriptedSymbol{\Delta_vap}{\Delta_vap_sym}{\vaporization}
\RenewDocumentCommand{\Deltavap}{m}{
  \cs_set:Npn \Delta_vap_sym {} { \Delta #1 }
  \Delta_vap
}
\cs_new:Npn \Delta_sub_sym {} {}
\NewSubscriptedSymbol{\Delta_sub}{\Delta_sub_sym}{\sublimation}
\RenewDocumentCommand{\Deltasub}{m}{
  \cs_set:Npn \Delta_sub_sym {} { \Delta #1 }
  \Delta_sub
}
\tl_new:N \l_@@_Deltaf_superscript_tl
\tl_new:N \l_@@_Deltaf_subscript_tl
\bool_new:N \l_@@_Deltaf_parentheses_bool
\tl_new:N \l_@@_Deltaf_entity_tl
\cs_set:Nn \@@_Deltaf_one:n
{
  \tl_set:Nn \l_@@_Deltaf_superscript_tl {#1}
  \peek_catcode_remove:NTF \c_math_subscript_token
  {
    \bool_set_true:N \l_@@_Deltaf_parentheses_bool
    \@@_Deltaf_two:n
  }
  {
    \bool_if:NTF \l_@@_Deltaf_parentheses_bool
    {
      (\Delta\l_@@_Deltaf_entity_tl\c_math_subscript_token\formation
        \tl_if_empty:NF \l_@@_Deltaf_superscript_tl
        { \c_math_superscript_token\l_@@_Deltaf_superscript_tl }
      )
      \tl_if_empty:NF \l_@@_Deltaf_subscript_tl
      { \c_math_subscript_token\l_@@_Deltaf_subscript_tl }
    }
    {
      \Delta\l_@@_Deltaf_entity_tl\c_math_subscript_token\formation
        \tl_if_empty:NF \l_@@_Deltaf_superscript_tl
        { \c_math_superscript_token\l_@@_Deltaf_superscript_tl }
```

```
      }
    }
  }
  \cs_set:Nn \@@_Deltaf_two:n
  {
    \tl_set:Nn \l_@@_Deltaf_subscript_tl {#1}
    % check for case 4
    \peek_catcode_remove:NTF \c_math_superscript_token
    { \@@_Deltaf_one:n }
    {
      \bool_if:NTF \l_@@_Deltaf_parentheses_bool
      {
        (\Delta\l_@@_Deltaf_entity_tl\c_math_subscript_token\formation
          \tl_if_empty:NF \l_@@_Deltaf_superscript_tl
            {\c_math_superscript_token\l_@@_Deltaf_superscript_tl}
        )
        \tl_if_empty:NF \l_@@_Deltaf_subscript_tl
          \c_math_subscript_token\l_@@_Deltaf_subscript_tl
      }
      {
        \Delta\l_@@_Deltaf_entity_tl\c_math_subscript_token\formation
          \tl_if_empty:NF \l_@@_Deltaf_superscript_tl
            {\c_math_superscript_token\l_@@_Deltaf_superscript_tl}
      }
    }
  }
  \RenewDocumentCommand{\Deltaf}{m}
  {
    \tl_clear:N \l_@@_Deltaf_superscript_tl
    \tl_clear:N \l_@@_Deltaf_subscript_tl
    \tl_set:Nn \l_@@_Deltaf_entity_tl {#1}
    \bool_set_false:N \l_@@_Deltaf_parentheses_bool
    \peek_catcode_remove:NTF \c_math_superscript_token
    {
      \@@_Deltaf_one:n
    }
    {
      \peek_catcode_remove:NTF \c_math_subscript_token
      {
        \bool_set_true:N \l_@@_Deltaf_parentheses_bool
        \@@_Deltaf_two:n
      }
      {
        \Delta #1\c_math_subscript_token \formation
      }
    }
  }
  \RenewDocumentCommand{\kappaT}{}{\compressibilitysymbol}
  \RenewDocumentCommand{\alphaP}{}{\expansivitysymbol}
  \RenewSubscriptedSymbol{\cV}{\@@_intensive:n \heatcapacitysymbol}
      {\@@_intensive:n \g_@@_volume_symbol}
  \RenewSubscriptedSymbol{\cVs}{\@@_specific:n \heatcapacitysymbol}
      {\@@_intensive:n \g_@@_volume_symbol}
  \RenewDocumentCommand{\Lm}{}{\omega}
  \RenewDocumentCommand{\Ls}{}{\hat\omega}
}
```

```
}
\DeclareOption{MSBB}{
  \ExecuteOptions{EUFGHAn,intensive-lowercase,delta,shortpm}
  \AtEndOfPackage{
    \RenewDocumentCommand{\IGM}{}{\ast} % FIXME: is this * or \circ?
    \RenewDocumentCommand{\IG}{}{\ast}
    \RenewDocumentCommand{\expansivitysymbol}{}{\beta}
    \RenewDocumentCommand{\muJT}{}{\mu\c_math_subscript_token J}
    \RenewDocumentCommand{\allcomponents}{O{} m}{#2}
    \RenewDocumentCommand{\allbut}{O{j} m m}
    {
      \tl_if_eq:nnTF {#1} {#2}
      { {#3}\c_math_subscript_token k }
      { {#3}\c_math_subscript_token{#1} }
    }
    \tl_gset_eq:NN \g_@@_Helmholtz_symbol \psi
    \RenewDocumentCommand{\Ft}{}{\Psi}
    \RenewDocumentCommand{\Fpm}{}{\partialmolar{\Psi}}
    \cs_set:Nn \@@_intensive:n {\@@_overline:n{\text_lowercase:n{#1}}}
    \cs_set:Nn \@@_specific:n {\text_lowercase:n{#1}}
    \RenewDocumentCommand{\fmix}{}{\bar f}
    \RenewDocumentCommand{\phimix}{}{\bar\phi}
    \RenewDocumentCommand{\phimix}{}{\bar\phi}
    \tl_gset:Nn \g_@@_pressure_symbol p
    \tl_gset:Nn \g_@@_volume_symbol v
    \RenewDocumentCommand{\partialmolar}{m}
    {
      \tl_set:Nn \l_@@_pm_symbol_tl {\text_uppercase:n #1}
      \@@_generic_pm:
    }
    \RenewDocumentCommand{\kappaT}{}{\compressibilitysymbol}
    \RenewDocumentCommand{\alphaP}{}{\expansivitysymbol}
    \RenewDocumentCommand{\mustd}{}{\Gm^\std}
    \RenewExpandableDocumentCommand{\formation}{}{{\mathrm{f}}}
    \RenewDocumentCommand{\Pstd}{}
      {\g_@@_pressure_symbol\c_math_subscript_token\text{ref}}
    \RenewExpandableDocumentCommand{\xrxn}{}{\varepsilon}
    \RenewExpandableDocumentCommand{\Lm}{}{\@@_intensive:n \omega}
    \RenewExpandableDocumentCommand{\Ls}{}{\@@_specific:n \omega}
    \RenewExpandableDocumentCommand{\heatcapacitysymbol}{}{C}
    \tl_new:N \l_@@_Deltaf_superscript_tl
    \tl_new:N \l_@@_Deltaf_subscript_tl
    \bool_new:N \l_@@_Deltaf_parentheses_bool
    \tl_new:N \l_@@_Deltaf_entity_tl
    \cs_set:Nn \@@_Deltaf_one:n
    {
      \tl_set:Nn \l_@@_Deltaf_superscript_tl {#1}
      \peek_catcode_remove:NTF \c_math_subscript_token
      {
        \bool_set_true:N \l_@@_Deltaf_parentheses_bool
        \@@_Deltaf_two:n
      }
      {
        \bool_if:NTF \l_@@_Deltaf_parentheses_bool
        {
          (\l_@@_Deltaf_entity_tl\c_math_subscript_token\formation
```

```
          \tl_if_empty:NF \l_@@_Deltaf_superscript_tl
          { \c_math_superscript_token\l_@@_Deltaf_superscript_tl }
        )
        \tl_if_empty:NF \l_@@_Deltaf_subscript_tl
        { \c_math_subscript_token\l_@@_Deltaf_subscript_tl }
      }
      {
        \l_@@_Deltaf_entity_tl\c_math_subscript_token{\formation}
          \tl_if_empty:NF \l_@@_Deltaf_superscript_tl
          { \c_math_superscript_token\l_@@_Deltaf_superscript_tl }
      }
    }
  }
  \cs_set:Nn \@@_Deltaf_two:n
  {
    \tl_set:Nn \l_@@_Deltaf_subscript_tl {#1}
    % check for case 4
    \peek_catcode_remove:NTF \c_math_superscript_token
    { \@@_Deltaf_one:n }
    {
      \bool_if:NTF \l_@@_Deltaf_parentheses_bool
      {
        (\l_@@_Deltaf_entity_tl\c_math_subscript_token\formation
          \tl_if_empty:NF \l_@@_Deltaf_superscript_tl
          { \c_math_superscript_token\l_@@_Deltaf_superscript_tl }
        )
        \tl_if_empty:NF \l_@@_Deltaf_subscript_tl
        { \c_math_subscript_token\l_@@_Deltaf_subscript_tl }
      }
      {
        \l_@@_Deltaf_entity_tl\c_math_subscript_token\formation
          \tl_if_empty:NF \l_@@_Deltaf_superscript_tl
          { \c_math_superscript_token\l_@@_Deltaf_superscript_tl }
      }
    }
  }
  \RenewDocumentCommand{\Deltaf}{m}
  {
    \tl_clear:N \l_@@_Deltaf_superscript_tl
    \tl_clear:N \l_@@_Deltaf_subscript_tl
    \tl_set:Nn \l_@@_Deltaf_entity_tl {#1}
    \bool_set_false:N \l_@@_Deltaf_parentheses_bool
    \peek_catcode_remove:NTF \c_math_superscript_token
    {
      \@@_Deltaf_one:n
    }
    {
      \peek_catcode_remove:NTF \c_math_subscript_token
      {
        \bool_set_true:N \l_@@_Deltaf_parentheses_bool
        \@@_Deltaf_two:n
      }
      {
        \Delta #1\c_math_subscript_token \formation
      }
    }
```

```
    }
  }
}
\DeclareOption{Prausnitz}{
  \ExecuteOptions{intensive-lowercase,shortpm}
  \AtEndOfPackage{
    \RenewExpandableDocumentCommand{\ncomponents}{}{m}
    \RenewDocumentCommand{\fmix}{}{f}
    \RenewDocumentCommand{\fsat}{}{\fpure\c_math_superscript_token\sat}
    % TODO: this should pick up H_2 and make it into H_{2,1} (assuming
    % the solvent is always 1...?)
    \RenewDocumentCommand{\Henryrat}{}{H}
    %^^A\RenewDocumentCommand{\residual}{}{{{\mathcal{R}}}}
    \RenewDocumentCommand{\allcomponents}{O{i} m}
      { {#2}\c_math_subscript_token{#1} }
    \RenewDocumentCommand{\allbut}{O{i} m m}
    { \tl_if_eq:nnTF {#1} {#2}
        { {#3}\c_math_subscript_token k }
        { {#3}\c_math_subscript_token{#1} }
    }
    \tl_set:Nn \l_@@_sub_separator_tl {\,}
    \tl_gset:Nn \g_@@_pressure_symbol {p}
    \tl_gset:Nn \g_@@_volume_symbol {v}
    \RenewSubscriptedSymbol{\fpure}{f}{{\text{pure}}}
    \RenewDocumentCommand{\phimix}{}{\varphi}
    \RenewDocumentCommand{\phisat}{}{\varphi^\sat}
    \RenewDocumentCommand{\sat}{}{s}
    \RenewDocumentCommand{\mixing}{}{\text{mixing}}
    \RenewDocumentCommand{\Lm}{}{\omega}
    \RenewDocumentCommand{\Ls}{}{\@@_specific:n \omega}
    \RenewSubscriptedSymbol{\phipure}{\varphi}{{\text{pure}}}
    \RenewDocumentCommand{\IG}{}{{\text{id}}}
    \RenewDocumentCommand{\IGM}{}{{\text{id}}}
    \RenewDocumentCommand{\IS}{}{{\text{(ideal)}}}
    \RenewExpandableDocumentCommand{\compressibilitysymbol}{}{\beta}
    \RenewDocumentCommand{\kappaT}{}{\compressibilitysymbol}
    \RenewDocumentCommand{\alphaP}{}{\expansivitysymbol}
    \RenewExpandableDocumentCommand{\std}{}{0}
    \@ifpackageloaded{emf}
      {\RenewDocumentCommand{\Epot}{}{\emf}}
      {\RenewDocumentCommand{\Epot}{}{\mathcal{E}}}
    \DeclareMathAlphabet{\mathdutchcal}{U}{dutchcal}{m}{n}
    \RenewExpandableDocumentCommand{\actrel}{}{\mathdutchcal{a}}
  }
}
\DeclareOption{Sandler}{
  \ExecuteOptions{EUAGHaN,extensive-plain,shortpm}
  \AtEndOfPackage{
    \RenewDocumentCommand{\Pvap}{}
        {{P\c_math_superscript_token{\text{vap}}}}
    \RenewDocumentCommand{\excess}{}{{\text{ex}}}
    \RenewDocumentCommand{\residual}{}{{\text{r}}}
    \RenewExpandableDocumentCommand{\ncomponents}{}{\mathcal{C}}
    \RenewDocumentCommand{\fmix}{}{\bar f}
    \RenewDocumentCommand{\fstd}{}{\bar f\c_math_superscript_token\std}
    \RenewDocumentCommand{\phimix}{}{\bar\phi}
```

```
    \RenewDocumentCommand{\allcomponents}{O{} m}{\@@_underline:n{#2}}
    \RenewDocumentCommand{\IG}{}{{\text{IG}}}
    \RenewDocumentCommand{\IGM}{}{{\text{IGM}}}
    \RenewDocumentCommand{\IS}{}{{\text{IM}}}
    \RenewDocumentCommand{\Deltamix}{m}
        {\Delta\c_math_subscript_token\mixing #1}
    \RenewDocumentCommand{\Deltarxn}{m}
        {\Delta\c_math_subscript_token\reaction #1}
    \RenewDocumentCommand{\Deltasub}{m}
        {\Delta\c_math_subscript_token\sublimation #1}
    \RenewDocumentCommand{\Deltafus}{m}
        {\Delta\c_math_subscript_token\fusion #1}
    \RenewDocumentCommand{\Deltavap}{m}
        {\Delta\c_math_subscript_token\vaporization #1}
    \RenewDocumentCommand{\Pstd}{}{\text{1~bar}
      \peek_catcode_remove:NT \c_math_subscript_token {\use_none:n}
    }
    \RenewDocumentCommand{\Cstd}{}{\text{1~molal}
      \peek_catcode_remove:NT \c_math_subscript_token {\use_none:n}
    }
    \RenewDocumentCommand{\Henryrat}{}{H}
    \RenewSubscriptedSymbol{\cV}
        {\heatcapacitysymbol}{\g_@@_volume_symbol}
    \RenewSubscriptedSymbol{\cP}
        {\heatcapacitysymbol}{\g_@@_pressure_symbol}
    \RenewSubscriptedSymbol{\cVt}
        {\Nt\heatcapacitysymbol}{\g_@@_volume_symbol}
    \RenewSubscriptedSymbol{\cPt}
        {\Nt\heatcapacitysymbol}{\g_@@_pressure_symbol}
    \RenewDocumentCommand{\formation}{}{\mathrm{f}}
    \RenewDocumentCommand{\Deltaf}{}
        {\Delta\c_math_subscript_token\formation}
    \RenewDocumentCommand{\alphaP}{}{\expansivitysymbol}
    \RenewDocumentCommand{\muJT}{}{\mu}
    \RenewDocumentCommand{\xrxn}{}{X}
  }
}
\DeclareOption{SVNAS}{
  \ExecuteOptions{extensive-superscript,shortpm}
  \AtEndOfPackage{
    \RenewDocumentCommand{\allcomponents}{O{} m}{#2}
    \RenewDocumentCommand{\allbut}{O{j} m m}
    {
      \tl_if_eq:nnTF {#1} {#2}
      { {#3}\c_math_subscript_token k }
      { {#3}\c_math_subscript_token{#1} }
    }
    \RenewDocumentCommand{\IG}{}{{ig}}
    \RenewDocumentCommand{\IGM}{}{{ig}}
    \RenewDocumentCommand{\IS}{}{{id}}
    \RenewDocumentCommand{\IS}{}{{id}}
    \RenewDocumentCommand{\fusion}{}{{sl}}
    \RenewDocumentCommand{\vaporization}{}{{vl}}
    \RenewDocumentCommand{\sublimation}{}{{vs}}
    \RenewDocumentCommand{\expansivitysymbol}{}{\beta}
    \RenewDocumentCommand{\xrxn}{}{\varepsilon}
```

```
    \RenewDocumentCommand{\Deltarxn}{m}{\Delta #1}
    \RenewDocumentCommand{\Deltamix}{m}{\Delta #1}
    \RenewSubscriptedSymbol{\cVt}
        {\Nt\heatcapacitysymbol}{\g_@@_volume_symbol}
    \RenewSubscriptedSymbol{\cPt}
        {\Nt\heatcapacitysymbol}{\g_@@_pressure_symbol}
    % FIXME
    \RenewDocumentCommand{\cP}{}
        {{\heatcapacitysymbol\c_math_subscript_token\g_@@_pressure_symbol}}
    \RenewDocumentCommand{\cV}{}
        {{\heatcapacitysymbol\c_math_subscript_token\g_@@_volume_symbol}}
    \RenewDocumentCommand{\kappaT}{}{\compressibilitysymbol}
    \RenewDocumentCommand{\alphaP}{}{\expansivitysymbol}
    \RenewDocumentCommand{\muJT}{}{\mu}
    \RenewDocumentCommand{\Cstd}{}{m\c_math_superscript_token\std
      \peek_catcode_remove:NT \c_math_subscript_token {\use_none:n}
    }
    \RenewDocumentCommand{\mustd}{}{\Gm\c_math_superscript_token\std}
    \RenewDocumentCommand{\Henryrat}{}{\mathcal{H}}
    \RenewDocumentCommand{\formation}{}
    {
      \tl_set:Nn \l_@@_sub_separator_tl {}
      f298
    }
    \cs_set:Nn \@@_specific:n {#1}
  }
}
\DeclareOption{ModellReid}{\ExecuteOptions{TesterModell}}
\DeclareOption{TesterModell}{
  \ExecuteOptions{EUAGHaN,delta,shortpm}
  \AtEndOfPackage{
    \cs_set:Nn \@@_specific:n {\text_lowercase:n{#1}}
    \RenewExpandableDocumentCommand{\ncomponents}{}{n}
    \RenewDocumentCommand{\allcomponents}{O{i} m}
    {
      {#2}\c_math_subscript_token{#1}
    }
    \RenewDocumentCommand{\allbut}{O{i} m m}
    { \tl_if_eq:nnTF {#1} {#2}
      { {#3}\c_math_subscript_token{k}[#2] }
      { {#3}\c_math_subscript_token{#1}[#2] }
    }
    \RenewDocumentCommand{\allbutlastand}{O{j} m m}
    { \tl_if_eq:xxTF {#2} {\ncomponents}
      { {#3}\c_math_subscript_token{#1}\relax[#2] }
      { \tl_if_eq:nnTF {#1} {#2}
        { {#3}\c_math_subscript_token{k}[#2,\ncomponents] }
        { {#3}\c_math_subscript_token{#1}[#2,\ncomponents] }
      }
    }
    \RenewDocumentCommand{\IG}{}{{o}}
    \RenewDocumentCommand{\IGM}{}{{o}}
    \RenewDocumentCommand{\IS}{}{{ID}}
    \RenewDocumentCommand{\excess}{}{{EX}}
    \RenewDocumentCommand{\reaction}{}{{rx}}
    \RenewDocumentCommand{\Henryrat}{}
```

```
        {f\c_math_superscript_token{\ast\ast}}
    \RenewDocumentCommand{\Henrymol}{}{f\c_math_superscript_token\ast}
    \cs_if_exist:NTF \gammaup
    { \RenewDocumentCommand{\gamma}{}{\gammaup} }
    { \cs_if_exist:NT \upgamma
        { \RenewDocumentCommand{\gamma}{}{\upgamma} }
    }
    \RenewDocumentCommand{\gammarat}{}
        {\gamma\c_math_superscript_token{\ast\ast}}
    \RenewDocumentCommand{\gammamol}{}
        {\gamma\c_math_superscript_token\ast}
    \RenewExpandableDocumentCommand{\JTsymbol}{}{\alpha}
    \RenewSubscriptedSymbol{\muJT}{\JTsymbol}{H}
    \cs_if_exist:NTF \xiup
    { \RenewDocumentCommand{\xrxn}{}{\xiup} }
    { \cs_if_exist:NT \upxi
        { \RenewDocumentCommand{\xrxn}{}{\upxi} }
    }
    \cs_if_exist:NTF \phiup
    {
      \RenewDocumentCommand{\phipure}{}{\phiup}
      \RenewDocumentCommand{\phimix}{}{\hat\phiup}
      \RenewDocumentCommand{\phisat}{}{\phiup\c_math_superscript_token\sat}
    }
    { \cs_if_exist:NT \upphi
      {
        \RenewDocumentCommand{\phipure}{}{\upphi}
        \RenewDocumentCommand{\phimix}{}{\hat\upphi}
        \RenewDocumentCommand{\phisat}{}{\upphi\c_math_superscript_token\sat}
      }
    }
    \RenewDocumentCommand{\Cstd}{}{m\c_math_superscript_token+
      \peek_catcode_remove:NT \c_math_subscript_token {\use_none:n}
    }
    \cs_if_exist:NTF \muup
    { \RenewDocumentCommand{\mu}{}{\muup} }
    { \cs_if_exist:NT \upmu
      { \RenewDocumentCommand{\mu}{}{\upmu} }
    }
    \RenewDocumentCommand{\std}{}{o}
    \RenewDocumentCommand{\Pstd}{}{P^\ast}
    \tl_gset:Nn \g_@@_area_symbol {\text{\large\(\mathit{a}\)}}
    \RenewDocumentCommand{\Epot}{}{\exists}
    \tl_set:Nn \l_@@_sub_separator_tl {}
    \tl_gset:Nn \g_@@_pressure_symbol {p}
    \RenewSubscriptedSymbol{\cVt}{\@@_extensive:n {\heatcapacitysymbol}}{v}
    \RenewSubscriptedSymbol{\cV}{\@@_intensive:n {\heatcapacitysymbol}}{v}
    \RenewSubscriptedSymbol{\cVs}{\@@_specific:n {\heatcapacitysymbol}}{v}
  }
}
\DeclareOption{Thompson}{
  \ExecuteOptions{EUAGHAn,delta,shortpm}
  \AtEndOfPackage
  {
    \RenewDocumentCommand{\excess}{}{{EX}}
    \RenewDocumentCommand{\residual}{}{{R}}
```

```
\RenewDocumentCommand{\actrel}{}{\widehat{a}}
\RenewSubscriptedSymbol{\Henryrat}{k}{H}
\RenewSubscriptedSymbol{\Henrymol}{k}{H}
\RenewDocumentCommand{\allcomponents}{O{j} m}
{
  {#2}\c_math_subscript_token{#1}
}
\RenewDocumentCommand{\allNs}{O{j}}{\allcomponents[#1]{\Nt}}
\RenewDocumentCommand{\allXs}{O{j}}{\allcomponents[#1]{x}}
\RenewDocumentCommand{\allYs}{O{j}}{\allcomponents[#1]{y}}
\RenewDocumentCommand{\allmus}{O{j}}{\allcomponents[#1]{\mu}}
\RenewDocumentCommand{\allMs}{O{j}}{\allcomponents[#1]{m}}
\RenewDocumentCommand{\allWs}{O{j}}{\allcomponents[#1]{w}}
\RenewExpandableDocumentCommand{\ncomponents}{}{c}
\RenewDocumentCommand{\IS}{}{{IS}}
\RenewDocumentCommand{\IG}{}{{IG}}
\RenewDocumentCommand{\IGM}{}{{IG}}
\cs_new:Nn \@@_fpure_one:n
{
  f\c_math_subscript_token{#1}
  \peek_catcode_remove:NF \c_math_superscript_token
  { \c_math_superscript_token\bullet }
}
\RenewDocumentCommand{\fpure}{}
{
  \peek_catcode_remove:NTF \c_math_subscript_token
  { \@@_fpure_one:n }
  { f }
}
\cs_new:Nn \@@_intensive_two:n
{
  \c_math_subscript_token{#1}
  \peek_catcode:NF \c_math_superscript_token
  {
    \c_math_superscript_token\bullet
  }
}
\cs_set:Nn \@@_intensive:n
{
  #1
  \peek_catcode_remove:NT \c_math_subscript_token
  { \@@_intensive_two:n }
}
\cs_new:Nn \@@_phipure_one:n
{
  \phi\c_math_subscript_token{#1}
  \peek_catcode:NF \c_math_superscript_token
  { \c_math_superscript_token\bullet }
}
\RenewDocumentCommand{\phipure}{}
{
  \peek_catcode_remove:NTF \c_math_subscript_token
  {
    \@@_phipure_one:n
  }
  {\phi}
```

```
    }
    \RenewDocumentCommand{\phimix}{}{\widehat\phi}
    \RenewDocumentCommand{\fmix}{}{\widehat f}
    \RenewDocumentCommand{\mixing}{}{{MIX}}
    \RenewDocumentCommand{\muJT}{}{\alpha\c_math_subscript_token H}
    \RenewDocumentCommand{\Deltamix}{m}
        {\Delta\c_math_subscript_token\mixing #1}
    \RenewDocumentCommand{\reaction}{}{R}
    \RenewDocumentCommand{\fusion}{}{{SL}}
    \RenewDocumentCommand{\vaporization}{}{{LV}}
    \RenewDocumentCommand{\sublimation}{}{{SV}}
    \RenewDocumentCommand{\allbut}{O{j} m m}
    { \tl_if_eq:nnTF {#1} {#2}
      {
        {#3}\c_math_subscript_token k\neq{#3}\c_math_subscript_token{#2}
      }
      {
        {#3}\c_math_subscript_token{#1}\neq{#3}\c_math_subscript_token{#2}
      }
    }
    \RenewDocumentCommand{\Cstd}{}{m^\std}
    \RenewDocumentCommand{\mustd}{}{\Gamma}
    \RenewDocumentCommand{\formation}{}{F}
%^^A    \RenewDocumentCommand{\Deltarxn}{}{\Delta}
  }
}
```

We execute the default options below.

```
\ExecuteOptions{EUAGHan,subscripts,parentheses,intensive-plain,
    moles-index,longpm}
\ProcessOptions
```

B.5 Variable Order

We next encode a routine to sort non-subscripted variables into a consistent order. It currently does not sort variables with subscripts.

```
\tl_const:Nn \c_@@_sort_order_tl
    {\Et\Em\Es\Ut\Um\Us\Ht\Hm\Hs\Ft\Fm\Fs\Gt\Gm\Gs\Lt\Lm\Ls T\St\Sm\Ss
        P\Vt\Vm\Vs\mu\Nt mwxyz\At\Am\As\sigma
        ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklnopqrstuvwxyz}
\clist_new:N \l_@@_in_list_clist
\clist_new:N \l_@@_sorted_list_clist
\clist_new:N \l_@@_remaining_list_clist
\cs_new:Nn \@@_sort_clist:n
{% Sort the list in the order of \c_@@_sort_order_tl

  % Wipe out any remnants from the last sort
  \clist_clear:N \l_@@_in_list_clist
  \clist_clear:N \l_@@_sorted_list_clist

  % Make a copy of the list
  \clist_set:Nn \l_@@_remaining_list_clist {#1}

  % Make a list of everything that's in the known sort order list
  % and put everything else in the "not in sort order list" list.
  \tl_map_inline:Nn \c_@@_sort_order_tl
```

```
  {
    \clist_if_in:NnT \l_@@_remaining_list_clist {##1}
    { \clist_put_right:Nn \l_@@_in_list_clist {##1} }

    \clist_remove_all:Nn \l_@@_remaining_list_clist {##1}
  }

  % Then merge the lists back together again.
  \clist_if_empty:NF \l_@@_in_list_clist
  {
    \clist_put_right:Nn \l_@@_sorted_list_clist \l_@@_in_list_clist
  }
  \clist_if_empty:NF \l_@@_remaining_list_clist
  {
    \clist_put_right:Nn \l_@@_sorted_list_clist \l_@@_remaining_list_clist
  }
  \clist_use:Nn \l_@@_sorted_list_clist ,
}
```

B.6 Commands for Partial Derivatives

The `\Partial` command and its second-order siblings are defined as below. They typeset partial derivatives of the first argument with respect to the second (and third, in the case of mixed second partial derivatives) arguments, holding the last argument constant.

The starred forms adjust the spacing after the partial derivative so the trailing binary operator (assumed to be the same width as an equals sign) overhangs the variables held constant. We thus set `operator_width` to be *just* greater than the width of an equals sign.

```
\dim_new:N \l_@@_Partial_const_dim
\dim_new:N \l_@@_operator_width_dim
\dim_new:N \l_@@_adjust_width_dim
\settowidth{\l_@@_operator_width_dim}{=}
\dim_set:Nn \l_@@_adjust_width_dim {0.1\l_@@_operator_width_dim}
\dim_add:Nn \l_@@_operator_width_dim \l_@@_adjust_width_dim
```

`\Partial` The command `\Partial` and its friends drastically simplify the creation of partial derivatives. The command `\Partial*` is the same as `\Partial` except that it adjusts the spacing so the (presumably) binary operator that follows it slightly overlaps the subscripts.

```
\tl_new:N \l_@@_Partial_start_tl
\tl_new:N \l_@@_Partial_end_tl
\tl_new:N \l_@@_Partial_empty_end_tl
\tl_new:N \l_@@_Partial_middle_tl
\tl_set:Nn \l_@@_Partial_start_tl {\left\l_@@_PartialOpen_tl}
\tl_set:Nn \l_@@_Partial_end_tl {\right\l_@@_PartialClose_tl}
\tl_set:Nn \l_@@_Partial_empty_end_tl {\right\l_@@_PartialEmptyClose_tl}
\tl_set:Nn \l_@@_Partial_middle_tl {\middle}
\cs_set_eq:NN \@@_frac:nn \frac
\cs_new:Npn \PartialStar #1#2#3
{ \settowidth{\l_@@_Partial_const_dim}{\ensuremath{#3}}%
  \dim_add:Nn \l_@@_Partial_const_dim {-0.20\l_@@_Partial_const_dim}%
  \PartialNoStar{#1}{#2}{#3}%
  \bool_if:NT \l_@@_subscripted_bool
```

```
  { \dim_compare:nNnTF \l_@@_operator_width_dim
                       < \l_@@_Partial_const_dim
    { \kern -\l_@@_operator_width_dim }
    { \kern -\l_@@_Partial_const_dim }
  }
}
\cs_new:Npn \PartialNoStar #1#2#3
{ \bool_if:NTF \l_@@_subscripted_bool
  {% Handle case of empty variables held constant
    \tl_if_eq:nnTF {#3} {}
    { \l_@@_Partial_start_tl
      \@@_frac:nn{\partial #1}{\partial #2}\l_@@_Partial_empty_end_tl
    }
    { \l_@@_Partial_start_tl\@@_frac:nn{\partial #1}
                                       {\partial #2}\l_@@_Partial_end_tl
      \c_math_subscript_token{#3}%
    }
  }
  {% Check whether #3 contains \allNsbut{i} and #2 is \Nt_i
    \tl_if_in:nnTF {#2} {\Nt}
    { \RenewDocumentCommand{\allbut}{O{j} m m}{\allcomponents{##3}}
      \l_@@_Partial_start_tl
      \@@_frac:nn{\partial #1(\@@_sort_clist:n{#3})}
                 {\partial #2}\l_@@_Partial_end_tl
    }
    { \l_@@_Partial_start_tl
      \@@_frac:nn{\partial #1(\@@_sort_clist:n{#2,#3})}
                 {\partial #2}\l_@@_Partial_end_tl
    }
  }
}
\NewDocumentCommand{\Partial}{s m m m}
{ \IfBooleanTF {#1}
  { \PartialStar{#2}{#3}{#4} }
  { \PartialNoStar{#2}{#3}{#4} }
}
```

\PartialBigg The \PartialBigg macro (and its starred form) replace the \left and \right commands in \Partial with amsmath's \Biggl and \Biggr variants. The starred form is inherited from \Partial without modification.

```
\NewDocumentCommand{\PartialBigg}{}
  { \tl_set:Nn \l_@@_Partial_start_tl {\Biggl\l_@@_PartialOpen_tl}
    \tl_set:Nn \l_@@_Partial_end_tl {\Biggr\l_@@_PartialClose_tl}
    \tl_set:Nn \l_@@_Partial_Empty_end_tl
        {\Biggr\l_@@_PartialEmptyClose_tl}
    \Partial
  }
```

\Partialbigg The \Partialbigg macro does the same thing as \PartialBigg, except using amsmath's \biggl/\biggr variants.

```
\NewDocumentCommand{\Partialbigg}{}
  { \tl_set:Nn \l_@@_Partial_start_tl {\biggl\l_@@_PartialOpen_tl}
    \tl_set:Nn \l_@@_Partial_end_tl {\biggr\l_@@_PartialClose_tl}
    \tl_set:Nn \l_@@_Partial_empty_end_tl
        {\biggr\l_@@_PartialEmptyClose_tl}
    \Partial
```

```
}
```

\PartialSecond The second partial derivatives are defined similarly to \Partial.

```
\cs_new:Npn \PartialSecondStar #1#2#3
{ \settowidth{\l_@@_Partial_const_dim}{\ensuremath{#3}}%
  \dim_add:Nn \l_@@_Partial_const_dim {-0.20\l_@@_Partial_const_dim}
  \PartialSecondNoStar{#1}{#2}{#3}%
  \bool_if:nT \l_@@_subscripted_bool
  {  \dim_compare:nNnTF {\l_@@_operator_width_dim}
                        < {\l_@@_Partial_const_dim}
    { \kern -\l_@@_operator_width_dim }
    { \kern -\l_@@_Partial_const_dim }
  }
}
\cs_new:Npn \PartialSecondNoStar #1#2#3
{ \bool_if:NTF \l_@@_subscripted_bool
  {% Handles case of empty variables held constant
    \tl_if_eq:nnTF {#3} {}
    { \l_@@_Partial_start_tl
          \@@_frac:nn{\partial\c_math_superscript_token 2 #1}
      {\partial #2\c_math_superscript_token 2}\l_@@_Partial_empty_end_tl
    }
    { \l_@@_Partial_start_tl
      \@@_frac:nn{\partial\c_math_superscript_token 2 #1}
          {\partial #2\c_math_superscript_token 2}\l_@@_Partial_end_tl
          \c_math_subscript_token{#3}%
    }
  }
  {% Check whether #3 contains \allNsbut{i} and #2 is \Nt_i
    \tl_if_in:nnTF {#1} {\Nt}
    { \RenewDocumentCommand{\allbut}{O{j} m m}{\allcomponents{##3}}
      \l_@@_Partial_start_tl
      \@@_frac:nn{\partial\c_math_superscript_token 2 #1(#3)}
          {\partial\c_math_superscript_token 2 #2}\l_@@_Partial_end_tl
    }
    { \l_@@_Partial_start_tl
      \@@_frac:nn{\partial\c_math_superscript_token 2
                    #1(\@@_sort_clist:n{#2,#3})}
          {\partial #2\c_math_superscript_token 2}\l_@@_Partial_end_tl
    }
  }
}
\NewDocumentCommand{\PartialSecond}{s m m m}
{
  \IfBooleanTF {#1}
  { \PartialSecondStar{#2}{#3}{#4} }
  { \PartialSecondNoStar{#2}{#3}{#4} }
}
```

\PartialSecondBigg The \PartialSecondBigg macro and its starred variant replace \left and \right with amsmath's \Biggl and \Biggr.

```
\NewDocumentCommand{\PartialSecondBigg}{}
{ \tl_set:Nn \l_@@_Partial_start_tl {\biggl\l_@@_PartialOpen_tl}
  \tl_set:Nn \l_@@_Partial_end_tl {\biggl\l_@@_PartialClose_tl}
  \tl_set:Nn \l_@@_Partial_empty_end_tl {\biggl\l_@@_PartialClose_tl}
  \PartialSecond
```

```
}
```

\PartialSecondbigg The \PartialSecondbigg macro and its starred variant replace \left and \right with amsmath's \biggl and \biggr.

```
\NewDocumentCommand{\PartialSecondbigg}{}
{ \tl_set:Nn \l_@@_Partial_start_tl {\biggl\l_@@_PartialOpen_tl}
  \tl_set:Nn \l_@@_Partial_end_tl {\biggl\l_@@_PartialClose_tl}
  \tl_set:Nn \l_@@_Partial_empty_end_tl {\biggl\l_@@_PartialClose_tl}
  \PartialSecond
}
```

\PartialMixSecond The macro \PartialMixSecond takes an extra argument, but is otherwise the same as its same-variable cousin.

```
\bool_new:N \l_@@_has_x_or_y_bool
\cs_new:Npn \PartialMixSecondStar #1#2#3#4
{ \settowidth{\l_@@_Partial_const_dim}{\ensuremath{#3}}%
  \dim_add:Nn \l_@@_Partial_const_dim {-0.20\l_@@_Partial_const_dim}
  \PartialMixSecond{#1}{#2}{#3}{#4}
  \bool_if:nT \l_@@_subscripted_bool
  { \dim_compare:nNnTF {\l_@@_operator_width_dim}
                       < {\l_@@_Partial_const_dim}
    { \kern -\l_@@_operator_width_dim }
    { \kern -\l_@@_Partial_const_dim }
  }
}
\cs_new:Npn \PartialMixSecondNoStar #1#2#3#4
{ \bool_if:nTF \l_@@_subscripted_bool
  {% subscripted version
    \tl_if_eq:nnTF {#4} {}
    {% Handle case of empty variables held constant
      \l_@@_Partial_start_tl
      \@@_frac:nn{\partial\c_math_superscript_token 2 #1}
          {\partial #2\partial #3}\l_@@_Partial_empty_end_tl
    }
    { \l_@@_Partial_start_tl
      \@@_frac:nn{\partial\c_math_superscript_token 2 #1}
          {\partial #2\partial #3}\l_@@_Partial_end_tl
          \c_math_subscript_token{#4}
    }
  }
  {% not subscripted
    \tl_if_eq:nnTF {#4} {}
    {% empty argument
      \l_@@_Partial_start_tl
      \@@_frac:nn{\partial\c_math_superscript_token 2
                      #1(\@@_sort_clist:n{#2,#3,#4})}
                  {\partial #2\partial #3}\l_@@_Partial_empty_end_tl
    }
    {% Check whether #2 OR #3 are \Nt_i/etc.
      \tl_if_in:nnTF {#2} {\Nt}
      { \RenewDocumentCommand{\allbut}{O{j} m m}{\allcomponents{##3}}%
        \l_@@_Partial_start_tl
        \@@_frac:nn{\partial\c_math_superscript_token 2
                      #1(\@@_sort_clist:n{#3,#4})}
                    {\partial #2\partial #3}\l_@@_Partial_end_tl
      }
```

```
      { \tl_if_in:nnTF {#3} {\Nt}
        { \RenewDocumentCommand{\allbut}{O{j} m m}{\allcomponents{##3}}%
          \l_@@_Partial_start_tl
          \@@_frac:nn{\partial\c_math_superscript_token 2
                          #1(\@@_sort_clist:n{#2,#4})}
                      {\partial #2\partial #3}\l_@@_Partial_end_tl
        }
        {% Check for x, y, or w
          \bool_set_false:N \l_@@_has_x_or_y_bool
          \tl_if_in:nnT {#2} {x}
          { \l_@@_has_x_or_y_bool }
          \tl_if_in:nnT {#2} {y}
          { \l_@@_has_x_or_y_bool }
          \tl_if_in:nnT {#2} {w}
          { \l_@@_has_x_or_y_bool }
          \bool_if:NTF \l_@@_has_x_or_y_bool
          { \RenewDocumentCommand{\allbutlastand}{O{j} m m}
              {\allcomponents{##3}}
            \l_@@_Partial_start_tl
            \@@_frac:nn{\partial\c_math_superscript_token 2
                          #1(\@@_sort_clist:n{#3,#4})}
                        {\partial #2\partial #3}\l_@@_Partial_end_tl
          }
          {
            \l_@@_Partial_start_tl
            \@@_frac:nn{\partial\c_math_superscript_token 2
                          #1(\@@_sort_clist:n{#2,#3,#4})}
                        {\partial #2\partial #3}\l_@@_Partial_end_tl
          }
        }
      }
    }
  }
}
\NewDocumentCommand{\PartialMixSecond}{s m m m m}
{
  \IfBooleanTF {#1}
  { \PartialMixSecondStar{#2}{#3}{#4}{#5} }
  { \PartialMixSecondNoStar{#2}{#3}{#4}{#5} }
}
```

\PartialMixSecondBigg
\PartialMixSecondbigg

The macro \PartialMixSecondBigg is analogous to the aforementioned macros \PartialBigg and \PartialSecondBigg. \PartialMixSecondbigg is analogous to \Partialbigg and \PartialSecondbigg.

```
\NewDocumentCommand{\PartialMixSecondBigg}{}
{ \tl_set:Nn \l_@@_Partial_start_tl {\Biggl\l_@@_PartialOpen_tl}
  \tl_set:Nn \l_@@_Partial_end_tl {\Biggl\l_@@_PartialClose_tl}
  \tl_set:Nn \l_@@_Partial_empty_end_tl {\Biggl\l_@@_PartialClose_tl}
  \PartialMixSecond
}
\NewDocumentCommand{\PartialMixSecondbigg}{}
{ \tl_set:Nn \l_@@_Partial_start_tl {\biggl\l_@@_PartialOpen_tl}
  \tl_set:Nn \l_@@_Partial_end_tl {\biggl\l_@@_PartialClose_tl}
  \tl_set:Nn \l_@@_Partial_empty_end_tl {\biggl\l_@@_PartialClose_tl}
  \PartialMixSecond
}
```

If the user does not load the amsmath package, we will not have access to \Biggl, \Biggr, \biggl, and \biggr, so we revert them back to the ordinary \left and \right versions and warn the user.

```
\AtBeginDocument{%
  \@ifpackageloaded{amsmath}{}{%
      \PackageWarningNoLine{thermodynamics}
        {Package~amsmath~not~loaded;~load~to~make~PartialBigg~and~friends~
            work~correctly}%
      \cs_set_eq:NN \PartialBigg \Partial
      \cs_set_eq:NN \Partialbigg \Partial
      \cs_set_eq:NN \PartialSecondBigg \PartialSecond
      \cs_set_eq:NN \PartialSecondbigg \PartialSecond
      \cs_set_eq:NN \PartialMixSecondBigg \PartialMixSecond
      \cs_set_eq:NN \PartialMixSecondbigg \PartialMixSecond
      \ProvideDocumentCommand{\rvert}{}{|}
      \ProvideDocumentCommand{\lvert}{}{|}
  }%
}
```

\Partialinline
\PartialSecondinline
\PartialMixSecondinline

Inline partial derivatives.

```
\NewDocumentCommand{\Partialinline}{}
{
  \cs_set:Nn \@@_frac:nn { ##1 \l_@@_Partial_middle_tl / ##2 }
  \Partial
}
\NewDocumentCommand{\PartialSecondinline}{}
{
  \cs_set:Nn \@@_frac:nn { ##1 \l_@@_Partial_middle_tl / ##2 }
  \PartialSecond
}
\NewDocumentCommand{\PartialMixSecondinline}{}
{
  \cs_set:Nn \@@_frac:nn { ##1 \l_@@_Partial_middle_tl / ##2 }
  \PartialMixSecond
}
```

\Partialinlinetext
\PartialSecondinlinetext
\PartialMixSecondinlinetext

Text-only (non-extensible delimiter) versions of \Partialinline and friends.

```
\NewDocumentCommand{\Partialinlinetext}{}
{ \cs_set_eq:NN \l_@@_Partial_start_tl \l_@@_PartialOpen_tl
  \cs_set_eq:NN \l_@@_Partial_end_tl \l_@@_PartialClose_tl
  \cs_set_eq:NN \l_@@_Partial_empty_end_tl \l_@@_PartialEmptyClose_tl
  \cs_set_eq:NN \l_@@_Partial_middle_tl \relax
  \Partialinline
}
\NewDocumentCommand{\PartialSecondinlinetext}{}
{ \cs_set_eq:NN \l_@@_Partial_start_tl \l_@@_PartialOpen_tl
  \cs_set_eq:NN \l_@@_Partial_end_tl \l_@@_PartialClose_tl
  \cs_set_eq:NN \l_@@_Partial_empty_end_tl \l_@@_PartialEmptyClose_tl
  \cs_set_eq:NN \l_@@_Partial_middle_tl \relax
  \PartialSecondinline
}
\NewDocumentCommand{\PartialMixSecondinlinetext}{}
{ \cs_set_eq:NN \l_@@_Partial_start_tl \l_@@_PartialOpen_tl
  \cs_set_eq:NN \l_@@_Partial_end_tl \l_@@_PartialClose_tl
  \cs_set_eq:NN \l_@@_Partial_empty_end_tl \l_@@_PartialEmptyClose_tl
```

```
  \cs_set_eq:NN \l_@@_Partial_middle_tl \relax
  \PartialMixSecondinline
}
```

B.7 Local Override of Delimiters

We define several environments that *locally* override the delimiters on partial derivatives generated with `\Partial` and friends, the subscript notation for partial derivatives, and/or the definitions of range-oriented macros such as `\allNs`. These environments can be nested; the inner-most one will be honored if conflicts occur.

`thermoparentheses` (*env.*) Inside this environment, partial derivatives will have parentheses around them, regardless of package options.

```
\NewDocumentEnvironment{thermoparentheses}{}
{ \cs_set:Nn \l_@@_PartialOpen_tl {(}
  \cs_set:Nn \l_@@_PartialClose_tl {)}
  \cs_set:Nn \l_@@_PartialEmptyClose_tl {)}
}{}
```

`thermobrackets` (*env.*) Inside this environment, partial derivatives will have brackets around them, regardless of package options.

```
\NewDocumentEnvironment{thermobrackets}{}
{ \tl_set:Nn \l_@@_PartialOpen_tl {[}
  \tl_set:Nn \l_@@_PartialClose_tl {]}
  \tl_set:Nn \l_@@_PartialEmptyClose_tl {]}
}{}
```

`thermobraces` (*env.*) Inside this environment, partial derivatives will have braces around them, regardless of package options.

```
\NewDocumentEnvironment{thermobraces}{}
{ \tl_set:Nn \l_@@_PartialOpen_tl {\{}
  \tl_set:Nn \l_@@_PartialClose_tl {\}}
  \tl_set:Nn \l_@@_PartialEmptyClose_tl {\}}
}{}
```

`thermobar` (*env.*) Inside this environment, partial derivatives will have a trailing vertical bar, regardless of package options.

```
\NewDocumentEnvironment{thermobar}{}
{ \tl_set:Nn \l_@@_PartialOpen_tl {.}
  \tl_set:Nn \l_@@_PartialClose_tl {\rvert}
  \tl_set:Nn \l_@@_PartialEmptyClose_tl {.}
}{}
```

`thermoplain` (*env.*) Inside this environment, partial derivatives will have no decorations around them, regardless of package options.

```
\NewDocumentEnvironment{thermoplain}{}
{ \tl_set:Nn \l_@@_PartialOpen_tl {.}
  \tl_set:Nn \l_@@_PartialClose_tl {.}
  \tl_set:Nn \l_@@_PartialEmptyClose_tl {.}
  \bool_set_false:N \l_@@_subscripted_bool
}{}
```

`thermoNOsubscripts` (*env.*) Inside this environment, subscripts will not be displayed to the right of partial derivatives, regardless of package options.

```
\NewDocumentEnvironment{thermoNOsubscripts}{}
    {\bool_set_false:N \l_@@_subscripted_bool}
    {}
```

`thermosubscripts` (*env.*) Inside this environment, subscripts will be displayed to the right of partial derivatives, regardless of package options.

```
\NewDocumentEnvironment{thermosubscripts}{}
    {\bool_set_true:N \l_@@_subscripted_bool}
    {}
```

`thermomolesrange` (*env.*) Inside this environment, the macro `\allNs` will expand to $n_1, \ldots, n_C$ (or equivalent symbols if `\Nt` and/or `\ncomponents` have been redefined), regardless of package options. Similar expansions will result for `\allXs`, `\allYs`, `\allMs`, and so on.

```
\NewDocumentEnvironment{thermomolesrange}{}
    { \@@_set_moles_range }
    {}
```

`thermointensiveplain` (*env.*)

```
%    \begin{macrocode}
\NewDocumentEnvironment{thermointensiveplain}{}
    { \@@_set_intensive_plain }
    {}
```

`thermoextensiveplain` (*env.*)

```
\NewDocumentEnvironment{thermoextensiveplain}{}
    { \@@_set_extensive_plain }
    {}
```

`thermointensivelowercase` (*env.*)

```
\NewDocumentEnvironment{thermointensivelowercase}{}
    {% {
% \RenewExpandableDocumentCommand{\MacroFont}{}{
%   \fontencoding\encodingdefault
%   \fontfamily\ttdefault
%   \fontseries\mddefault
%   \fontshape\shapedefault
%   \footnotesize}

      \@@_set_intensive_lowercase
      \@@_set_lowercase_pms
    }
    {}
```

`thermoextensivesuperscript` (*env.*)

```
\NewDocumentEnvironment{thermoextensivesuperscript}{}
    {
      \@@_set_extensive_superscripts
    }
    {}
```

B.8 User-Interface Macros to Define Symbols

`\NewSubscriptedSymbol` First, we define a command that serves to create "subscripted" symbols; for example, typing `\cP_i` should yield $C_{P,i}$ rather than C_{Pi}, C_{P_i}, or C_{P_i}. Superscripts are also handled properly and can be in either order.

```
\str_new:N \l_@@_tmp_str
\cs_new:Npn \@@_check_definable:nN #1#2
{
  \tl_trim_spaces_apply:nN {#1} \tl_if_single_token:nTF
  {
    \str_set:Nx \l_@@_tmp_str {\tl_to_str:n {#1}}
    \int_compare:nNnT {\str_count:N \l_@@_tmp_str} = 1
    { \PackageError{thermodynamics}
        {First~argument~of~'\tl_trim_spaces:o {\tl_to_str:n {#2}}'~
         must~be~a~command}
        {The~first~argument~of~'\tl_trim_spaces:o {\tl_to_str:n {#2}}'~
         should~be~the~macro~that~will~be~used~to~refer~to~the~symbol.~
         The~provided~argument~'\tl_trim_spaces:o {\tl_to_str:n {#1}}'~
         is~a~single~character.
         \MessageBreak Perhaps~a~backslash~is~missing?}
    }
  }
  { \PackageError{thermodynamics}
      {First~argument~of~'\tl_trim_spaces:o {\tl_to_str:n {#2}}'~
       must~be~a~command}
      {The~first~argument~of~'\tl_trim_spaces:o {\tl_to_str:n {#2}}'~
       should~be~the~macro~that~will~be~used~to~refer~to~the~symbol.~
       The~provided~argument~'\tl_trim_spaces:o {\tl_to_str:n {#1}}'~
       contains~more~than~one~token.
       \MessageBreak Perhaps~a~backslash~is~missing?}
  }
}
\tl_new:N \l_@@_super_separator_tl
\tl_new:N \l_@@_sub_separator_tl
\tl_set:Nn \l_@@_super_separator_tl {,}
\tl_set:Nn \l_@@_sub_separator_tl {,}
\NewDocumentCommand{\NewSubscriptedSymbol}{m m m}
{
  \@@_check_definable:nN {#1} \NewSubscriptedSymbol
  \cs_if_exist:NT #1
  { \PackageError{thermodynamics}
      {Command~'\tl_trim_spaces:o {\tl_to_str:n {#1}}'~already~defined}
      {You~have~used~
       '\tl_trim_spaces:o {\tl_to_str:n {\NewSubscriptedSymbol}}'~
       with~a~command~that~already~has~a~definition}
  }
  \cs_new:cpn {\cs_to_str:N #1_one:n} ##1
  {
    {#2}\c_math_superscript_token{##1}
    \peek_catcode_remove:NTF \c_math_subscript_token
    { \use:c {\cs_to_str:N #1_three:n} }
    { \c_math_subscript_token{#3} }
  }

  \cs_new:cpn {\cs_to_str:N #1_two:n} ##1
  { {#2}\c_math_subscript_token{#3\l_@@_sub_separator_tl ##1} }

  \cs_new:cpn {\cs_to_str:N #1_three:n} ##1
  { \c_math_subscript_token{#3\l_@@_sub_separator_tl ##1} }

  \NewDocumentCommand{#1}{}
```

```
  {% @branch
    \peek_catcode_remove:NTF \c_math_superscript_token
    { \use:c {\cs_to_str:N #1_one:n} }
    { \peek_catcode_remove:NTF \c_math_subscript_token
      { \use:c {\cs_to_str:N #1_two:n} }
      { {#2}\c_math_subscript_token{#3} }
    }
  }
}
\NewDocumentCommand{\RenewSubscriptedSymbol}{m m m}
{
  \@@_check_definable:nN {#1} \RenewSubscriptedSymbol
  \cs_if_exist:NF #1
  { \PackageError{thermodynamics}
      {Command~'\tl_trim_spaces:o {\tl_to_str:n {#1}}'~not~defined}
      {You~have~used~
       '\tl_trim_spaces:o {\tl_to_str:n {\RenewSubscriptedSymbol}}'~
       with~a~command~that~does~not~have~a~definition}
  }
  \cs_set:cpn {\cs_to_str:N #1_one:n} ##1
  {
    {#2}\c_math_superscript_token{##1}
    \peek_catcode_remove:NTF \c_math_subscript_token
    { \use:c {\cs_to_str:N #1_three:n} }
    { \c_math_subscript_token{#3} }
  }

  \cs_set:cpn {\cs_to_str:N #1_two:n} ##1
  { {#2}\c_math_subscript_token{#3\l_@@_sub_separator_tl ##1} }

  \cs_set:cpn {\cs_to_str:N #1_three:n} ##1
  { \c_math_subscript_token{#3\l_@@_sub_separator_tl ##1} }

  \RenewDocumentCommand{#1}{}
  {% @branch
    \peek_catcode_remove:NTF \c_math_superscript_token
    { \use:c {\cs_to_str:N #1_one:n} }
    { \peek_catcode_remove:NTF \c_math_subscript_token
      { \use:c {\cs_to_str:N #1_two:n} }
      { {#2}\c_math_subscript_token{#3} }
    }
  }
}
```

\NewSuperscriptedSymbol

```
\NewDocumentCommand{\NewSuperscriptedSymbol}{m m m}
{
  \@@_check_definable:nN {#1} \NewSuperscriptedSymbol
  \cs_if_exist:NT #1
  { \PackageError{thermodynamics}
      {Command~'\tl_trim_spaces:o {\tl_to_str:n {#1}}'~already~defined}
      {You~have~used~
       '\tl_trim_spaces:o {\tl_to_str:n {\NewSuperscriptedSymbol}}'~
       with~a~command~that~already~has~a~definition}
  }
  \cs_new:cpn {\cs_to_str:N #1_one:n} ##1
```

```
  {
    {#2}\c_math_subscript_token{##1}
    \peek_catcode_remove:NTF \c_math_superscript_token
    { \use:c {\cs_to_str:N #1_three:n} }
    { \c_math_superscript_token{#3} }
  }

  \cs_new:cpn {\cs_to_str:N #1_two:n} ##1
  { {#2}\c_math_superscript_token{#3\l_@@_super_separator_tl ##1} }

  \cs_new:cpn {\cs_to_str:N #1_three:n} ##1
  { {#2}\c_math_superscript_token{#3\l_@@_super_separator_tl ##1} }

  \NewDocumentCommand{#1}{}
  {
    \peek_catcode_remove:NTF \c_math_subscript_token
    { \use:c {\cs_to_str:N #1_one:n} }
    { \peek_catcode_remove:NTF \c_math_superscript_token
      { \use:c {\cs_to_str:N #1_two:n} }
      { {#2}\c_math_superscript_token{#3} }
    }
  }
}
\NewDocumentCommand{\RenewSuperscriptedSymbol}{m m m}
{
  \@@_check_definable:nN {#1} \RenewSuperscriptedSymbol
  \cs_if_exist:NF #1
  { \PackageError{thermodynamics}
      {Command~'\tl_trim_spaces:o {\tl_to_str:n {#1}}'~not~defined}
      {You~have~used~
       '\tl_trim_spaces:o {\tl_to_str:n {\RenewSuperscriptedSymbol}}'~
       with~a~command~that~does~not~have~a~definition}
  }
  \cs_set:cpn {\cs_to_str:N #1_one:n} ##1
  {
    {#2}\c_math_subscript_token{##1}
    \peek_catcode_remove:NTF \c_math_superscript_token
    { \use:c {\cs_to_str:N #1_three:n} }
    { \c_math_superscript_token{#3} }
  }

  \cs_set:cpn {\cs_to_str:N #1_two:n} ##1
  { {#2}\c_math_superscript_token{#3\l_@@_super_separator_tl ##1} }

  \cs_set:cpn {\cs_to_str:N #1_three:n} ##1
  { \c_math_superscript_token{#3\l_@@_super_separator_tl ##1} }

  \RenewDocumentCommand{#1}{}
  {% @branch
    \peek_catcode_remove:NTF \c_math_subscript_token
    { \use:c {\cs_to_str:N #1_one:n} }
    { \peek_catcode_remove:NTF \c_math_superscript_token
      { \use:c {\cs_to_str:N #1_two:n} }
      { {#2}\c_math_superscript_token{#3} }
    }
  }
```

```
}
\cs_new:Nn \@@_subscripted_and_superscripted_core:nnnn
{
  \cs_set:cpn {\cs_to_str:N #1_one:n} ##1
  {
    {#2}\c_math_superscript_token{##1}
    \peek_catcode_remove:NTF \c_math_subscript_token
    { \use:c {\cs_to_str:N #1_three:n} }
    { \c_math_subscript_token{#3} }
  }
  \cs_set:cpn {\cs_to_str:N #1_two:n} ##1
  {
    {#2}\c_math_subscript_token{#3 ##1}
    \peek_catcode_remove:NTF \c_math_superscript_token
    { \use:c {\cs_to_str:N #1_four:n} }
    { \c_math_superscript_token{#4 \bullet} }
  }
  \cs_set:cpn {\cs_to_str:N #1_three:n} ##1
  { \c_math_subscript_token{#3 ##1} }
  \cs_set:cpn {\cs_to_str:N #1_four:n} ##1
  { \c_math_superscript_token{#4 ##1} }
}
\NewDocumentCommand{\NewSubscriptedandSuperscriptedSymbol}{m m m m}
{
  \@@_check_definable:nN {#1} \NewSubscriptedandSuperscriptedSymbol
  \cs_if_exist:NT #1
  { \PackageError{thermodynamics}
      {Command~'\tl_trim_spaces:o {\tl_to_str:n {#1}}'~already~defined}
      {You~have~used~
       '\tl_trim_spaces:o
          {\tl_to_str:n {\NewSubscriptedandSuperScriptedSymbol}}'~
           with~a~command~that~already~has~a~definition}
  }
  \@@_subscripted_and_superscripted_core:nnnn {#1} {#2} {#3} {#4}
  \NewDocumentCommand{#1}{}
  {
    \peek_catcode_remove:NTF \c_math_superscript_token
    { \use:c {\cs_to_str:N #1_one:n} }
    { \peek_catcode_remove:NTF \c_math_subscript_token
      { \use:c {\cs_to_str:N #1_two:n} }
      { {#2}\c_math_subscript_token{#3}\c_math_superscript_token{#4} }
    }
  }
}
%^^A FIXME what is going on here?!?
\NewDocumentCommand{\RenewSubscriptedandSuperscriptedSymbol}{m m m m}
{
  \@@_check_definable:nN {#1} \RenewSubscriptedandSuperscriptedSymbol
%^^A  \cs_if_exist:NF #1
%^^A  { \PackageError{thermodynamics}
%^^A      {Command~'\tl_trim_spaces:o {\tl_to_str:n {#1}}'~not~already~defined}
%^^A      {You~have~used~
%^^A       '\tl_trim_spaces:o
%^^A          {\tl_to_str:n {\RenewSubscriptedandSuperScriptedSymbol}}'~
%^^A           with~a~command~that~does~not~have~a~definition}
%^^A  }
```

```
%^^A  \@@_subscripted_and_superscripted_core:nnnn {#1} {#2} {#3} {#4}
%^^A  \RenewDocumentCommand{#1}{}
%^^A  {
%^^A    \peek_catcode_remove:NTF \c_math_superscript_token
%^^A    { \use:c {\cs_to_str:N #1_one:n} }
%^^A    { \peek_catcode_remove:NTF \c_math_subscript_token
%^^A      { \use:c {\cs_to_str:N #1_two:n} }
%^^A      { {#2}\c_math_subscript_token{#3}\c_math_superscript_token{#4} }
%^^A    }
%^^A  }
}
```

B.9 Symbol Definitions

\heatcapacitysymbol
\compressibilitysymbol
\expansivitysymbol

We define symbols for the heat capacities, compressibilities, and so forth.

```
\NewExpandableDocumentCommand{\heatcapacitysymbol}{}{C}
\NewExpandableDocumentCommand{\compressibilitysymbol}{}{\kappa}
\NewExpandableDocumentCommand{\expansivitysymbol}{}{\alpha}
\NewExpandableDocumentCommand{\JTsymbol}{}{\mu}
```

\cV
\cP

The heat capacities are molar by default; we also declare extensive and specific heat capacities. The heat capacities themselves are defined to be "smart": `\cV_i` will recognize the subscript appropriately and render $C_{V,i}$ rather than C_{Vi} or some other unintended symbol. Superscripts are also handled appropriately and can be in either order.

```
\NewSubscriptedSymbol{\cV}{\@@_intensive:n \heatcapacitysymbol}
    {\g_@@_volume_symbol}
\NewSubscriptedSymbol{\cP}{\@@_intensive:n \heatcapacitysymbol}
    {\g_@@_pressure_symbol}
```

\cVt
\cPt

We also introduce *extensive* (rather than molar) heat capacity macros.

```
\NewSubscriptedSymbol{\cVt}{\@@_extensive:n \heatcapacitysymbol}
    {\g_@@_volume_symbol}
\NewSubscriptedSymbol{\cPt}{\@@_extensive:n \heatcapacitysymbol}
    {\g_@@_pressure_symbol}
```

\cVs
\cPs

`\cPs` and `\cVs` are the specific heat capacities.

```
\NewSubscriptedSymbol{\cVs}{\@@_specific:n \heatcapacitysymbol}
    {\g_@@_volume_symbol}
\NewSubscriptedSymbol{\cPs}{\@@_specific:n \heatcapacitysymbol}
    {\g_@@_pressure_symbol}
```

\kappaT
\kappaS

The isothermal and adiabatic compressibilities are defined similarly, but those do not have extensive versions for obvious reasons.

```
\NewSubscriptedSymbol{\kappaT}{\compressibilitysymbol}
    {\g_@@_temperature_symbol}
\NewSubscriptedSymbol{\kappaS}{\compressibilitysymbol}
    {\g_@@_entropy_symbol}
```

\alphaP
\alphaS

The macro `\alphaP` is intended to refer to the isobaric volume expansivity, while `\alphaS` is the isentropic volume expansivity.

```
\NewSubscriptedSymbol{\alphaP}{\expansivitysymbol}{\g_@@_pressure_symbol}
\NewSubscriptedSymbol{\alphaS}{\expansivitysymbol}{\g_@@_entropy_symbol}
```

\muJT The macro \muJT renders the Joule–Thomson coefficient.

```
\NewSubscriptedSymbol{\muJT}{\JTsymbol}{\text{JT}}
```

\Psat The \Psat macro (and its clone, the \Pvap macro) should be used for the saturation
\Pvap pressure. Similarly, a \phisat macro typesets the fugacity coefficient at saturation.
\phisat The \fsat macro similarly renders the fugacity at saturation. Other saturation prop-
\fsat erties should use M^\sat or similar, preferably by defining another macro such as
\sat \Gmsat.

```
\NewDocumentCommand{\sat}{}{{\text{sat}}}
\NewDocumentCommand{\Psat}{}{P\c_math_superscript_token\sat}
\NewDocumentCommand{\Pvap}{}{\Psat}
\NewDocumentCommand{\phisat}{}{\phi\c_math_superscript_token\sat}
\NewDocumentCommand{\fsat}{}{\fpure\c_math_superscript_token\sat}
```

\std The \std macro denotes standard properties. \Pstd, \Cstd, \fstd, and \mustd are
\Pstd defined for convenience and for consistency across textbooks.
\fstd
\Cstd
\mustd

```
\NewDocumentCommand{\std}{}{\circ}
\NewDocumentCommand{\Pstd}{}{P\c_math_superscript_token \std}
\NewDocumentCommand{\Cstd}{}{C\c_math_superscript_token \std}
\NewDocumentCommand{\fstd}{}{f\c_math_superscript_token \std}
\NewDocumentCommand{\mustd}{}{\mu\c_math_superscript_token \std}
```

\xrxn The \xrxn macro denotes the extent of reaction.

```
\NewDocumentCommand{\xrxn}{}{\xi}
```

\fmix The \fmix command is intended to describe fugacities in mixtures. It renders as $\hat{f}$ by default, and would be used as \fmix_i or the like, producing $\hat{f}_i$; some authors like to use $\bar{f}_i$ or just f_i, and this command creates a consistent way to change between such options.

```
\NewDocumentCommand{\fmix}{}{\hat{f}}
```

\phimix A similar command, \phimix, renders $\hat{\phi}$ by default to represent the fugacity coefficient in a mixture.

```
\NewDocumentCommand{\phimix}{}{\hat\phi}
```

\fpure The \fpure command is intended to describe fugacities in pure substances. It renders as f by default, and would be used as \fpure or \fpure_i or the like, producing f_i; some authors like to use $f_{\text{pure}\,i}$, and others like to use $f_i^\bullet$; this command creates a consistent way to change between the these options. A similar command for ϕ is given, \phipure, for fugacity coefficients.

```
\NewDocumentCommand{\fpure}{}{f}
\NewDocumentCommand{\phipure}{}{\phi}
```

\actabs The \actabs and \actrel macros are intended to standardize the macro for the
\actrel absolute and relative activities, respectively, across textbooks. The defaults are λ and a, respectively.

```
\NewExpandableDocumentCommand{\actabs}{}{\lambda}
\NewExpandableDocumentCommand{\actrel}{}{a}
```

B.9.1 Property Changes

\Deltamix
\mixing

Mixing properties, such as ΔG_{mix}, should be accessed using `\Deltamix\Gm` and similar constructions—this construct will typeset as $\Delta_{MIX}G$ using the `Thompson` package option, for example, and as $\Delta_{\text{mix}}\underline{G}$ using the `Sandler` package option.

```
\NewDocumentCommand{\mixing}{}{{\text{mix}}}
\NewDocumentCommand{\Deltamix}{m}
    {\Delta{#1}\c_math_subscript_token\mixing}
```

\formation
\fusion
\reaction
\sublimation
\vaporization

Macros for subscripts/superscripts on property changes,

```
\NewDocumentCommand{\formation}{}{f}
\NewDocumentCommand{\fusion}{}{{\text{fus}}}
\NewDocumentCommand{\reaction}{}{{\text{rxn}}}
\NewDocumentCommand{\sublimation}{}{{\text{sub}}}
\NewDocumentCommand{\vaporization}{}{{\text{vap}}}
```

\Deltafus
\Deltasub
\Deltavap
\Deltarxn

and similar macros for the property changes themselves. Some of these may be redefined by package options that select a particular textbook.

```
\NewDocumentCommand{\Deltafus}{m}
    {\Delta #1\c_math_superscript_token\fusion}
\NewDocumentCommand{\Deltasub}{m}
    {\Delta #1\c_math_superscript_token\sublimation}
\NewDocumentCommand{\Deltavap}{m}
    {\Delta #1\c_math_superscript_token\vaporization}
\NewDocumentCommand{\Deltarxn}{m}
{
  \cs_set:Npn \@@_Deltarxn_one ##1
  {
      \Delta #1\c_math_subscript_token{\reaction,##1}
  }
  \peek_catcode_remove:NTF \c_math_subscript_token
  {
    \@@_Deltarxn_one
  }
  {
    \Delta #1\c_math_subscript_token{\reaction}
  }
}
\tl_new:N \l_@@_Deltaf_sym_tl
\NewSubscriptedSymbol{\@@_Deltaf}{\l_@@_Deltaf_sym_tl}{\formation}
\NewDocumentCommand{\Deltaf}{m}
{ \tl_set:Nn \l_@@_Deltaf_sym_tl {\Delta #1}
  \@@_Deltaf
}
```

B.9.2 Partial Molar Quantities

\partialmolar

Partial molar quantities with superscripts appear as $\overline{G_i^{\text{IG}}}$ or $\overline{G_i^R}$ (or, with the `shortpm` option, as $\overline{G}_i^{\text{IG}}$ or $\overline{G}_i^R$), rather than something like $\overline{G_i^{\text{IG}}}$ or $\overline{G_i^R}$; the former looks better but is harder to implement for obvious reasons. Their definitions allow them to be used as symbols, something like `\Gpm_i`, `\Gpm^{\IGM}_i`, `\Gpm^{\IGM}_i`, and even `\Gpm_i^{\IGM}`; they can also be treated as commands: `\Gpm{i}` is equivalent to `\Gpm_i` and `\Gpm[\IGM]{i}` is equivalent to `\Gpm_i^{\IGM}`. The macro `\partialmolar` can be used to create an arbitrary partial molar symbol.

```
\tl_new:N \l_@@_pm_symbol_tl
\tl_new:N \l_@@_pm_arg_tl
\NewDocumentCommand{\partialmolar}{m}
{
  \tl_set:Nn \l_@@_pm_symbol_tl {#1}
  \@@_generic_pm:
}
%% cases to consider:
%% (1) \Mpm{i}
%% (2) \Mpm[S]{i}
%% (3) \Mpm^S_i
%% (4) \Mpm_i^S
%% (5) \Mpm_i
%% note that \Mpm^S with no subscript makes no sense and is thus forbidden
\cs_new:Nn \@@_generic_pm:
{
  \peek_catcode_remove:NTF \c_math_subscript_token
  {% case 4 or case 5
    \@@_pm_case_four_or_five
  }
  {% look for superscript token
    \peek_catcode_remove:NTF \c_math_superscript_token
    {% case 3: \Mpm^{#1}_{#2} or \Mpm^{#1}{#2}
      \@@_pm_case_three
    }
    {% Look for optional argument [...]
      \peek_charcode:NTF [
      {% case 2: \Mpm[S]{i}
        \@@_pm_case_two
      }
      {% case 1: \Mpm{i}
        \@@_pm_case_one
      }
    }
  }
}
\cs_new:Npn \@@_pm_case_one #1
{
  \bool_if:NTF \l_@@_longpm_bool
  { \@@_overline:n {\l_@@_pm_symbol_tl\c_math_subscript_token{#1}} }
  {
    \@@_overline:n {\l_@@_pm_symbol_tl}\c_math_subscript_token{#1}
  }
}
\cs_new:Npn \@@_pm_case_two [#1]#2
{
  \bool_if:NTF \l_@@_longpm_bool
  {  \@@_overline:n {\l_@@_pm_symbol_tl
       \c_math_superscript_token{#1}\c_math_subscript_token{#2}}
  }
  {  \@@_overline:n {\l_@@_pm_symbol_tl}
       \c_math_superscript_token{#1}\c_math_subscript_token{#2}
  }
}
\cs_new:Npn \@@_pm_case_three #1
{
```

```
  \tl_set:Nn \l_@@_pm_arg_tl {#1}
  \peek_catcode_remove:NTF \c_math_subscript_token
  { \@@_pm_case_three_part_two }
  { \@@_pm_case_three_part_two }
}
\cs_new:Npn \@@_pm_case_three_part_two #1
{
  \bool_if:NTF \l_@@_longpm_bool
  { \@@_overline:n {\l_@@_pm_symbol_tl
      \c_math_superscript_token{\l_@@_pm_arg_tl}
      \c_math_subscript_token{#1}}
  }
  { \@@_overline:n {\l_@@_pm_symbol_tl}
      \c_math_superscript_token{\l_@@_pm_arg_tl}
      \c_math_subscript_token{#1}
  }
}
\cs_new:Npn \@@_pm_case_four_or_five #1
{
  \tl_set:Nn \l_@@_pm_arg_tl {#1}
  \peek_catcode_remove:NTF \c_math_superscript_token
  { \@@_pm_case_four }
  { \@@_pm_case_five }
}
\cs_new:Npn \@@_pm_case_four #1
{
  \bool_if:NTF \l_@@_longpm_bool
  { \@@_overline:n {\l_@@_pm_symbol_tl\c_math_superscript_token{#1}
      \c_math_subscript_token{\l_@@_pm_arg_tl}}
  }
  { \@@_overline:n {\l_@@_pm_symbol_tl}\c_math_superscript_token{#1}
      \c_math_subscript_token{\l_@@_pm_arg_tl}
  }
}
\cs_new:Npn \@@_pm_case_five
{
  \bool_if:NTF \l_@@_longpm_bool
  { \@@_overline:n {\l_@@_pm_symbol_tl
      \c_math_subscript_token{\l_@@_pm_arg_tl}}
  }
  { \@@_overline:n {\l_@@_pm_symbol_tl}
      \c_math_subscript_token{\l_@@_pm_arg_tl}
  }
}
```

B.9.3 Thermodynamic Property Definitions

These macros define the user interface to the symbols for energy, volume, and so forth. There are five commands that define thermodynamic properties.

`\NewExtensiveProperty` The command `\NewExtensiveProperty` declares macros for a total, molar, and specific version of the symbol; for example, a second heat-like property could be defined via

```
\NewExtensiveProperty{R}{\mathcal{Q}}
```

The command above would declare the macros `\Rt`, `\Rm`, and `\Rs` that expand to $\underline{\mathcal{Q}}$, $\mathcal{Q}$, and $\hat{\mathcal{Q}}$, respectively, using the default package options.

\NewPartialMolarProperty The command \NewPartialMolarProperty declares a macro for the partial molar quantity. For example,

```
\NewPartialMolarProperty{I}{\Psi}
```

would create the command \Ipm, which would typeset a partial molar command with the base symbol Ψ, yielding $\overline{\Psi}_i$.

\NewThermodynamicProperty Declaring a new potential is handled by the \NewThermodynamicProperty macro, which takes two arguments. The first is the base of the name, and the second is the base of the symbol. This declares four new commands for the extensive, molar, specific, and partial molar properties. These commands consist of the first argument followed by t, m, s, and pm, respectively. For example, one might define the entropy via

```
\NewThermodynamicProperty{S}{S}
```

and it would define the macros \St, \Sm, \Ss, and \Spm that yield, respectively, $\underline{S}$, S, $\hat{S}$, and $\overline{S}_i$ (assuming the subscript to the partial molar quantity was i). It would also declare residual and excess properties for that base symbol. Note that the actual definition of the entropy and the other standard properties is slightly more complicated so as to allow for different symbols to be used in different textbooks.

```
\NewDocumentCommand{\NewThermodynamicProperty}{m m}
{
  \NewExtensiveProperty{#1}{#2}
  \NewPartialMolarProperty{#1}{#2}
  \NewResidualProperty{#1}{#2}
  \NewExcessProperty{#1}{#2}
}
\ProvideDocumentCommand{\NewExtensiveProperty}{m m}
{
  % Extensive property
  \exp_after:wN \NewDocumentCommand \exp_after:wN
    {\cs:w #1t\cs_end:}{}{\@@_extensive:n {#2}}
  % Molar property
  \exp_after:wN \NewDocumentCommand \exp_after:wN
    {\cs:w #1m\cs_end:}{}{\@@_intensive:n {#2}}
  % Specific property
  \exp_after:wN \NewDocumentCommand \exp_after:wN
    {\cs:w #1s\cs_end:}{}{\@@_specific:n {#2}}
}
\NewDocumentCommand{\NewPartialMolarProperty}{m m}
{
  % Partial molar property
  \exp_after:wN \NewDocumentCommand \exp_after:wN
    {\cs:w #1pm\cs_end:}{}{\partialmolar{#2}}
}
\ProvideDocumentCommand{\NewExcessProperty}{m m}
{
  \exp_after:wN \NewSuperscriptedSymbol \exp_after:wN
    {\cs:w #1 Et\cs_end:}{\@@_extensive:n{#2}}{\excess}
  \exp_after:wN \NewSuperscriptedSymbol \exp_after:wN
    {\cs:w #1 E\cs_end:}{\@@_intensive:n{#2}}{\excess}
  \exp_after:wN \NewSuperscriptedSymbol \exp_after:wN
    {\cs:w #1 Es\cs_end:}{\@@_specific:n{#2}}{\excess}

```

```
  % Excess partial molar property
  \exp_after:wN \NewDocumentCommand \exp_after:wN
    {\cs:w #1Epm\cs_end:}{}{\partialmolar{#2}
       \c_math_superscript_token\excess}
}
\ProvideDocumentCommand{\NewResidualProperty}{m m}
{
  \exp_after:wN \NewSuperscriptedSymbol \exp_after:wN
    {\cs:w #1 Rt\cs_end:}{\@@_extensive:n{#2}}{\residual}
  \exp_after:wN \NewSuperscriptedSymbol \exp_after:wN
    {\cs:w #1 R\cs_end:}{\@@_intensive:n{#2}}{\residual}
  \exp_after:wN \NewSuperscriptedSymbol \exp_after:wN
    {\cs:w #1 Rs\cs_end:}{\@@_specific:n{#2}}{\residual}

  % Residual partial molar property
  \exp_after:wN \NewDocumentCommand \exp_after:wN
    {\cs:w #1Rpm\cs_end:}{}{\partialmolar{#2}
        \c_math_superscript_token\residual}
}
```

\Nt \Et \Em \Es \Epm

We define \Nt as the number of moles, as that changes between books a lot, but it does not have extensive, molar, and specific equivalents. Heat and work are defined, but lack partial molar properties. Area does not have excess or residual properties.

```
\NewDocumentCommand{\Nt}{}{\g_@@_mole_symbol}
\NewThermodynamicProperty{E}{\g_@@_total_energy_symbol}
\NewThermodynamicProperty{U}{\g_@@_internal_energy_symbol}
\NewThermodynamicProperty{F}{\g_@@_Helmholtz_symbol}
\NewThermodynamicProperty{G}{\g_@@_Gibbs_symbol}
\NewThermodynamicProperty{H}{\g_@@_enthalpy_symbol}
\NewThermodynamicProperty{L}{\g_@@_Landau_symbol}
\NewThermodynamicProperty{V}{\g_@@_volume_symbol}
\NewThermodynamicProperty{S}{\g_@@_entropy_symbol}
\NewExtensiveProperty{A}{\g_@@_area_symbol}
\NewPartialMolarProperty{A}{\g_@@_area_symbol}
\NewExtensiveProperty{Q}{\g_@@_heat_symbol}
\NewExtensiveProperty{W}{\g_@@_work_symbol}
```

\cVpm \cPpm

Partial molar heat capacities are *hard*, but the following implementation seems to work flawlessly. . . so far.

```
\NewPartialMolarProperty{cP}{\cP}
\NewPartialMolarProperty{cV}{\cV}
\NewSubscriptedSymbol{\cPpmshort}{\@@_overline_copy:n{\heatcapacitysymbol}}
    {\g_@@_pressure_symbol}
\NewSubscriptedSymbol{\cVpmshort}{\@@_overline_copy:n{\heatcapacitysymbol}}
    {\g_@@_volume_symbol}
```

B.9.4 Electrochemistry

\Epot

The \Epot command can be used for the electric potential.

```
\NewExpandableDocumentCommand{\Epot}{}{E}
```

B.9.5 Residual and Excess Properties

\residual \excess

Macros are defined for residual properties (departure from ideal gases) and excess properties (departure from ideal solutions). We begin with two macros to use for

defining generic residual and excess properties that are not already defined.

```
\NewDocumentCommand{\residual}{}{R}
\NewDocumentCommand{\excess}{}{E}
```

\prodall \sumall \summallbutlast

The \sumall macro and its cousin, \sumallbutlast, simplify the typesetting of commonly-used sums; the command \prodall does the same thing for products, viz.,

```
\[ \sumall_i x_i = 1 \qquad \sumallbutlast_i x_i = 1 - x_\ncomponents
    \qquad K = \exp\left(\frac{-\Deltarxn\Gm^\std}{RT}\right)
             = \prodall_i a_i^{\nu_i} \]
```

gives

$$\sum_{i=1}^{C} x_i = 1 \qquad \sum_{i=1}^{C-1} x_i = 1 - x_C \qquad K = \exp\left(\frac{-\Delta G^\circ_{\text{rxn}}}{RT}\right) = \prod_{i=1}^{C} a_i^{\nu_i}$$

```
\NewDocumentCommand{\sumall}{m m}
  { \sum\c_math_subscript_token{#2=1}
      \c_math_superscript_token{\ncomponents} }
\NewDocumentCommand{\sumallbutlast}{m m}
  { \sum\c_math_subscript_token{#2=1}
      \c_math_superscript_token{\ncomponents-1} }
\NewDocumentCommand{\prodall}{m m}
  { \prod\c_math_subscript_token{#2=1}
      \c_math_superscript_token{\ncomponents} }
```

\IG \IGM \IS

The \IG, \IGM, and \IS macros (meaning "ideal gas," "ideal gas mixture," and "ideal solution," respectively) should be used to make clean transitions between textbooks—some use "IM" or "ID" rather than "IS," for example.

```
\NewDocumentCommand{\IG}{}{{\text{IG}}}
\NewDocumentCommand{\IGM}{}{{\text{IGM}}}
\NewDocumentCommand{\IS}{}{{\text{IS}}}
```

B.9.6 Henry's Law Constants and Activity Coefficients

\Henryrat \Henrymol

The Henry's Law constants for the rational basis ($y_i P = x_i h_i$) and the molal basis ($y_i P = C_i \mathcal{H}_i$) are given by the macros \Henryrat and \Henrymol, respectively. Using them this way consistently allows for easy switching back and forth.

```
\NewDocumentCommand{\Henryrat}{}{h}
\NewDocumentCommand{\Henrymol}{}{\mathcal{H}}
```

\gammait \muit \gammarat \gammamol

The ordinary activity coefficient is typically denoted γ or γ, so the base symbol will still be \gamma. The macro \gammait is defined just in case \gamma is redefined by a package option. However, symbols for the Henry's Law activity coefficients are far from universal, so I have defined macros to make their use consistent. The defaults render \gammarat as γ^* and \gammamol as $\gamma^\square$. \gammamol will use \square from packages if it is defined; if not, it "fakes it" with the definition below. The symbol for the chemical potential is \mu, but \muit is defined so the symbol is still available, should \mu be redefined later.

```
\cs_gset_eq:NN \gammait \gamma
\cs_gset_eq:NN \muit \mu
\AtBeginDocument{%
  \ProvideDocumentCommand{\square}{}{%
```

```
    \text{\leavevmode
      \hbox to.65em{%
      \hfil\vrule
      \vbox to.53em{\hrule width.45em\vfil\hrule}%
      \vrule\hfil}%
    }%
  }%
}
\NewDocumentCommand{\gammarat}{}{\gamma\c_math_superscript_token\ast}
\NewDocumentCommand{\gammamol}{}{\gamma\c_math_superscript_token\square}
```

B.10 Jacobians

`thermovmatrix` (*env.*) This is a non-user-interface wrapper environment used to detect, in effect, whether amsmath has been loaded. If so, it uses its `vmatrix` environment for Jacobians; if not, it fakes it with `array` (which does not look nearly as good).

```
\NewDocumentEnvironment{thermovmatrix}{}
{ \cs_if_exist:NTF \vmatrix
  { \begin{vmatrix} }
  { \left|\begin{array}{c c c c c c c c c c} }
}
{ \cs_if_exist:NTF \endvmatrix
  {  \end{vmatrix} }
  {  \end{array}\right| }
}
```

`thermobmatrix` (*env.*) This is a non-user-interface wrapper environment used to detect, in effect, whether amsmath has been loaded. If so, it uses its `bmatrix` environment for Jacobians; if not, it fakes it with `array` (which does not look nearly as good).

```
\NewDocumentEnvironment{thermobmatrix}{}
{ \cs_if_exist:NTF \pmatrix
  { \begin{bmatrix} }
  { \left[\begin{array}{c c c c c c c c c c} }
}
{ \cs_if_exist:NTF \endpmatrix
  {  \end{bmatrix} }
  {  \end{array}\right] }
}
```

`thermopmatrix` (*env.*) This is a non-user-interface wrapper environment used to detect, in effect, whether amsmath has been loaded. If so, it uses its `pmatrix` environment for Jacobians; if not, it fakes it with `array` (which does not look nearly as good).

```
\NewDocumentEnvironment{thermopmatrix}{}
{ \cs_if_exist:NTF \pmatrix
  { \begin{pmatrix} }
  { \left(\begin{array}{c c c c c c c c c c} }
}
{ \cs_if_exist:NTF \endpmatrix
  {  \end{pmatrix} }
  {  \end{array}\right) }
}
```

`Jacobian` The `\Jacobian` command typesets the Leibnitz notation for the Jacobian determinant.

```
\NewDocumentCommand{\Jacobian}{m m}
    {\@@_frac:nn{\partial(#1)}{\partial{(#2)}}}
```

`Jacobianpmatrix` The `\Jacobianpmatrix` macro typesets the Jacobian matrix with parentheses.

```
\NewDocumentCommand{\Jacobianpmatrix}{O{} O{} m m}
{
  \@@_Jacobian_set_ncomponents:nn {#3} {#4}
  \begin{thermopmatrix}
    \@@_Jacobianmatrix:nnnn {#1} {#2} {#3} {#4}
  \end{thermopmatrix}
}
```

`Jacobianbmatrix` The `\Jacobianbmatrix` macro typesets the Jacobian matrix with brackets.

```
\NewDocumentCommand{\Jacobianbmatrix}{O{} O{} m m}
{
  \@@_Jacobian_set_ncomponents:nn {#3} {#4}
  \begin{thermobmatrix}
    \@@_Jacobianmatrix:nnnn {#1} {#2} {#3} {#4}
  \end{thermobmatrix}
}
```

`\Jacobiandet` Similarly, the `\Jacobiandet` macro typesets the actual determinant that the Jacobian notation represents.

```
\NewDocumentCommand{\Jacobiandet}{O{} O{} m m}
{
  \@@_Jacobian_set_ncomponents:nn {#3} {#4}
  \begin{thermovmatrix}
    \@@_Jacobianmatrix:nnnn {#1} {#2} {#3} {#4}
  \end{thermovmatrix}
}
\seq_new:N \l_@@_row_seq
\seq_new:N \l_@@_matrix_seq
\clist_new:N \l_@@_other_vars_clist
\clist_new:N \l_@@_other_vars_copy_clist
\tl_new:N \l_@@_Jacobian_x_tl
\tl_new:N \l_@@_Jacobian_n_tl
\tl_new:N \l_@@_Jacobian_temp_tl
\bool_new:N \l_@@_found_dots_bool
\cs_new:Nn \@@_Jacobian_set_ncomponents:nn
{
  % If any entry is \dots, we assume the Jacobian is of the form
  % d(f_1,\dots,f_n)/d(x_1,\dots,x_n) where f is some function
  % (any symbol) and x is some variable (any symbol).
  \tl_if_in:nnTF {#1} {\dots}
  {% Has dots
    \bool_set_true:N \l_@@_found_dots_bool
    % look for what "x" is
    \tl_set:Nn \l_@@_Jacobian_x_tl {\tl_head:n {#2}}
    % look for what "n" is and set \ncomponents to it
    \tl_set:Nx \l_@@_Jacobian_n_tl {\tl_item:nn {#2} {-1}}
    \RenewExpandableDocumentCommand{\ncomponents}{}{\l_@@_Jacobian_n_tl}
  }
  {% Does not have dots; proceed accordingly
    \bool_set_false:N \l_@@_found_dots_bool
  }
}
\cs_new_protected:Nn \@@_Jacobianmatrix:nnnn
{
  \seq_clear:N \l_@@_matrix_seq
```

```
\clist_set:Nn \l_@@_other_vars_clist {#4}
\clist_set_eq:NN \l_@@_other_vars_copy_clist \l_@@_other_vars_clist

\clist_map_inline:nn {#3}
{
  \seq_clear:N \l_@@_row_seq
  \tl_if_in:nnTF {##1} {\dots}
  {% The current row has "dots" => row is \vdots & \ddots & \vdots
    \seq_put_right:Nn \l_@@_matrix_seq
      { \vdots \c_alignment_token \ddots \c_alignment_token \vdots }
  }
  {% Ordinary row
    \clist_map_inline:nn {#4}
    {
      \tl_if_in:nnTF {####1} {\dots}
      {% this column has "dots" in it
        \seq_put_right:Nn \l_@@_row_seq \dots
      }
      {% Normal column
        \clist_set_eq:NN \l_@@_other_vars_clist
                         \l_@@_other_vars_copy_clist
        \clist_remove_all:Nn \l_@@_other_vars_clist {####1}
        \bool_if:NTF \l_@@_found_dots_bool
        { \tl_set:Nn \l_@@_Jacobian_temp_tl {\tl_item:nn {####1} {-1}}
          \seq_put_right:Nx \l_@@_row_seq
          {
            #1\Partial{##1}{####1}
                {\allbut{\l_@@_Jacobian_temp_tl}{\l_@@_Jacobian_x_tl}}
          }
        }
        { \seq_put_right:Nx \l_@@_row_seq
          {
            #1\Partial{##1}{####1}
                       {\clist_use:Nn \l_@@_other_vars_clist ,}
          }
        }
      }
    }
    \seq_put_right:Nx \l_@@_matrix_seq
    {
      \seq_use:Nn \l_@@_row_seq { \c_alignment_token }
    }
  }
}
\tl_if_empty:nTF {#2}
{
  \tl_if_eq:nnTF {#1} {\displaystyle}
  { \seq_use:Nn \l_@@_matrix_seq { \\[2.75ex] } }
  { \seq_use:Nn \l_@@_matrix_seq { \\[1.25ex] } }
}
{
  \seq_use:Nn \l_@@_matrix_seq { \\[#2] }
}
}
```

Change History

v1.00

General: Initial public release 1

v1.01

General: Added \Partialinline and friends to facilitate in-line (non-display-mode) partial derivatives, with corresponding changes to \Partial and friends for ease of implementation. Also added \Partialinlinetext and friends for non-expanding delimiters. 54

Changed options with two E or two A variables to use calligraphic letters for the less-common of the two. 27

\allcomponents: Updated \allcomponents to include an optional argument that changes N_i to N_j, say, when using TesterModell or other options that denote moles of all components that way. Similar updates to \allNs and friends. 32

\Partial: Changed \adjust@width 0.1\operator@width (from 2pt). . . 49

Changed \adjust@width to 2pt (up from 1pt). 49

v2.00

General: Added \muJT to represent Joule–Thomson coefficients (which have different notation across textbooks). 6

Added a sorting routine to make function arguments be in a consistent order using the nosubscripts option. 48

Revision to use LaTeX3 (expl3/xparse) syntax layer. 1

Jacobian: Reimplemented \Jacobian to handle an arbitary number of variables and implemented \Jacobiandet to handle the matrix representation of the Jacobian. . . . 69

\NewSubscriptedSymbol: Deleted \DeclareSubscriptedSymbol in favor of xparse-based \NewSubscriptedSymbol and \RenewSubscriptedSymbol. 56

\NewSuperscriptedSymbol: Created \NewSuperscriptedSymbol to handle superscripted excess and residual properties without intervention. 58

\Partial: Changed length added to \l_@@_Partial_const_dim from −0.15 to −0.20. 49

thermoextensiveplain: Added environment to invoke the "extensive-plain" option locally. . 56

thermoextensivesuperscript: Added environment to invoke the "extensive-superscript" option locally. 56

thermointensivelowercase: Added environment to invoke the "intensive-lowercase" option locally. 56

thermointensiveplain: Added environment to invoke the "intensive-plain" option locally. . . 56

thermomolesrange: Added environment to invoke the "moles-range" definitions of \allNs and friends locally. 56

v2.01

\NewSuperscriptedSymbol: Fixed two typos in \NewSuperscriptedSymbol. 58

v2.02

General: Added KlotzRosenberg option. 33

Improved consistency of package options for textbooks and added a table of symbols organized by textbook option. 21

\actrel: Added \actabs and \actrel to make absolute and relative activity symbols consistent. 62

\cPpm: Simplified implementations of partial molar heat capacities that take advantage of \NewPartialMolarProperty and \NewSubscriptedProperty. This fixes the issue of the subscripts being "persistent" after \cPpm is used in a line. Also declared alternative symbols for use with the shortpm option. 67

\Deltarxn: Changed implementation of \Deltarxn to handle subscripts. 63

\Epot: Added \Epot to standardize the electric potential across textbooks for electrochemistry. . . . 67

\muit: Added \muit and \gammait to preserve symbols in case the base

macros are redefined by a package. 68
\mustd: Added \Cstd and \mustd to standardize standard molalities and chemical potentials across textbooks. 62
thermoshortpm: Added "longpm" and "shortpm" options to control how partial molar properties are rendered along with the environments thermolongpm and thermoshortpm to change them locally. 30
\xrxn: Added \xrxn macro to standardize the extent of reaction macro across textbooks. 62
v2.03
General: Changed contact information; typo fixes 1
v2.04
\Partial: Refactored \Partial and friends to avoid having expl3 code inside xparse definitions (which probably was fine, but just to be safe...). 49
v2.05
General: Added \Jacobianbmatrix and \Jacobianpmatrix. 14
\Jacobiandet: Changed second row of \Jacobiandet from \vdots && \vdots to \vdots & \ddots & \vdots 70

Index

Numbers written in italics refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition.

A

\actabs 1820
\actrel 5, 1820
\allbut 13, 267
\allbutlastand 13, 267
\allcomponents 267
\allMs 12, 255
\allMsbut 12, 261
\allmus 12, 255
\allmusbut 12
\allNs 12, 19, 19, 255
\allNsbut 12, 19, 19, 261
\allWs 12, 255
\allWsbut 12, 261
\allXs 12, 19, 255
\allXsbut 12, 19, 261
\allYs 12, 255
\allYsbut 12, 261
\alphaP 5, 6, 1802
\alphaS 5, 6, 1802
\Am 4
\Apm 4
\As 4
\At 4

C

\compressibilitysymbol 5, 1782
\cP 3, 5, 6, 1786
\cPpm 3, 2022
\cPs 3, 1794
\cPt 3, 1790
\Cstd 5, 8, 1810
\cV 3, 5, 6, 1786
\cVpm 3, 2022
\cVs 3, 1794
\cVt 3, 1790

D

\dbar 4, 19
\Deltaf 8
\Deltafus 5, 8, 1830
\Deltamix 5, 8, 1822
\Deltarxn 5, 8, 1830
\Deltasub 5, 8, 1830
\Deltavap 5, 8, 1830

E

\EE 4
\EEpm 4
\EEs 4
\EEt 4
\Em 4, 2009
environments:
thermobar 18, 1504
thermobmatrix 2068
thermobraces 18, 1499
thermobrackets 18, 1494
thermoextensiveplain 16, 1528
thermoextensivesuperscript 16, 1544
thermointensivelowercase . . 16, 1531
thermointensiveplain 16, 1524
thermolongpm 17, 200
thermomolesrange 19, 1521
thermoNOsubscripts 18, 1515

thermoparentheses 18, 1489
thermoplain 18, 1509
thermopmatrix 2077
thermoshortpm 17, 200
thermosubscripts 18, 1518
thermovmatrix 2059
\Epm 4, 2009
\Epot 5, 2028
\ER 4
\ERpm 4
\ERs 4
\ERt 4
\Es 4, 2009
\Et 4, 2009
\excess 9, 2029
\expansivitysymbol 5, 1782

F

\FE 4
\FEpm 4
\FEs 4
\FEt 4
\Fm 4
\fmix 5, 6, 1816
\formation 1825
\Fpm 4
\fpure 5, 6, 1818
\FR 4
\FRpm 4
\FRs 4
\FRt 4
\Fs 4
\fsat 5, 7, 1805
\fstd 5, 8, 1810
\Ft 4
\fusion 5, 1825

G

\gamma 7
\gammait 7, 2045
\gammamol 5, 7, 2045
\gammarat 5, 7, 2045
\GE 4
\GEpm 4
\GEs 4
\GEt 4
\Gm 4
\Gpm 4, 4
\GR 4
\GRpm 4
\GRs 4
\GRt 4
\Gs 4
\Gt 4

H

\HE 4
\heatcapacitysymbol 5, 1782
\Henrymol 5, 7, 2043
\Henryrat 5, 7, 2043
\HEpm 4
\HEs 4
\HEt 4
\Hm 3, 4
\Hpm 3, 4
\HR 4
\HRpm 4
\HRs 4
\HRt 4
\Hs 3, 4
\Ht 3, 4

I

\IG 2040
\IGM 2040
\IS 2040

J

\Jacobian 13, 2086
\Jacobianbmatrix 13, 2095
\Jacobiandet 13, 2102
\Jacobianpmatrix 13, 2088

K

\kappaS 5, 6, 1798
\kappaT 5, 6, 1798

L

\LE 4
\LEpm 4
\LEs 4
\LEt 4
\Lm 4
\Lpm 4
\LR 4
\LRpm 4
\LRs 4
\LRt 4
\Ls 4
\Lt 4

M

\mixing 5, 8, 1822
\mu 6
\muit 6, 2045
\muJT 5, 6, 1804
\mustd 5, 8, 1810

N

\ncomponents 19, 254
\NewExcessProperty 4
\NewExtensiveProperty 4, 1956
\NewPartialMolarProperty 4, 1956
\NewResidualProperty 4

\NewSubscriptedSymbol 1549
\NewSuperscriptedSymbol 1648
\NewThermodynamicProperty 4, 1956
\Nt 4, 2009

P

\Partial 10, 1222
\Partial* 10
\PartialBigg 11, 1272
\Partialbigg 11, 1279
\PartialClose 81
\PartialEmptyClose 81
\Partialinline 10, 1453
\Partialinlinetext 11, 1468
\PartialMixSecond 10, 1343
\PartialMixSecond* 10
\PartialMixSecondBigg 11, 1426
\PartialMixSecondbigg 11, 1426
\PartialMixSecondinline 10, 1453
\PartialMixSecondinlinetext . 11, 1468
\partialmolar 4, 1856
\PartialOpen 81
\PartialSecond 10, 1286
\PartialSecond* 10
\PartialSecondBigg 11, 1331
\PartialSecondbigg 11, 1337
\PartialSecondinline 10, 1453
\PartialSecondinlinetext 11, 1468
\phimix 5, 6, 1817
\phipure 5, 6
\phisat 5, 7, 1805
\prodall 14, 2031
\Psat 5, 7, 1805
\Pstd 5, 8, 1810
\Pvap 5, 7, 1805

Q

\Qm 4
\Qs 4
\Qt 4

R

\reaction 5, 1825
\residual 9, 2029

S

\sat 5, 7, 1805
\SE 4
\SEpm 4
\SEs 4
\SEt 4
\Sm 4
\Spm 4
\SR 4
\SRpm 4
\SRs 4
\SRt 4
\Ss 4
\St 4
\std 5, 8, 1810
\sublimation 5, 1825
\sumall 14, 2031
\sumallbutlast 14
\summallbutlast 2031

T

thermobar (env.) 18, 1504
thermobmatrix (env.) 2068
thermobraces (env.) 18, 1499
thermobrackets (env.) 18, 1494
thermoextensiveplain (env.) . . . 16, 1528
thermoextensivesuperscript (env.) 16, 1544
thermointensivelowercase (env.) 16, 1531
thermointensiveplain (env.) . . . 16, 1524
thermolongpm (env.) 17, 200
thermomolesrange (env.) 19, 1521
thermoNOsubscripts (env.) 18, 1515
thermoparentheses (env.) 18, 1489
thermoplain (env.) 18, 1509
thermopmatrix (env.) 2077
thermoshortpm (env.) 17, 200
thermosubscripts (env.) 18, 1518
thermovmatrix (env.) 2059

U

\UE 4, 9
\UEpm 4, 9
\UEs 4, 9
\UEt 4, 9
\Um 3, 4
\Upm 3, 4
\UR 4, 9
\URpm 4, 9
\URs 4, 9
\URt 4, 9
\Us 4
\Ut 3, 4

V

\vaporization 5, 1825
\Vpm 3

W

\Wm 4
\Ws 4
\Wt 4

X

\xrxn 5, 1815